

2 W

DC-12.4GHz


SMA

COAXIAL ATTENUATOR

issue  
28. jul. 93

Page  
1 / 1

**DRAWING**



General tolerances: +/- 0.5 mm

**R F CHARACTERISTICS**

FREQUENCY RANGE : DC - 12.4 GHz  
 IMPEDANCE : 50 Ohms  
 ATTENUATION - NOMINAL : 50 dB

FREQUENCY	DC- 4 GHz	4 -12.4GHz
V.S.W.R	<= 1.15	<= 1.25
DEVIATION (dB)	+2 / -2	+2 / -2

TEMPERATURE SENSITIVITY :  $4 \times 10^{-4}$  dB / dB \* °C

PEAK POWER at 25°C (1µs,1%.) : 100 W


AVERAGE POWER at 25°C : 2 W

**MECHANICAL CHARACTERISTICS**

CONNECTORS : SMA male/female per MIL-C 39012  
 WEIGHT : < 10 g

**ENVIRONMENTAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE (°C) : -55 , +125  
 STORAGE TEMPERATURE RANGE (°C) : -55 , +125



QUALITY Dpt app.  
 CREATION  
 PEN : CAT  
 EP :  
 Nom : KL  
 Date : 11. apr. 91

28. jul. 93	New format	VE
ISSUE	REVISIONS	NAME

**RADIALL®**

101. Philibert Hoffmann - Z.I Ouest -  
 93116 ROSNY/BOIS Cedex-FRANCE  
 Phone: 33.1.49353535  
 Fax : 33.1.48546363  
 Twx RADIA 235220F

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.