THE RICOH AFICIO CL3000 COLOR LASER PRINTER



Color Printer The color printer you can't afford not to have...

Workgroup Performance on the Desktop

Ricoh's Aficio CL3000 brings the performance of a workgroup printer in the same footprint as a desktop-at a fraction of the price.

- An amazing 16.9 ppm color and 21 ppm black & white output. Even better, automatic duplex printing has no impact on throughput, while cutting your paper consumption and filing requirements in half!
- A First Page Out time of less than 15.5 seconds for both color and black & white means less waiting between documents.

All the Right Connections for the Ultimate Workflow

Unlike other printers in its class, you won't need any additional options to connect your CL3000. It comes ready to integrate with your network right out of the box, with an auto-switching 10/100 BaseTX network interface and support for all the major protocols. There's also a USB port (1.1 and 2.0), an increasingly popular interface for the mobile workforce, and a bi-directional parallel port for direct connection to a workstation or print server.

• For the ultimate in accessibility, take advantage of the CL3000's wireless options. Choose between IEEE 802.11b and Bluetooth to position the CL3000 anywhere in the office and transparent support for visiting telecommuters and other users.

- If you generate complex color graphics, the optional IEEE 1394 port offers transfer speeds of up to 400 Mbps and saves precious network bandwidth. This option also enables visiting laptop users to plug in and print without rebooting.
- The Aficio CL3000 offers seamless compatibility with computers running Windows, Macintosh, and UNIX operating systems, and comes with three page description languages: Adobe® PostScript® 3™, Ricoh's RPCS, or a PCL5c emulation.

Transforming Old Perceptions with New Economics

Traditionally, high performance, quality and versatility have meant high price. Not with the CL3000: It features a low hardware investment and low cost of operation. While the CL3000 can be a resource for several users, it's affordable enough so that users can even have their own.

- Everything you need to get up and running out of the box is configured with the CL3000. There are no hidden costs or surprises to get into printing production.
- Auto Color Sensing saves money on documents consisting of monochrome and color pages. Only the necessary number of development cycles are used to image each page to minimize operating costs. By contrast, other printers can output all pages in a mixed document at the higher cost of color pages.
- The Aficio CL3000 uses just 10 or less watts of power in EnergySaver mode, saving you money when idle, while the rapid recovery time means virtually no waiting when you're ready to print again.



THE RICOH AFICIO CL3000 COLOR LASER PRINTER

General Specifications

Part# 400832

Controller Options

Configuration:	Desktop
Technology:	Laser-beam scanning, electro-photographic printing with
	mono-component toner development
Resolution:	1,200 x 1,200 dpi, 1,200 x 600 dpi, 600 x 600 dpi (default)
Printing Speed:	21 ppm (black & white), 16.9 ppm (full color) @ 600 x 600 or
	1,200 x 600 dpi); 8 ppm (color or black & white) @ 1,200 x 1,200 dpi,
	Thick Papers/Transparencies: 8 ppm (black & white/full color)
	Duplex Speed: 21 ipm (black & white), 16.9 ipm (full color)
First Print Speed:	15.5 seconds
Dimensions (W x D x H):	16.5" x 21.1"x 15.5" (419 x 536 x 395mm)
Weight:	68.3 lbs. (31kg)
Input Capacity:	Bypass Tray: 100 sheets
	Standard Tray: 530 sheets
	Up to 1,690 sheet total capacity
Output Capacity:	250 sheets face up
Paper Sizes:	Trays: 8.5" x 11"; 8.5" x 14"; A4; B5
	Bypass Tray: 3.56" x 5.85" (min.); 7.25" x 10.5"; 8" x 13"; 8.5" x 14"
	(90 x 148 to 216 x 356mm min./max.)
Paper Weight:	Trays: 16 to 28 lb. Bond (60 to 105g/m ²)
	Bypass tray: 20 to 44 lb. Bond (64 to 165g/m ²)
Paper Types:	Plain paper, Laser-printer qualified transparencies, card stock,
	labels, envelopes
Duplex Printing:	Optional
Warm-up Time:	Less than 30 seconds
Power Consumption:	1,300W or less
	Energy Saver Mode: 10W or less

Controller Specifications

CPU:	RM7065 400 MHz
Printer Languages:	Adobe PostScript 3, PCL 5c emulation, Ricoh RPCS
Fonts:	For Adobe PostScript 3: 136 Type 1 fonts
	For PCL5c: 35 Intellifonts; 10 TrueType fonts; 1 bitmap font
Memory:	64 MB RAM; expansion up to 384 MB
Hard Disk Drive:	10 GB (Optional)
Interface:	IEEE 1284 Bi-directional Parallel port
	USB 2.0 Serial Port
	10/100 BaseTX Ethernet
Optional Interface:	IEEE 1394 port
	IEEE 802,11b wireless LAN interface
	Bluetooth interface
Network Protocols:	Simultaneous auto-sensing and auto-switching protocols:
	TCP/IP, Novell IPX/SPX, AppleTalk, SMB/NetBEUI
Driver:	PCL 5c: Windows 95/98/Me/NT 4.0/2000/XP
	PS: Windows 95/98/Me/NT 4.0/2000/XP, Macintosh 8.6 or later, UNIX
	(Solaris, HP-UX, Red Hat Linux, HP-VX, SCO, IBM AIX)
	RPCS: Windows 95/98/Me/NT 4.0/2000/XP
	For Unix support, visit www.ricoh-usa.com/download
Printer Utilities	SmartNetMonitor; Web Status Monitor; DeskTopBinder;
	Printer Utility for Mac; Agfa Font Manager 2000

10 GB Hard Disk	Drive: HDD is necessary for Locked Print (Secure Printing), Sam and permanent font downloading. Either HDD or 128 M necessary for electronic collation or RIP Once and Print	IB of memory is
Memory Options:	144-pin DIMM SD-RAM (PC133 compliant) Maximum of 384 MB total 64 MB RAM 128 MB RAM 256 MB RAM	Part # 001179MIL
IEEE 1394 Interfa	ace Board Type 4510	Part # 400745
Included Cables: Hardware Specifications: Data Transmission Speed: System Requirement:	2.0m 6pin to 6pin cable, 2.0m 6pin to 4pin cable 6 pins; 2 ports available 100/200/400 Mbps Windows 2000 Professional/Server with Server Pack 1 Windows XP for IP over IEEE 1394 (TCP/IP Protocol)	I
IEEE 802.11b Wi	reless LAN Interface Type A	Part # 400779
Data Transmission Speed:	1/2/5.5/11 Mbps Note: Cannot be used simultaneously with 10/100 Bas Must be manually selected at printer control panel.	seTX.
Bluetooth Interface Board Type A		Part # 400851
Range: Supported OS: Transmission Specification	Approximately 10m Same as print driver Bluetooth v1.1	
Use Account Enh	ance Unit Type B Printing usage can be monitored and users accessing or restricted using SmartNetMonitor.	Part # 400570 color printing can be
Optional Accesso	ries	
Paper Feed Unit	Туре 3000	Part # 400836
Paper Size: Paper Weights: Capacity: Note: The CL3000 can	Trays: 8.5" x 11"; 8.5" x 14"; A4; B5 Trays: 16 to 28 lb. Bond (60 to 105g/m ²) 530 sheets be configured with up to two additional paper trays.	
Duplex Unit AD440		Part # 400835
Paper Size: Paper Weights:	Trays: 8.5" x 11"; 8.5" x 14"; A4; B5 16 - 28 lb. Bond (60 to 105g/m²)	
Color LP Toner Type 12 Color LP Toner Type 12	25 Black	Part # 40096 Part # 40097

Color LP Toner Type 125 Cyan Part # 400969
Color LP Toner Type 125 Magenta Part # 400975
Color LP Toner Type 125 Yellow
Photoconductor Unit Type 125 Black
Photoconductor Unit Type 125 Color
Waste Toner Bottle Type 125 Part # 400844
Fusing Unit Type 125
Intermediate Transfer Unit Type 125 Part # 400846









Tivoli.

siness software









Windows' and Windows' 95/98/Me/NT4.0/2000/XP are registered trademarks of Microsoft Corporation. Macintosh', Mac'OS and AppleTalk' are registered trademarks of Apple Computer, Inc. Adobe' and PostScript' are trademarks of Adobe Systems, Inc. PCL' is a registered trademark of Hewlett-Packard Company, Rich' and Aflicio' are registered trademarks of Ricoh Company, Ltd. RPCSTM is a trademark of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.



3

EPA 2000 Office Products Partner of the Year (5th consecutive year) EPA 2000 Labeling Partner of the Year Ricoh Corporation has determined that this product meets the Energy Star² guidelines for energy efficiency.

RIGOR[®] Image Communication

Ricoh Corporation, Five Dedrick Place, West Caldwell, NJ 07006 Phone: (973) 882-2000 • www.ricoh-usa.com

Printed in the U.S.A. or recycled paper because Ricoh cares.