

## Specifications in brief of Single Power Supplies

Type	Order No.	Setting ranges		Resolution		Max. deviation of output for				Z <sub>out</sub> for		t <sub>r</sub> for	Max. PARD		Remote sensing		Dimens. WxHxD Weight
		Voltage	Current	V	I	ΔV AC supply ±10%		Δtamb -10 to +40 xC		V	I	V	V <sub>rms</sub>	I <sub>rms</sub>	OV	protec.	
		V	A	%	%	V(%)	I(%)	V(%/xC)	I(%)	mΩ	kΩ	μs	mV	mA	S	O	
<b>NGA</b>	<b>7.5</b> 192.0010.02	0.01 to 7.5	0.2 to 15	0.02	0.5	0.01	0.2	0.01	0.1	0.25	0.25	75	0.15	-	S	-	129/172/ 330 (8)
	<b>15</b> 192.0010.03	0.01 to 15	0.1 to 8	0.02	0.5	0.01	0.2	0.01	0.1	0.375	1	75	0.3	-	S	-	
	<b>35</b> 192.0010.04	0.01 to 35	0.05 to 4	0.02	0.5	0.01	0.2	0.01	0.1	0.875	4.4	75	0.6	-	S	-	
	<b>70</b> 192.0010.05	0.01 to 70	0.025 to 2	0.01	0.5	0.01	0.2	0.01	0.1	3.5	17.5	75	1	-	S	-	
<b>NGAS</b> <b>32/10</b>	192.0803.04	0.01 to 32 0.01 to 16	0.1 to 10 (15)	0.02	0.5	0.01	0.2	0.01	0.1	0.16	1	75	0.6	-	S	-	129/172/ 330 (8)
<b>NGB</b>	<b>32</b> 117.7210.90	0.01 to 35	0.02 to 10	0.02	0.02	0.001	0.002	0.01	0.01	0.35	17.5	50	0.2	10	S	O	190/172/ 330 (10)
	<b>70</b> 117.7227.90	0.01 to 70	0.01 to 5	0.02	0.02	0.001	0.002	0.01	0.01	1.4	70	50	0.5	5	S	O	
<b>NGK</b>	<b>15</b> 192.0003.02	0.01 to 15	0.01 to 4	0.02	0.02	0.001	0.002	0.01	0.01	0.75	37.5	50	0.2	0.1	S	O	190/172/ 278 (8)
	<b>35</b> 192.0003.03	0.01 to 35	0.01 to 2	0.01	0.02	0.001	0.002	0.01	0.01	1.75	175	50	0.4	0.05	S	O	
	<b>70</b> 192.0003.04	0.01 to 70	0.01 to 1	0.01	0.02	0.001	0.002	0.01	0.01	7	700	50	0.8	0.015	S	O	
	<b>280</b> 192.0003.05	0.01 to 280	0.002 to 0.2	0.01	0.02	0.001	0.002	0.01	0.01	140	700	50	3	0.005	S	-	
<b>NGM</b>	<b>7.5</b> 117.7110.12	0.01 to 7.5	0.01 to 4	0.02	0.02	0.001	0.002	0.01	0.01	0.75	10	50	0.2	0.1	-	O	95/172/ 278 (4)
	<b>15</b> 117.7110.13	0.01 to 15	0.01 to 2	0.02	0.02	0.001	0.002	0.01	0.01	1.5	40	50	0.2	0.05	-	O	
	<b>35</b> 117.7110.14	0.01 to 35	0.01 to 1	0.02	0.02	0.001	0.002	0.01	0.01	3.5	175	50	0.4	0.02	-	O	
	<b>70</b> 117.7110.15	0.01 to 70	0.01 to 0.5	0.01	0.02	0.001	0.002	0.01	0.01	14	700	50	0.8	0.001	-	O	
	<b>280</b> 117.7110.06	0.01 to 280	0.002 to 0.1	0.01	0.02	0.001	0.002	0.01	0.01	280	1400	50	3	0.002	-	-	