

Specifications in brief of Dual and Triple Power Supplies

Type	Order No.	Setting ranges		Resolution		Max. deviation of output for				Zout for		tr for	Max. PARD		Over-voltage protection	Dimensions WxHxD Weight mm (kg)	
		Voltage V	Current A	V %	I %	ΔV AC supply $\pm 10\%$ V(%)	Δt_{amb} -10 to +40 °C I(%) V(%/°C)	I(%)	V	I	V	V _{rms}	I _{rms}	mV			mA
Dual Power Supplies																	
NGMD35	117.7127.02	0.01 to 35 (2 x)	0.01 to 1	0.02	0.02	0.001	0.001	0.01	0.01	3.5	175	50	0.4	0.02	●	190/172/ 278 (8)	
Triple Power Supplies																	
NGL35	192.0026.02	0.01 to 35 (3 x)	0.01 to 0.6	contin.	1	0.01	0.2	0.1	0.1	3.5	15	75	0.2	-	-	190/172/ 278 (7)	
NGT20	117.7133.02	0.01 to 20 (2 x) 0.01 to 6 (1 x)	0.01 to 1 0.01 to 5	0.02	1	0.01	0.2	0.01	0.1	2 1	9 0.4	75 75	0.15 0.2	-	- ●	190/172/ 278 (7)	
NGT25	192.0503.02	0.01 to 25 (2 x) 0.01 to 6 (1 x)	0.01 to 0.8 0.01 to 5	0.02	1	0.01	0.2	0.01	0.1	2.5 1	10 0.4	75 75	0.2 0.2	- -	- ●	190/172/ 278 (7)	
NGT35	191.2019.02	0.01 to 35 (2 x) 0.01 to 6 (1 x)	0.01 to 0.6 0.01 to 5	0.02	1	0.01	0.2	0.01	0.1	3.3 1	15 0.4	75 75	0.25 0.2	- -	- ●	190/172/ 278 (7)	