

Version  
02.00July  
2004

## Vector Signal Analyzer R&S® FSQ-K70

Universal demodulation, analysis and documentation of digital radio signals

- ◆ For all major mobile radio communication standards:
  - GSM & EDGE
  - WCDMA-QPSK
  - cdma2000-QPSK
  - Bluetooth®
  - TETRA
  - PDC
  - PHS
  - DECT
  - NADC
- ◆ For all common digital modulation modes:
  - BPSK, QPSK, OQPSK
  - $\pi/4$  DQPSK
  - 8PSK, D8PSK,  $3\pi/8$  8PSK
  - (G)MSK
  - 2, 4, (G)FSK
  - 16, 32, 64, 128, 256 (D)QAM
  - 8VSB
- ◆ 25 MHz symbol rate expandable up to 81.6 MHz
- ◆ 28 MHz I/Q demodulation bandwidth expandable up to 120 MHz
- ◆ Optimum representation of results:
  - In-phase and quadrature signals versus time
  - Magnitude and phase versus time
  - Eye diagram
  - Vector diagram
  - Constellation diagram
  - Table with modulation errors
  - Demodulated bit stream
  - Statistical evaluation of modulation parameters
  - Spectral evaluation
  - Amplifier distortion measurements



**ROHDE & SCHWARZ**

## Universal analysis of digital radio signals

The vector signal analyzer option upgrades the high-quality Signal Analyzers R&S®FSQ, adding universal demodulation and analysis capability down to bit stream level for digital radio signals. The option supports all common mobile radio communications standards.

## Measurement and analysis of digital modulation signals

You want to measure and analyze digitally modulated signals? This can easily be done in the analog baseband or at the RF up to 40 GHz with the vector signal analyzer option in the R&S®FSQ.

In addition to performing standard measurements such as determination of modulation accuracy, carrier leakage or I/Q imbalance, you can also study the information statistics of these parameters such as the standard deviation of carrier frequency error calculated over 10 measurements.

Since the R&S®FSQ-K70 can analyze digital signals, it is an ideal tool for use in development and production.

## Versatile in the lab

You may want to develop future or company standards, use unconventional formats or modify synchronization sequences.

In all these cases, the R&S®FSQ with the option R&S®FSQ-K70 will support you by providing user-selectable bit and symbol rates, filters, modulation schemes and synchronization sequences. You can even generate and store your own generic standards, save the settings and recall them at any time.

## Fit for future standards

The option R&S®FSQ-B72 allows the standard demodulation bandwidth of 28 MHz to be expanded to 60 MHz for frequencies below 3.6 GHz and above 120 MHz.

## Efficient in production

The high measurement speed of 60 sweeps/s in the analyzer mode and typically 20 measurements/s using the vector signal analyzer function is ideal for applications in production. The high flexibility allows multistandard test systems to be configured for easy adaptation to varying production requirements.

## Any mobile radio standard at a keystroke

The high flexibility offered by the analyzer is by no means at the price of complicated operations: all major digital modulation standards can be activated at a keystroke. The instrument is then completely configured for measurements in line with the activated standard. The corresponding synchronization sequences are of course offered along with the standard.

## Multiple test functions integrated in one unit

The Signal Analyzers R&S®FSQ in conjunction with the option R&S®FSQ-K70 replace several individual instruments:

- ◆ High-grade spectrum analyzer
- ◆ Vector demodulator
- ◆ Constellation analyzer

## Principle of vector signal analysis

The IF signal is digitized by means of a fast A/D converter, allowing purely digital processing of all subsequent analysis steps, thus making them practically error-free and providing high long-term and temperature stability. After A/D conversion, the signal is digitally mixed into the baseband and split into a real and an imaginary component. The complete signal information is thus available for further analysis.

The signal is demodulated down to bit level by a DSP. From the data stream thus obtained, an ideal signal is calculated. This reference signal is compared with the test signal. The resulting difference signal contains all modulation errors (see block diagram).

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., USA and licensed to Rohde&Schwarz

GENERIC STANDARD	STANDARD
3G_WCDMA	3G_WCDMA_FHD
BLUETOOTH	3G_WCDMA_FHD
CDMA2K	3G_WCDMA_REV
DECT	BLUETOOTH_LDH1
GSM-EDGE	BLUETOOTH_LDH3
NADC	BLUETOOTH_LDH5
PDG	CDMA2K_1X_FHD
PHS	CDMA2K_1X_REV
TETRA	DECT_LP
(ALL)	EDGE_NB
	GSM_LB
	GSM_LB
	GSM_NB
	GSM_SB
	NADC_FHD
	NADC_REV
	PDG_DOWN
	PDG_UP
	<DOWN>

List of standards

The R&S®FSQ features a newly developed digital back end that benefits from the progress in ADC and ASIC development. Time-consuming evaluation algorithms can be implemented directly in the hardware – a prerequisite for fast measurement and high accuracy.

- ◆ 81.6 MHz A/D converter
  - Optional second converter for baseband inputs
  - Optional 326.4 MHz A/D converter, SFDR >58 dB
- ◆ Digital hardware resampler to match the sampling rate to a multiple of the symbol rate
- ◆ Sampling rate from 10 kHz to 326.4 MHz adaptable to the modulation rate
- ◆ SFDR >80 dBfs
- ◆ Digital downconversion to baseband with high output bandwidth (120 MHz referred to RF)

**Intermodulation distortion of I/Q data: a distortion-free transmission range is particularly important for amplifier measurements; the illustration above shows the intermodulation characteristics of the I/Q data of a two-tone signal.**

### Visualizing amplifier influence on your signal



By analyzing the difference between the reference signal and the signal under test, the analyzer can display the distribution of the amplitude and phase error as a probability density function.

Furthermore, the phase and amplitude errors can be analyzed with respect to signal amplitude. The results can reveal the cause of modulation errors and help finding the optimum operating point for the amplifier.

### Searching for rare events

By activating the multiburst capability you can fill the 16 Msamples of memory with continuous data and then search through the buffer to locate specific events.

If you have a burst signal with sporadic disturbances, all you need to do is to capture the signal and then step through the bursts one by one to find the distorted burst. You can then use all the tools of the R&S®FSQ-K70 to locate the origin of the disturbance.



Block diagram of vector signal analysis section in the R&S®FSQ

## Applications

### Measurements on parts of signals (1)

To perform these measurements on TDMA systems such as EDGE in line with standards, a time reference must be established from synchronization sequences to pre- or midamble. This is done in the PATTERN SEARCH mode, in which the analyzer triggers on preset or user-defined synchronization sequences.

This not only allows established standards to be measured with high precision, but also modified settings in the case of new developments. Further trigger modes are:

- ◆ External
- ◆ Burst
- ◆ IF power

Picture 1 shows an example where the modulation quality is measured only on the training sequence of an EDGE signal.

### Modulation error measurements on EDGE signals (2)

The upper screen (A) shows the EVM versus time of an EDGE signal; the lower screen provides a summary of relevant errors measured over a burst signal and several statistical parameters calculated over 10 bursts.



### Modulation accuracy measurements on WCDMA mobile phones (3 and 4)

The low inherent EVM of <math><0.6\%</math> (rms) of the option R&S®FSQ-K70 substantially reduces uncertainty. Tolerances, e.g. an rms EVM error of 17.5% for WCDMA, can thus be allowed practically completely for the DUT, thus widening the DUT tolerance margin.


The SYMBOL TABLE/MODULATION ACCURACY lists the demodulated bits and the errors found. The bit sequences and the errors can be read via the fast IEC/IEEE bus or 100 Mbit LAN connection of the analyzer.

The constellation diagram of the QPSK signal and the probability distribution of the amplitudes are shown below.


### Convenient analysis with vector diagram (5)

The vector diagram enables convenient analysis of the degradation of modulation accuracy caused, for example, by nonlinearities, phase noise or amplitude-dependent phase response of amplifiers, converters, etc. The upper screen (A) shows the complete constellation diagram, the lower screen (B) the probability distribution of the error vector magnitude (EVM).

4



5






**AM/φM and AM/AM distortion example with a 16 QAM signal (6 and 7)**

Picture 6 shows the constellation diagram where the outer constellation points are drawn to the center of the diagram as a result of the amplifier compression. Picture 7 shows the AM/AM and AM/φM conversion curve of the same signal.

**WLAN IEEE 802.11b constellation diagram (8)**

Signals where the modulation format changes the signal quality can be analyzed with the R&S®FSQ-K70. The constellation diagram in the upper half of the display is calculated from the QPSK part of an IEEE 802.11b signal marked with the red display lines. Due to the Gaussian pulse shaping filter used by the transmitter, the signal is not intersymbol-interference-free and the symbol points are not single points but are distributed in a square.




## DVB-S constellation diagram (9 and 10)

The MAPWIZ tool that is available on the Rohde&Schwarz website for download free of charge allows the mapping of the DVB-S signal to be created. The mapping is imported into the R&S®FSQ-K70 and the constellation diagram of the measured DVB-S signal can be displayed.


## Spectral evaluation of measurement results (11)

The spectrum of the error vector magnitude of an EDGE signal has clear peaks. These peaks indicate that an interferer with a specific frequency is present on the signal. Designers can thus identify the sources causing the increased EVM.


9



10



11





For specifications see PD 0758.1706.22  
and [www.rohde-schwarz.com](http://www.rohde-schwarz.com)  
(search term: FSQ-K70)



**ROHDE & SCHWARZ**

[www.rohde-schwarz.com](http://www.rohde-schwarz.com)