

# HF Transceiver Family




## R&S® XK 2000



## Telephone Exchange Set R&S® GA 2160

PABX and telephone set for advanced automatic telephone operation via R&S® XK 2000 radios



For the optional telephone-operated service within the R&S®XK 2000 family, the radio must be equipped with the internal ALE, APP and EMC filter ALE/APP options.

Moreover, the accessory Telephone Exchange Set R&S®GA 2160 – which consists of a PABX and a standard analog telephone set – must be connected to the telephone connection box of the APP. This assembly allows telephone-like operation of the entire radio system, with full radio operation (link setup), ringing, signaling and (semiduplex) operation from the telephone set.

To increase the number of subscribers or to provide access to the telephone network, other (larger-capacity) PABXs can be used, or a direct PSTN line can be connected to the APP's telephone connection box.

**Note:** Any access to a public telephone network must comply with local PTT regulations.

The technical interface specifications of the APP's telephone box are designed to comply with the German PTT regulations FTZ 1 TR 2 and FTZ 144 TV 41 regarding equipment connected to telephone lines, but the box is not officially certified.

The dialing tone is generated from the power line frequency. In order for the R&S®GA 2160 to function properly, all peripheral equipment (dial-up modem) must therefore be operated at the same power line frequency.

## Specifications

<b>Power supply</b>	
Voltage	230 V AC $\pm$ 10%, 50 Hz
<b>PSTN line</b>	
Transfer technical	meets BAPT 223 ZV 5
Values	
Voltage at exchange	20 V to 75 V DC
Call impedance	approx. 17 k $\Omega$ at 25 Hz
<b>Extension</b>	
DC voltage	29 V to 38 V DC
Circuit current	approx. 23 mA
Operating range	2 $\times$ 50 $\Omega$ , 790 m at 0.6 mm $\varnothing$
Call voltage	approx. 45 V (rms), 50 Hz
Reference tones	425 Hz $\pm$ 5% interval $\pm$ 10%
<b>Interface</b>	
<b>Serial interface</b>	standard RS-232-C, V.24 for configuration with external PC
<b>Environmental conditions</b>	
Temperature range	
Operating	+0 °C to +40 °C (do not expose to direct sunlight!)
Storage and shipping	-20 °C to +70 °C
Humidity	10% to 75%, uncondensed
<b>Other data</b>	
Case size	217 mm $\times$ 157 mm $\times$ 63 mm
Weight	approx. 1050 g
<b>Subscriber telephone set (1 <math>\times</math>)</b>	Siemens Euroset 2015 (for example) or compatible

## Ordering information

Telephone Exchange Set	R&S®GA 2160	6064.9507.02
------------------------	-------------	--------------

More information at  
[www.rohde-schwarz.com](http://www.rohde-schwarz.com)  
(search term: GA2160)



**ROHDE & SCHWARZ**

[www.rohde-schwarz.com](http://www.rohde-schwarz.com)

Europe: Tel. +49 1805 12 4242, e-mail: [customersupport@rohde-schwarz.com](mailto:customersupport@rohde-schwarz.com) · North America: Tel. +1 410-910-7988, e-mail: [customer.support@rsa.rohde-schwarz.com](mailto:customer.support@rsa.rohde-schwarz.com)  
Asia: Tel. +65 68463710, e-mail: [customer-service@rssg.rohde-schwarz.com](mailto:customer-service@rssg.rohde-schwarz.com)