

Fixture R&S®GK3005

Fixture for detachable frontpanel

R&S®GK3005 is an accessory to allow detached operation of a M3TR radio by its detachable front-panel. It consists of a plastic cover with a flexible cable supporting operation of the radio up to a distance of approx. 2 m. Delivery is without radio front-panel, which is part of radio R&S®MR3000U or R&S®MR3000H.

R&S®GK3005 is intended to operate the radio in portable applications where the radio is located on the users back in the man-pack bag. By means of straps (part of delivery) the unit can be worn at the arm, in front of users chest, or can be fixed at the belt. It can also be installed in vehicles as a simple remote control unit.

The detached front-panel supports control of all radio functions, but does not include any radio interfaces. Audio/data accessories, antennas etc. therefore connect directly at the radio.



Specifications

Dimensions (w \times d \times h)	175 mm × 65 mm × 90 mm	
Weight	0.4 kg	
Cable length	0,5 m to approx. 2 m	
Color	RAL6014 (yellow olive)	
nvironmental data		
Temperature range (acc to MIL-STD-810E method 501.3 and	d 502.3)	
Operational	−40 °C to + 70 °C	
Full specified	−25 °C to + 55 °C	
Storage	-40 °C to + 85 °C	
Temperature shock	acc. MIL-STD-810E method 503.3	
Transit drop	acc. MIL-STD-810E method 516.4 Procedure IV, (height of drop 122 cm)	
Shock	acc. MIL-STD-810E method 516.4	
Vibration	acc. MIL-STD-810E method 514.4	
Water tightness	1 m immersion during 2 hours acc. MIL-STD-810E method 512.3	

Ordering information

Designation	Туре	Order No
Fixture for detachable frontpanel	R&S®GK3005	6118.1008.02



More information at www.rohde-schwarz.com (search term: M3TR)









