

Standard Battery Pack R&S $^{\circ}$ IB 3001

Power supply for portable use of Transceivers R&S $^{\circ}MR\,3000$

- ◆ Rechargeable, up to 1000 cycles
- ◆ Li-lon technology, no memory effect
- Smart bus control for continuous monitoring of battery parameters
- High capacity for higher autonomy
- ◆ Low volume and weight



The R&S®IB 3001 is a sealed power pack with a watertight connector to the radio. Due to Li-lon technology maximum energy density is achieved. The battery pack's interface supports charge control functions such as battery state-of-charge, remaining capacity, remaining time, and chemical composition, which are available over the serial link. The battery pack does not require any maintenance.

The battery pack is equipped with quick-release fasteners, and single-hand operation is provided.

The battery pack is protected against:

- Short circuit (all cases)
- Overdischarging (rechargeable batteries only)
- Overcharging (rechargeable batteries only)
- Polarity inversion during charging (rechargeable batteries only)

The rechargeable battery packs withstand as much as 1000 charge/discharge cycles with no less than 60% of the initial capacity.

Specifications

Nominal voltage	28.8 V	
Capacity	5.5 Ah	
Charging time	6 h	
Dimensions (W \times H \times D)	199 mm × 74 mm × 94 mm	
Weight	1.8 kg	

Ordering information

Order designation	Туре	Order No.
Standard Battery Pack	R&S®IB 3001	6118.0201.03











