

# Accessory mapping

Model	CLAMP SENSOR	OPTICAL LINK	TEMPERATURE SENSOR
Model	CL-140 CL-124 CL33DC CL-22AD CL-20D	KB-LAN KB-USB1 KB-USB2 KB-RS1 KB-RS2 T-THP	T-300PC K-250CD K-250PC K-8-250 K-8-300 K-8-500 K-8-800
CD721/NH	●		
CD731/a	●		
CD751 (except CD731a)	●		
CD750P	●		
CD770	●		
CD771	●		
CD772	●		
CD800			○
CD800a			
CD801			
DA-50C	●		
PC20	●		
PC500	●		
PC5000	●		
PC510	●		
PC520M	●		
PM3			
PM5			
PM7a			
PS8a			
PM10			
PM11			
RD700	●		
RD701	●		
SD-420C			
CAM600S		●	
DCL10/20R/30DR			
DCL1000			
DCL1200R			
DCM-22AD			
DCM2000			
DCM2000AD			
DCM2000R			
DCM400			
DCM400AD			
DCM60L			
DCM600			
DLC-330L			
DLC-400A			
DG6/7/8/9			
DG251			
DG525			
DM1008S			
DM-1006S/506S			
PDM-506S			
DM-1527			
DM-5257			
DM1528S			
DM5218S			
DM508S			
PDM508S			
M53			
MG1000			
MG500/125			
AP33			
AU-31/32			
CP-7D			
CX506a			
EM7000			
PW100Fb			
SH-88TR			
SP-18D			
SP20			
SP21			
TA55	●		
VS-100			
YX360TRD			
YX360TRF			
YX-361TR			

● Optional ○ Standard △ Only with TL-21/TL-21M

# Clamp Meter comparative chart

Display Type	AC	AC	AC	AC	AC	AC	AC (Analog)	DC/AC	DC/AC	DC/AC	DC/AC	DC/AC	LEAK	LEAK
Model	DCL1200R	DCL1000	DCL20R	DCL10	DCM60L	DCM400	CAM600S	DCM400AD	DCM-22AD	DCM2000AD	DCM2000R	DCL30DR	DLC-400A	DLC-330L
Digit	4000	4000	6000	6000	1999	4000	-	4000	1999	4000	6000	1999	1999	3200
Category	CAT.III 600V	CAT.III 600V	CAT.IV 600V	CAT.IV 600V	CAT.IV 600V	CAT.IV 600V	CAT.IV 600V	CAT.IV 600V	-	CAT.III 600V	CAT.IV 600V	-	-	-
CE	●	●	●	●	●	●	●	●	-	●	●	-	-	-
Clamp diameter (mm)	42	42	25	25	21	25	36	25	22	53	24.5	38	32	32
Withstand voltage	5550	5550	3700	3700	3700	3700	5550	3700	2000	5550	3700	2000	2000	2000
Range	A/M	A/M	A	A	A	A	M	A	M	M	A	M	A/M	A/M
DCA (A)	-	-	-	-	-	-	-	40	20	40	60	-	-	-
ACA (A)	400	400	60	60	200	40	6	40	20	40	60	20m	30m	30m
DCV (V)	6	400m	-	-	-	400	60	400	2	400m	-	200m	-	-
ACV (V)	6	400m	-	-	200	400	150	400	2	400m	-	2	-	-
Resistance (Ω)	6k	400	-	-	200	400	1k	400	2k	400	-	200	-	-
Frequency (Hz)	9.999	-	-	-	-	-	20~4k (when clamping)	-	-	100	-	-	-	-
Backlight	●	-	●	●	-	-	-	-	-	-	-	●	-	-
True RMS	●	-	●	-	-	-	-	-	-	● (DCM2000R Only)	●	-	-	-
Auto power off	●	●	●	●	-	●	-	●	-	●	●	-	●	●
Peak hold	-	-	-	-	-	-	-	-	-	-	-	●	-	-
Data hold	●	●	●	●	●	●	POINTER LOCK	●	●	●	●	●	●	●
Range hold	●	-	-	-	-	-	-	●	-	●	-	-	-	-
Output terminal	-	-	-	-	-	-	-	-	-	-	-	-	●	-
EF (NCV)	●	-	-	-	-	-	-	-	-	-	-	-	-	-
Bargraph	-	-	-	-	-	●	-	●	-	-	-	-	-	●
Continuity	BUZZER	BUZZER	-	-	BUZZER	BUZZER	-	BUZZER	BUZZER	BUZZER	-	-	-	-
Dimension (H) mm	238	238	145	145	187	193	221	193	179	240	145	205	162	162
Dimension (W) mm	95	95	54	54	50	50	97	50	56	84	54	84	64	64
Dimension (D) mm	45	45	28	28	29	28	43	28	26.5	34	28	34	23	23
Weight (g)	290	290	120	120	210	230	420	230	140	400	120	390	125	125

Clamp Meter

Insulation Resistance Tester

PC Link System, Digital Multimeter

Analog Multimeter

Various Instruments

Accessories

Clamp Meter

Insulation Resistance Tester

PC Link System, Digital Multimeter

Analog Multimeter

Various Instruments

Accessories