

sanwa

World's best seller Drop shock proof !!

Analog Multimeter YX360TRF

- Drop shock-proof meter
- Null (zero center) meter
- $\pm 5/\pm 25$ in DCV
- High resistance up to 200M ohm
- Protective full-face cover
- Capacitance, dB, Li measurement



Standard Accessories Included

- Hand strap x 1

Optional Accessories

- DC high voltage probe (HV-10T)

Basic Specification



Function	Measuring range	Accuracy
DCV (NULL)	0.1V (20k Ω / V)	$\pm 5\%$ of full scale
	0.25 / 2.5 / 10 / 50 (20k Ω / V) / 250 / 1000V (9k Ω / V)	$\pm 3\%$ of full scale
	± 5 / 25V (40k Ω / V)	$\pm 5\%$ of full scale
ACV	10 / 50 / 250 / 750V (9k Ω / V)	$\pm 4\%$ of full scale
DCA	50 μ / 2.5m / 25m / 0.25A	*1 $\pm 5\%$ of full scale
Resistance	2k / 20k / 200k / 2M Ω (X1 / X10 / X100 / X1k) 200M Ω (X100k)	$\pm 3\%$ of arc $\pm 5\%$ of arc
Load current (LI)	0~150m / 15m / 1.5m / 150 μ / 1.5 μ A	
Capacitance	10 μ F	*2
dB	-10dB~+22dB (for 10VAC) ~+62dB	—
DC high voltage	DC25kV (optional probe: "HV-10T" is necessary)	—
hFE	1000 at X10 range (optional probe "HFE-6T" is necessary)	—

Battery	R6 (IEC) or UM-31.5V \times 2
Fuse	$\phi 5.2 \times 20$ mm (250V / 0.5A)
Size / Weight	H159.5 \times W129 \times D41.5mm / approx. 320g
Standard accessories included	Instruction manual, Test lead (TL-61T), Hand strap

The value in bracket at DCV and ACV is input resistance.

*1 Not including the resistance of fuse.

*2 Pointer indication of the maximum move by charged current in the capacitor.