

Analog Type



CE

DM1528S

3 test voltage ranges

- Test voltage DC1000V / 500V / 250V
- One-shot or continuous measurement push switch
- DCV measurement range (DC60V)
- Auto discharge function
- Inner battery check range
- Shoulder Strap

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT Ⅲ
600V

AD 1000V 2000MΩ 500V 1000MΩ 250V 500MΩ

DM1528S	
Insulation resistance (MΩ)	1~2~1000~2000MΩ 1000V 0.5~1~500~1000MΩ 500V 0.1~0.5~200~500MΩ 250V
Accuracy	±5% of reading (1st effective measurement range : written in thick print above) ±10% of reading (2nd effective measurement range : written in small type above)
ACV	600V
Accuracy	±5% of full scale (50~60Hz sine wave)
DCV	60V
Accuracy	±5% of full scale
Battery	6LR61 (9V)×1
Size / Weight	H144×W99×D43mm/approx. 310g
Standard accessories included	Test lead (TL-508S), Carrying case (C-08S), Instruction manual

DM5218S

3 test voltage ranges

- Test voltage DC500V / 250V / 125V
- One-shot or continuous measurement push switch
- DCV measurement range (DC60V)
- Auto discharge function
- Inner battery check range
- Shoulder Strap

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT Ⅲ
600V

Optional accessories

Test lead : TLF-120

AD 500V 1000MΩ 250V 500MΩ 125V 200MΩ

DM5218S	
Insulation resistance (MΩ)	0.5~1~500~1000MΩ 500V 0.1~0.5~200~500MΩ 250V 0.05~0.2~100~200MΩ 125V
Accuracy	±5% of reading (1st effective measurement range : written in thick print above) ±10% of reading (2nd effective measurement range : written in small type above)
ACV	600V
Accuracy	±5% of full scale (50~60Hz sine wave)
DCV	60V
Accuracy	±5% of full scale
Battery	6LR61 (9V)×1
Size / Weight	H144×W99×D43mm / approx. 310g
Standard accessories included	Test lead (TL-508S), Carrying case (C-08S), Instruction manual



CE

DM1008S

Single test voltage range

- Test voltage DC1000V
- One-shot or continuous measurement push switch
- DCV measurement range (DC60V)
- Auto discharge function
- Inner battery check range
- ACV measurement range
- Shoulder Strap

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT Ⅲ
600V

AD 1000V 2000MΩ

DM1008S	
Insulation resistance (MΩ)	1~2~1000~2000MΩ
Accuracy	±5% of reading (1st effective measurement range : written in thick print above) ±10% of reading (2nd effective measurement range : written in small type above)
ACV	600V
Accuracy	±5% of full scale (50~60Hz sine wave)
DCV	60V
Accuracy	±5% of full scale
Battery	6LR61 (9V)×1
Size / Weight	H144×W99×D43mm/approx. 310g
Standard accessories included	Test lead (TL-508S), Carrying case (C-08S), Instruction manual



CE

DM508S

Single test voltage range

- Test voltage DC500V·1000MΩ
- One-shot or continuous measurement push switch
- DCV measurement range (DC60V)
- Auto discharge function
- Inner battery check range
- Shoulder Strap

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT Ⅲ
600V

Optional accessories

Test lead : TLF-120

AD 500V 1000MΩ

DM508S	
Insulation resistance (MΩ)	0.5~1~500~1000MΩ
Accuracy	±5% of reading (1st effective measurement range : written in thick print above) ±10% of reading (2nd effective measurement range : written in small type above)
ACV	600V
Accuracy	±5% of full scale (50~60Hz sine wave)
DCV	60V
Accuracy	±5% of full scale
Battery	6LR61 (9V)×1
Size / Weight	H144×W99×D43mm/approx. 310g
Standard accessories included	Test lead (TL-508S), Carrying case (C-08S), Instruction manual



CE

PDM508S

Single test voltage range

- Test voltage DC500V·100MΩ
- One-shot or continuous measurement push switch
- DCV measurement range (DC60V)
- Auto discharge function
- Inner battery check range
- ACV measurement range
- Shoulder Strap

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT Ⅲ
600V

Optional accessories

Test lead : TLF-120

AD 500V 100MΩ

PDM508S	
Insulation resistance (MΩ)	0.05~0.1~50~100MΩ
Accuracy	±5% of reading (1st effective measurement range : written in thick print above) ±10% of reading (2nd effective measurement range : written in small type above)
ACV	600V
Accuracy	±5% of full scale (50~60Hz sine wave)
DCV	60V
Accuracy	±5% of full scale
Battery	6LR61 (9V)×1
Size / Weight	H144×W99×D43mm/approx. 310g
Standard accessories included	Test lead (TL-508S), Carrying case (C-08S), Instruction manual



CE