

PC20

sanwa

AC adapter available for long time measurement



Feature

- 4000 count display
- Measuring data can be transferred to PC through RS232 cable with PC Link.
- AC adapter is available for long time measurement.
- Data hold, Range hold
- Capacitance measurement
- Safety cover for the 10A terminal to avoid miss insertion.
- Tilt stand
- Holster for wall hanging and fixing test lead

○ RS232 cable, PC Link and AC adapter are optional accessories.

Standard Accessories

- Instruction Manual 1copy
- Test Lead (TL-21) 1set
- Protective Holster (H-70) 1piece

Optional Accessories

- Clamp Probe: CL-22AD, CL-20D, CL33DC
- Temperature Probe: T-300PC
- Soft case: C-C7
- Carrying case: C-PC10/S
- AC adapter: AD-71AC (100V), AD-72AC (220V)
- RS-232C interface cable: KB-RS1
- PC Link
- Clip adapter: CL-11

General Specification

Measuring Method	Sigma Delta
ADC display updates	3 times / sec
Display	Approx. 4000 counts in max.
Range Selection	Auto and Manual ranges
Over Display	"O.L." mark indication
Polarity	Automatic selection (only "-" is displayed)
Battery Discharge Display	" \square +" mark indication at approx. 2.4V 0.15V

CE