

The Essence of Digital Copying

Outstanding Quality Copying at an Exceptional Value

It's a simple fact: The faster the world of business moves, the more flexibility you need to be able to respond to it. In fact, your ability to generate, duplicate, integrate and disseminate information quickly, seamlessly and securely is essential to your success. Designed for busy workgroups and office enterprises that need first-class digital copying functionality, the AR-M350U/M450U Imager combines superior productivity with exceptional image quality. And, because the AR-M350U/M450U Imager is completely modular, new capabilities (such as high speed faxing) can be added as your needs evolve.

A Powerful Blend of Features, Functionality and Flexibility

Productive 35/45 cpm Digital Copying

- Duplex Single Pass Feeder for fast, efficient two-sided copying
- Wide zoom range from 25 to 400%
- Scan Once/Print Many for productive copying
- Various image editing functions: Margin Shift, Edge/Centre Erase, Dual Page Copy, Multi-shot, etc.
- Convenient automated features including auto paper selection, auto magnification selection and auto tray switching
- Trayless duplex copying (optional)
- 600 dpi and 1,200 dpi equivalent resolution with smoothing technology
- Large 3,100-sheet paper capacity with options
- Multi-Purpose Tray handles special print media including OH transparencies, heavy stock and envelopes
- Job Build capability allows large documents to be stored in memory temporarily, and then copied as a continuous set

Additional Paper Handling Accessories:



AR-FN7
Saddle Stitch Finisher



AR-D14
Stand with three
500-Sheet Paper Drawers



AR-FN6
Stapler/Sorter Finisher



Multifunction modularity at its best – with the AR-M350/450 U Imager, you can add new functionalities as your needs change.



The easy to use touch screen on the control panel of the AR-M350/450 U Digital IMAGER quickly guides users step-by-step through various functions.

Specifications

General

Type:	Console
Copy system:	Dry, electrostatic transfer system
Paper size:	Max. 11" x 17" / Min. 5.5" x 8.5"
Paper capacity:	500 sheets, expandable up to 3,100 sheets with options
Copy/print speed (max):	35/45 cpm/ppm (8.5" x 11")
Memory:	64MB, upgradable to 320MB w/ options, 5GB HDD (Optional)
Warm-up time ¹ :	Less than 80 seconds
First copy time:	5.3 seconds (8.5" x 11", 1st paper tray, fast platen mode)
Power requirements:	Rated local AC voltage \pm 10%, 50/60 Hz
Power consumption:	Max. 1.6 kW
Dimensions (WxDxH) ² :	32 17/32" x 26 31/32" x 43 15/16"
Weight ³ :	215 lbs

Copier

Original size:	Max. 11" x 17"
Continuous copy:	Max. 999 copies
Resolution copy:	600 dpi
Zoom range:	From 25 to 400% with 8 preset ratios (4 reduction + 4 enlargement). From 25 to 200% when equipped with DSPF
Other features:	Auto paper selection, auto magnification selection, paper type selection (by type setting), auto tray switching, E-Sort, rotation copy, reserved copy, pre-heat/auto power shut-off modes, copy auditing (100 accounts), margin shift, edge/centre erase, dual page copy mode, multi-shot copy (N in 1), booklet copy

Optional Network Print Kit (AR-P14)

Network Protocol ⁴ :	Enables printing via TCP/IP for Windows and UNIX environments or IPX/SPX for Novell environments
---------------------------------	--

Optional Scanner Expansion Kit

Resolution:	200, 300, 600 dpi
Compatibility:	TWAIN compliant (push out method)
Sharpdesk licenses:	10-user licenses included

Optional Network Interface Card

Hardware interface:	10Base-T, 100Base-TX
Support platforms:	UNIX, Windows 95/98/Me, Windows NT 4.0, Windows 2000, Novell Netware 3.x/4.x (IntranetWare)/Netware5, Macintosh System 8.5.1-9.x
Network protocols:	IPX/SPX for Novell environments, TCP/IP for Windows and UNIX environments, EtherTalk for Macintosh environments
Printing protocols:	Novell Printserver Application w/ NCS and Bindery, Printer resident LPD (includes reaction to LPQ request), TCP FTP for downloading of print files, EtherTalk printing, IPP, NetBEUI for Windows

Optional Fax

Transmission time ¹ :	2 seconds (Super G3); 6 seconds (G3)
Compression method:	MH, MR, MMR, JBIG
Modem speed:	33.6Kbps/2.4Kbps automatic fallback
Intercommunication:	Super G3, G3
Communication line:	PSTN, PBX
# of support lines:	1
Image quality:	256 grayscale levels
Exposure adjustment:	Dark/Auto/Light
Resolution settings:	Normal/Small Letter/Fine/Extra Fine
One touch dial keys:	500 (e-mail addresses included)

Design and specifications are subject to change without notice.

Sharp is a registered trademark of Sharp Corporation.
All other trademarks and registered trademarks are property of their respective holders.

¹With ITU-T No.1 chart standard resolution, SUPER G3 mode, 33,600 bps, JBIG compression.

²At rated voltage, 20°C (68°F), 65% RH.

³Dimensions and weight include scanner rack and stand.

⁴Standard configuration allows printing via parallel port only.

SHARP
be sharp™

SHARP ELECTRONICS CORPORATION
Network Office Systems Group • Sharp Plaza, Mahwah, NJ 07430-1163
1-800-BE-SHARP • www.sharppusa.com



As an ENERGY STAR® Partner, SHARP has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.