



COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX COPY PRINT FAX

# AR-F152 Digital Copier

**SHARP.**

## BIG COPY AND FACSIMILE FEATURES IN A SMALL SLEEK PACKAGE



The Sharp AR-F152 Digital IMAGER is the innovative solution to the productivity demands of today's small office. Packed with the high-tech advantages of a digital copier and a full-featured facsimile the AR-F152 IMAGER delivers enhanced image quality, efficiency and heightened productivity. For even more functionality, add the optional printing capabilities to transform the AR-F152 IMAGER into a high-quality laser printer.

The Sharp AR-F152 IMAGER demonstrates Sharp's commitment to improving people through technology and innovation. It's time to take your business to a better place. Sharp Digital IMAGER series, that better place is here now.

### FEATURES

- 15 ppm engine speed
- Standard Single Pass Feeder (SPF) for automatic document feeding
- 2 x 250-sheet paper trays (500 sheets)
- Standard fax capability
  - 14.4 kbps modem
  - 20 Rapid keys
  - 100 Speed dials
  - 50 broadcast locations
  - Book Fax
- Standard 50-sheet bypass
- High resolution 600 dpi output
- Scan Once – Print Many (1-page memory buffer) – 6MB
- 50-200% Zoom (1% Increments)
- 9.6 second first copy time
- Photo Mode
- Optional print kit
- Economical cost of operation

**AR-F152****Copier Specifications****AR-F 152 COPIER SPECIFICATIONS**

TYPE	Digital copying machine, desk-top type
COPY SYSTEM	Dry, electrostatic
ORIGINALS	Sheets, bound documents
FEEDER	Standard single pass feeder (SPF)
ORIGINAL SIZE	Max. 10" x 14"
COPY SIZES	3 1/2" x 5 1/2" to 8 1/2" x 14"
COPYING SPEED	15 copies per minute
CONTINUOUS COPY	Max. 99; subtractive counter
COPY RATIO	Variable: 50-200% in 1% increments (total 151 steps) fixed presets: 50%, 64%, 78%, 100%, 129%, 200%
FIRST COPY TIME	Approx. 9.6 sec. (normal copying mode)
COPY PAPER FEED	Two 250-sheet paper trays with automatic feed; one bypass tray with 50-sheet automatic feed capability
FUSING SYSTEM	Heat rollers
DEVELOPER SYSTEM	Magnetic brush development
EXPOSURE SYSTEMS	Moving optical source, slit exposure (stationary platen) with automatic exposure
LIGHT SOURCE	Xenon lamp
RESOLUTION	Output: 600 dpi
GRADATION	Scan: 256 levels; Output: 2 levels
MEMORY	6 MB (1-page memory buffer)
POWER SUPPLY	AC (120 V $\pm$ 10%), 60 HZ ( $\pm$ 2%)
POWER CONSUMPTION	Max 1.3kW
WEIGHT	approx. 54.3 lbs.; (24.6 kg); including supplies
COPIER DIMENSIONS	20.4" (W) x 19" (D) x 15" (H)
OPERATING CONDITIONS	Temperature: 50° F to 86° F (10° C to 30° C); Humidity 20-85%
OPTIONAL EQUIPMENT	Print Kit

**FAX SPECIFICATIONS**

MODEM	14.4 kbps
TRANSMISSION SPEED	6 seconds per page*
COMPRESSION	MH/MR/MMR
ECM	Yes
BOOK FAX	Yes
RAPID/SPEED DIALS	20/100 locations
BROADCAST	50 destinations
AUTO REDUCTION	Yes
OUT OF PAPER RECEPTION	Yes
FAX MEMORY	2MB (approximately 120 letter size pages)*
FAX MEMORY BACKUP	approximately 1 hour

**AR-PG1 KIT (OPTIONAL)**

PRINTING SPEED	8ppm
PDL	Host-based
RESOLUTION	600dpi /300dpi
STANDARD INTERFACE	IEEE P1284 Bi-directional Parallel Port (1), USB Port (1)
PLUG AND PLAY	Yes
PRINT DRIVER	Microsoft Windows 3.1x/Windows95/Windows98/Windows NT 4.0

Design and specifications are subject to change without notice.

Sharp is a registered trademark of Sharp Corporation. All trademarks and registered trademarks are the property of their respective holders.

As an ENERGY STAR® Partner, Sharp® has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.

\* Based on Test Chart #1 at standard resolution excluding time for protocol signals (i.e., phase C time only) sent at 14.4 Kbps. Transmission speeds will vary based on line type and conditions.



SHARP ELECTRONICS CORPORATION  
Document and Network Systems of America  
Sharp Plaza, Mahwah, NJ 07430-2135  
201-529-9600  
www.sharp-usa.com



**SHARP®**

WWW.SHARP-USA.COM

CPD-3335