

How to Simply Generate a PSK Modulation

Phase-Shift Keying (PSK) is a technique used to transmit data by modifying the phase of a sinusoid carrier wave. Tabor Arbitrary Waveform Generators (AWGs) supports PSK modulation according to the following variations: PSK, BPSK, QPSK, OQPSK, pi/4DQPSK, 8PSK, 16PSK, as well as user-defined variations. This document will quickly guide you through the definition process as shown on a WW2572A.

NOTE


You can also generate **Quadrature Amplitude Modulation (QAM)** by following steps similar to those described in this document. The (n)PSK and (n)QAM modulations are available in the WW2572A, WW5064/1074/2074, WS8102 and PM8572A models.

The front panel of the AWG is depicted below.




→ **To generate a PSK Modulation using the front panel:**


1. Press the **TOP** menu button.




2. Press the **Waveform** button.




3. Press the **Modulated** button.



4. Press the **Modulation Type** menu button. A list of modulation types appears on the screen. By default, the modulation type is set to "OFF".




5. Select the **(n)PSK** modulation type from the list box using the arrow keys, and press **ENTER**.



6. Press the **PSK Type** menu button. A list of PSK varieties appears on the screen.

- PSK
- BPSK
- QPSK
- OQPSK
- pi/4DQPSK
- 8PSK
- 16PSK
- USER (user-defined)

7. Select the required PSK modulation from the list box using the arrow keys, and press **ENTER**.



- 8.** Following your selection, you will be able to configure the characteristics of the modulation with the modulation-type specific menu buttons that appear on the left-hand side of the panel.



TIP

Whenever the  icon is displayed there are more attribute menu buttons to be shown below. Simply scroll down using the dial or cursor key.

- 9.** Choose the menu buttons on the left-hand side of the screen to modify any of the following attributes:

- **PSK Data.** A table used to program a sequence of phase changes, as shown in step 10.
- **CW Control.** Used to turn the carrier waveform **CW OFF** or **CW ON**.
- **CW Frequency.** The frequency of the sinusoid carrier waveform.
- **Symbol Rate.** The rate at which the symbols step through. The rate can be programmed within the range of 1 S/s to 1 MS/s (when the length of the symbol is a single bit).
- **Marker.** Defines an index point in the PSK sequence at which the Sync Output generates a marker pulse.
- **Amplitude.** The amplitude of the carrier wave (in Volts peak-to-peak).
- **Offset.** The amplitude (in VDC) offset with reference to zero-level amplitude.

- 10.** Press the **PSK Data** menu button to program a sequence of phase changes, as shown below.




Each row in the table includes the following parameters:

- **Line.** The index number of the row.
- **Symbol.** The PSK data symbol. Each symbol defines a specified phase shift.


The following operations can be performed on the table:

- **Edit Line.** To edit an existing row.
- **Insert Line.** To add a new row to the table.
- **Delete Line.** To delete an existing row from the table.
- **Load DEMO Table.** To restore the factory-set demo values to the table.
- **Delete Table.** To delete the entire table.
- **Apply Changes.** Applies all the changes made to the table.

- 11.** When selecting a numeric attribute for modification, modify the displayed value either by using the dial or the cursor keys, or by entering the value using the numeric keypad. Press **ENTER** to save the modified parameter value.



- 12.** Press the **TOP** menu button to return to the main menu.
13. Press the **Outputs** button to configure the output settings.




- 14.** Define the channels in the **Outputs** section as being **ON** or **OFF**, modifying the settings using the dial or the cursor keys:

- To scroll between the fields, use the cursor keys.
- To edit a field, select the field, and press **ENTER**. Use the keypad to enter the chosen value.
- To toggle between **ON** and **OFF**, select the field and press **ENTER**. Use the cursor keys to choose the selected option.
- Press **ENTER** again to exit the edit mode, and save the value.



TIP

You can quickly modify the output settings by selecting **CH1** or **CH2** on the keypad, and toggling the **OUTPUT** key to turn the channel on or off.



For More Information

To learn more about Tabor's solutions or to schedule a demo, please contact your local Tabor representative or email your request to info@tabor.co.il. More information can be found at our website at www.taborelec.com

© Proprietary of Tabor Electronics Ltd.