



## WAVE STANDARD SERIES



## MODEL WS8251

### 250MHz Single Channel Arbitrary Function Generator

- Single-channel Arbitrary / Function Generator
- 250MHz sine and 150MHz square waves
- Triangle, ramp, sin(x)/x, Gaussian, exponential, noise, pulse and DC waveforms
- 4Vp-p into 50Ω, 8Vp-p into open circuit
- 12 Bit, 625MS/s, 512k points arbitrary waveforms
- Linear & logarithmic sweeps
- Continuous, triggered, gate and burst
- FM, FSK, and PSK modulation
- High resolution 3.8" LCD, color display
- Ethernet, USB and GPIB interfaces
- ArbConnection software for easy waveform creation

The Tabor WS8251 is a Single Channel Arbitrary / Function Generator with a 250MHz bandwidth and the functionality of a Function generator, arbitrary generator and Pulse generator all in one easy to use high performance unit. It is a compact stand alone bench top unit that will satisfy all of the industry and education standard testing needs for years to come.

#### **Standard Waveforms**

The WS8251 has 11 built in functions for quick and easy wave generation. Front panel operations allows for easy selection of wave form and editing of all wave parameters. All of the standard waves can reach up to 50MHz with Sine and Square going as high as 250MHz and 150MHz respectively.

#### **User Defined Waveforms**

For more advanced users the WS8251 with its 12-bit vertical resolution offers a standard 512k points memory depth and a 625MS/s sample clock for designing waveforms. With the ability to control and edit the value of each and every point any wave is possible. The memory can be divided into segments for storing all of the user defined waveforms.

#### **Modulated Waveforms**

Agility and modulation capabilities open the door to diverse applications. In addition to the capability of generating any shape and style of waveform with the arbitrary waveform generation power, the products can also do standard modulation schemes such as FM, FSK, sweep and PSK without sacrificing the power of the instrument control and output run modes.

#### **Accuracy and Stability**

As standard, the instrument is equipped with an internal frequency reference that has 1ppm accuracy and stability over a period of 1 year. An external frequency reference is provided on the rear panel for applications requiring greater accuracy or stability, supported by the instrument's 9 digits resolution.

#### **Easy to Use**

Large and user-friendly 3.8" back-lit color LCD display facilitates browsing through menus, updating parameters and displaying detailed and critical information for your waveform output. Combined with numeric keypad, cursor position control and a dial, the front panel controls simplify the often complex operation of an arbitrary function generator.

#### **Remote Control**

Model WS8251 comes standard with a variety of interfaces: Ethernet, USB and GPIB allowing the user to freely select the interface best suited to his individual requirements. The included ArbConnection software is a powerful editorial tool for designing waveforms and provides the user with full control of instrument functions, modes and features.

#### **Multiple Environments to Write Your Code**

Model WS8251 comes with a complete set of drivers, allowing you to write your application in various environments such as: Labview, CVI, C++, VB, and MATLAB. You may also link the supplied dll to other Windows based API's or, use low level SCPI commands (Standard Commands for Programmable Instruments) to program the instrument, regardless if your application is written for Windows, Linux or Macintosh operating systems.

#### **Automated External Self-Calibration**

Leading-edge technology is implemented to allow calibration from any interface, USB, GPIB or LAN and calibration factors are stored in a flash memory thus eliminating the need to open instrument covers.

Visit our website at [www.taborelec.com](http://www.taborelec.com)

  
**TABOR ELECTRONICS Inc.**  
Since 1971

# MODELS WS8251

## 250MHz Single Channel Arbitrary Function Generator



### Specification

#### CONFIGURATION

Output Channels 1

#### STANDARD WAVEFORMS

**Waveforms:** Sine, Triangle, Square, Pulse, Ramp, Sine(x)/x, Gaussian, Exponential, Repetitive Noise, DC.

#### Frequency Range:

Sine 50Hz to 250MHz, continuous  
50Hz to 125MHz, triggerable  
Square, Pulse 50Hz to 150MHz  
All others 50Hz to 50MHz

#### SINE

**Start Phase:** 0 to 360°

**Phase Resolution:** 0.1°

#### Harmonics Distortion (1Vp-p, typ.):

1MHz to 5MHz <-50dBc  
5MHz to 50MHz <-47dBc  
50MHz to 100MHz <-45dBc  
100MHz to 250MHz <-35dBc

#### Non-Harmonics Distortion (1Vp-p, typ.):

1MHz to 50MHz <-65dBc  
50MHz to 100MHz <-63dBc  
100MHz to 200MHz <-55dBc  
200MHz to 250MHz <-45dBc

#### Total Harmonic Distortion:

DC to 100kHz 0.3%

#### Flatness (1MHz, 1Vp-p, typ.):

1MHz to 25MHz <0.3dBc  
25MHz to 100MHz <0.5dBc  
100MHz to 250MHz <1dBc

#### SSB Phase Noise (10kHz offset, typ.):

1MHz Carrier <-115dBc  
10MHz Carrier <-108dBc  
100MHz Carrier <-90dBc  
250MHz Carrier <-85dBc  
350MHz Carrier <-80dBc

#### TRIANGLE

**Start Phase:** 0 to 360°

**Phase Resolution:** 0.1°

#### SQUARE

**Duty cycle Range:** 1.0% to 99.9%

**Resolution:** 0.1%

**Rise/Fall time:** <1ns (<900ps typ.)

**Overshoot:** <5%, typ.

**Jitter (rms):** <10ps

#### RAMP

**Time Range:** 1.0% to 99.9%

#### SINC (Sine(x)/x)

“0 Crossings” 4 to 100 cycles

#### GAUSSIAN

**Time Constant** 10 to 200

#### EXPONENTIAL PULSE

**Type:** Rise or Decay, selectable

**Time Constant:** -100 to 100

#### NOISE

**Type:** Repetitive

**Bandwidth:** 50MHz

#### DC

**Range:** -3V to +3V

#### PULSE

**Pulse Mode:** Single or double, programmable

**Polarity:** Normal, inverted or complement

**Period:** 4ns to 1000s

**Resolution:** 1ns

**Pulse Width:** 2ns to 1000s

**Rise/Fall Time:**

Fast <600ps, typ.

Linear 1ns to 1000s

#### High Time, Delay &

**Double Pulse Delay:** 1ns to 1000s

**Impedance:** 50Ω

**Amplitude Window:** 50mVp-p to 4Vp-p

Low Level -3V to +2.975V

High Level -2.975V to +3V

(1) Double into high impedance

#### NOTES:

1. All pulse parameters, except rise and fall times, may be freely programmed within the selected pulse period provided that the ratio between the period and the smallest incremental unit does not exceed the ratio of 512,000 to 1, hence the specifications above do not show maximum limit as each must be computed from the above relationship.
2. Rise and fall times, may be freely programmed provided that the ratio between the rise/fall time and the smallest incremental unit does not exceed the ratio of 100,000 to 1.
3. The sum of all pulse parameters must not exceed the pulse period setting

#### ARBITRARY WAVEFORMS

**Sample Rate:** 50kS/s to 625MS/s

**Vertical Resolution:** 12 bits

**Waveform Memory:** 512k points

**Min. Segment Size:** 64 points

**Resolution:** 16 points

**No. of Segments:** 1 to 1k

**Waveform Granularity:** 1 point

#### MODULATION

**Carrier Waveform:** Sine wave

**Carrier Frequency:** 1Hz to 250MHz

**Modulation Source:**

Internal FM, Arbitrary FM, Sweep  
External FSK, PSK

#### FM

**Modulating Shape:** Sine, square, triangle, ramp

**Modulating Freq.:** 1mHz to 100kHz

**Peak Deviation:** Up to 249MHz

#### FSK/PSK

**Baud Rate:** DC to 10Mbits/sec

**Resolution:** Frequency dependent.

**Carrier Phase:** 0 to 360° (Up to 125MHz)

#### SWEEP

**Sweep Type:** Linear or log

**Sweep Direction:** Up or down

**Sweep Time:** 1ms to 1000s

#### COMMON CHARACTERISTICS

##### FREQUENCY

**Resolution:** 9 digits

**Accuracy/Stability:** Same as reference

##### ACCURACY REFERENCE CLOCK

Internal 0.0001% (1 ppm TCXO)  
1ppm/year

External 10 MHz TTL, 50% 2%,

##### AMPLITUDE

**Range:** 50 mV to 4Vp-p into 50Ω;

Double into open circuit

**Resolution:** 4 digits

**Accuracy (1kHz):** ±(3% + 5 mV)

**Rise/Fall Time:** 1ns (typically <900ps)

**Overshoot:** 5%, typical

##### OFFSET

**Range:** 0 to ±2V, into 50Ω

**Resolution:** 4 digits

**Accuracy:** ±(3% + 50 mV)

##### OUTPUTS

###### MAIN OUTPUT

**Coupling:** DC coupled

**Type:** Single-ended

**Connector:** Front panel SMA

**Impedance:** 50Ω ±1%

**Protection:** Short Circuit to Ground, 10s max

# MODELS WS8251

## 250MHz Single Channel Arbitrary Function Generator



### Specification

#### SYNC / MARKER OUTPUT

<b>Connector:</b>	Front panel SMA
<b>Source:</b>	Channel 1
<b>Type:</b>	Single ended
<b>Waveform Type:</b>	BIT (16 points wide)
<b>Impedance:</b>	50Ω
<b>Amplitude:</b>	>2 V into 50Ω, 3V nominal into high impedance

#### Variable Position Control:

Range	0 to segment length
Resolution	16 points

#### INPUTS

##### TRIGGER INPUT

<b>Connector:</b>	Front panel SMA
<b>Input Impedance:</b>	50Ω, ±2%
<b>Polarity:</b>	Positive or negative
<b>Level:</b>	±5V, programmable
<b>Sensitivity:</b>	250mV
<b>Damage Level:</b>	±8V
<b>Min. Pulse Width:</b>	20ns

##### EXTERNAL REFERENCE INPUT

<b>Connector:</b>	Rear panel BNC
<b>Frequency:</b>	10MHz
<b>Impedance &amp; Level:</b>	
Default	10kΩ ±2%, TTL, 50% ±2%
Option	50Ω ±5%, 0dBm Sinewave

##### FILTERS

<b>Type:</b>	50MHz, 125MHz
--------------	---------------

##### RUNMODES

<b>Continuous:</b>	Free-run output of a waveform.
<b>Triggered:</b>	Upon trigger, outputs one waveform cycle. Last cycle always completed.
<b>Gated</b>	External signal enables generator. First output cycles synchronous with the active slope of the triggering signal. Last cycle of output waveform always completed
<b>Burst:</b>	Upon trigger, outputs a Dual or multiple pre-programmed number of waveform cycles from 1 through 1M.

#### TRIGGER CHARACTERISTICS

<b>System Delay:</b>	1 SCLK + 100ns
<b>Trigger Delay:</b>	0 to 512k SCLK
<b>Delay Resolution:</b>	1 sample clock

#### EXTERNAL

<b>Input:</b>	Front panel SMA
<b>Frequency:</b>	DC to 10 MHz
<b>Threshold Level:</b>	±5V, programmable
<b>Damage Level:</b>	±8V
<b>Sensitivity:</b>	250mV
<b>Min Pulse Width:</b>	20 ns
<b>Slope:</b>	Positive or negative
<b>Trigger Jitter:</b>	±1 sample clock

#### INTERNAL

<b>Range:</b>	0.1μs to 100s
<b>Resolution:</b>	4 digits, limited by 0.1μs
<b>Accuracy:</b>	0.1%
<b>Software:</b>	Soft trigger

#### MANUAL

<b>Source:</b>	Soft trigger command from the front panel or remote
----------------	---

#### GENERAL

<b>Voltage Range:</b>	85 to 265 VAC, 47-63 Hz
<b>Power Consumption:</b>	60W
<b>Display Type:</b>	Reflective Color LCD, back-lit
Size	3.8"
Resolution	320 x 240 pixels
<b>Interfaces:</b>	
USB	1 x rear, USB device, (A type)
LAN	100/10 BASE-T
GPIB	IEEE-488.2 - SCPI – 1993.0
<b>Dimensions:</b>	
With Feet	212 x 102 x 415 mm (WxHxD)
Without Feet	212 x 88 x 415 mm (WxHxD)
<b>Weight:</b>	
Without Package	3.5 kg
Shipping Weight	4 kg
<b>Temperature:</b>	
Operating	0°C - 50°C
Storage	-40°C to + 70°C.
<b>Humidity:</b>	85% RH, non condensing
<b>Safety:</b>	CE Marked, IEC61010-1
<b>Calibration:</b>	1 year
<b>Warranty <sup>(1)</sup>:</b>	3 years standard

#### ORDERING INFORMATION

MODEL	DESCRIPTION
WS8251	250MHz Single Channel Arbitrary Function Generator

#### ACCESSORIES

<b>S-Rack Mount:</b>	19" Single Rack Mounting Kit
<b>D-Rack Mount:</b>	19" Dual Rack Mounting Kit
<b>Case Kit:</b>	Professional Carrying Bag

<b>Note:</b>	Options and Accessories must be specified at the time of your purchase.
--------------	---

<sup>(1)</sup> Standard warranty in India is 1 year.