

TEGAM, Inc. • Ten Tegam Way • Geneva, Ohio 44041  
 PH (440) 466-6100 • FX (440) 466-6110 • sales@tegam.com

[www.tegam.com](http://www.tegam.com)



**17502 - Spade Lug Adapter**

This four-terminal cable assembly is used to connect a custom-built test fixture to the input of the 1750. The assembly includes gold-plated phosphor bronze spade lugs and a 3 ft (.914m) long, low inductance cable, for connection to the 1750. The 1750 includes one each of either the 17501 or 17502.



**17505 - Male LEMO Connector**

Heavy Duty LEMO connector and strain relief for construction of custom input cables or as a replacement connector.



**17503 - Sorting Fixture**

This fixture reduces component test handling time while ensuring a solid four-terminal connection. Rotation of the test heads allows the unit to accommodate axial-leaded components up to 3.0 in. (76mm) long and radial leaded components as narrow as .75 in. (19mm) between leads.



**17501 - Kelvin Klips**

Kelvin Klip assemblies are true four-terminal connections that allow precise measurement by minimizing the affects of lead resistance. Kelvin Klips are particularly useful for manual testing of leaded components such as resistors, inductors, & electrolytic capacitors, and can also be used on many other types of components & connectors. The gold-plated beryllium copper jaws ensure low contact resistance, low thermal emf to copper, high corrosion resistance, and a long life. The assembly includes a 3 ft. (.914m) long, low inductance cable for connection to the 1750. The 1750 includes one each of either the 17501 or 17502.



**17508 - Calibration Standard**

The 17508 is designed specifically for manufacturers who own a large number of 1750 units. The 17508 performs in-house verification and calibration on these units. The standard contains 11x2 resistance values from 2mΩ through 20MΩ.



**KK100 - Kelvin Klip Rebuild Kit**

Includes all hardware, tape and shrink tubing for the total replacement of 1 set of Kelvin Klips.



**CBL-3102 - BNC Cable**

BNC to BNC, RG 58/U, coaxial cable for use at the Trigger Input and Reading Done Output of the 1750. Cable length 1 meter (3.28 ft) long.



**GPIB (IEEE-488) Cables**

- 1583-3 - 1-meter GPIB buss cable
- 1583-6 - 2-meter GPIB buss cable
- 1583-9 - 3-meter GPIB buss cable

**Calibration Software**

This Visual Basic program automates the calibration of the 1750. The program communicates with the 1750 and provides step-by-step instructions for the calibration technician. A 17508 or equivalent calibration standard is required. This freeware can be downloaded from [www.tegam.com](http://www.tegam.com).

**For a FREE Catalog Call 800-666-1010**

**Your Global Source for Test and Measurement Solutions**