

# Accessories For Models 252,253,254

TEGAM, Inc. • Ten Tegam Way • Geneva, Ohio 44041 PH (440) 466-6100 • FX (440) 466-6110 • sales@tegam.com

www.tegam.com



#### 43072 Kelvin Klips

Kelvin Klip assemblies are true fourterminal connections that allow precise measurement by minimizing the affects of lead resistance. Kelvin Klips are particularly useful for manual testing of leaded components such as resistors, inductors, & electrolytic capacitors, and can also be used on many other types of components & connectors. The goldplated beryllium copper jaws ensure low contact resistance, low thermal emf to copper, high corrosion resistance, and a long life. The assembly includes a 3 ft. (.914m) long, low inductance cable for connection to the LCR meter. One set of Kelvin Klips is included with each meter.



## KK100 Kelvin Klip Rebuild Kit

Includes all hardware, tape and shrink tubing for the total replacement of 1 set of Kelvin Klips.



### 1412B Limits Comparator

This allows you to speed component sorting in incoming inspection and production applications. You can simultaneously sort by capacitance and dissipation factor. Nominal Value can be set to 4 1/2 digits of resolution. Two limit ranges, 10% and 100% of full scale, and independently set upper and lower limits give you outstanding flexibility and accuracy.



If you plan on transporting your LCR meter, this hard plastic dust cover provides good protection for the front panel. It is also a handy place to store test leads.



#### 2005B/SP5132 Chip Tweezer

Designed for manual sorting of chip components, these four-terminal tweezers make solid connections on chips up to 0.50 in. (12.7mm) long. The set includes a 5 ft. (1.5m) cable for connection to the LCR meter.



### 47422 Chip Tweezer Rebuild Kit

Tweezer tips are intended to last 100,000 to 500,000 operations. This tip replacement kit includes 12 replacement tips, 2 screws, and 1 wrench.



#### 46973 Input Protection

Provides input protection for Models 252, 253 and 254 against charged capacitors. The accessory plugs into the input connector on the front of the instrument. Includes input protection circuitry and matching Kelvin Klip assembly and 3 ft. (.914m) long, low-inductance cable.

For a FREE Catalog Call 800-666-1010