CERTIFICATE OF CALIBRATION

Issued By Transmille Ltd.

Date of Issue 09 December 2008

Certificate Number EXAMPLE

Page 1 of 2 Pages

Approved Signatory



Transmille Ltd.
Unit 4, Select Business Centre
Lodge Road
Staplehurst, Kent. TN12 0QW.
TEL 01580 890700 FAX 01580 890711

EXAMPLE CERTIFICATE

□ EXAMPLE
□ EXAMPLE

Date of Calibration: EXAMPLE

Customer:

Date Received: 03 December 2008

Instrument: System ID: EXAMPLE

Description: Torque Adapter
Manufacturer: TRANSMILLE
Model Number: EA014
Serial Number: EXAMPLE
Procedure Version: 1.00

Environmental Conditions

Temperature: 20°C +/- 1°C Mains Voltage: 240V +/- 12V Relative Humidity: 50% +/- 20% Mains Frequency: 50Hz +/- 1Hz

Comments

Instrument was placed in laboratory and allowed to stabilise before calibration.

The torque wrench was calibrated with reference to B.S.E.N. 26789: 1994

Measurements taken from zero to cancel out any fixtures readings

All Tests Passed calibration.

Traceability Information

Instrument descriptionSerial numberCertificate numberCal. DateCal. Period3010 Precision Multi-Product Calibrator107842C61512503/12/200852Norbar Torque Wrench AnalyserTL6188133515/08/2005208

Calibrated By: EXAMPLE

This certificate provides traceability of measurement to recognised National Standards, and to the units of measurement realised at the National Physical Laboratory or other recognised National Standards laboratories.

Copyright of this certificate is owned by the issuing laboratory and may not be reproduced except with the prior written approval of the issuing laboratory. This certificate complies with the requirements of BS EN ISO 10012:2003.

CERTIFICATE OF CALIBRATION

AFTER ADJUSTMENT RESULTS

Certificate Number EXAMPLE

Page 2 of 2 Pages

| Test Title | Tolerance | Applied Value | Reading | Pass/Fail |
|---------------------------------|-----------|---------------|---------|-----------|
| Peak hold function | | | Pass | |
| Continuous function | | | Pass | |
| Reset function | | | Pass | |
| TORQUE MEASUREMENTS | | | | |
| 10Nm | 200mNm | 10.0Nm | 10.0Nm | Pass |
| Scale Factor Used in VFP 1.0869 | | | | |

Uncertainties

Torque (Nm) $\pm 0.5\% \pm 0.02$ Nm