

# UT60E

# Modern Digital Multimeters



Registered Design No.: 0011438. 1M002

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.8%+1)
AC Voltage	4V/40V/400V/750V	±(1%+5)
DC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1%+2)
AC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Capacitance	40nF/400nF/4µF/40µF/100µF	±(3%+5)
Temperature (°C)	-40°C ~ 1000°C	±(1%+3)
Frequency	10Hz-10MHz	±(0.1%+3)
Duty Cycle	0.1%~99.9%	✓
Special Functions		
Fused 10A Range		✓
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
True RMS	AC	✓
Relative Mode		✓
Data Hold		✓
RS232C		✓
Display Backlight		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max Display	3999	✓

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	320g
Product Size	177 x 85 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip, RS232C Interface Cable, Software
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326mm (0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	26.6kg

\*Available at Extra Cost