

# UT60H

# Modern Digital Multimeters



## SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	4V/40V/400V/1000V	±(0.1%+5)
AC Voltage	4V/40V/400V/750V	±(1%+4)
DC Current	400µA/4000µA/40mA/400mA/10A	±(0.5%+10)
AC Current	400µA/4000µA/40mA/400mA/10A	±(1.2%+4)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(0.5%+10)
Capacitance	40nF/400nF/4µF/40µF/400µF/4mF/40mF	±(1.5%+20)
Temperature(°C)	-40°C ~ 400°C	±(1%+5)
Frequency	4kHz/40kHz/400kHz/4MHz/40MHz/400MHz	±(0.01%+3)
<b>Special Functions</b>		
Fused 10A Range	✓	
Auto Ranging	✓	
4~20mA Loop	✓	
EF Function	✓	
Diode	✓	
Continuity Buzzer	✓	
True RMS	AC	
Max/Min Mode	✓	
Relative Mode	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	39999	
Input Impedance for DC Voltage Measurement	3999 (on functions of AC Voltage, AC Current, Diode and Continuity Buzzer) 39999 (on functions of DC Voltage, DC Current, Resistance, Capacitance, Frequency, EF Function and 4-20mA Loop)	
Analogue Bar Graph	✓	



UL/cUL Pending

Registered Design No.: 0011438. 1M002

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	320g
Product Size	177 x 85 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Multi-Purpose Socket, Alligator Clip
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326mm (0.078CBM Per Standard Carton)
Standard Carton Gross Weight	Around 25kg