



VOLTCRAFT®

VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY

“For more than 25 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft’s success.”

BS-20 ENDOSCOPE

Nº 12 22 49

CE

VERSION 08/09

Positions difficult to access can be explored effortlessly. The approximately 92 cm long, flexible gooseneck is ideal for checking pipes and lines at home or in the car for damage or corrosion, etc.

HIGHLIGHTS

Mini colour camera with LED lighting //

6 cm large monitor with 320 x 234 pixels //

Dimmable LED camera light //

NTSC video output //

Magnetic and hook attachment //



GENERAL SPECIFICATIONS

BENDING RADIUS (MAX.): 45 mm **MIN. FOCUS:** 30 mm **ANGLE OF VIEW:** 54° **PROBES Ø:** 10 mm **VOLTAGE SUPPLY:** 4 x 1,5 V Mignon batteries (type AA, not included) **PROTECTION TYPE:** Probe IP67 **WEIGHT:** 370 g **TOTAL LENGTH:** approx. 115 cm

TECHNICAL DATA

TFT monitor:	6 cm (2.4") screen size
Resolution:	320 x 234 pixels
Sensitivity:	0.7 V/lux-sec.
White balance:	automatic
Exposure:	automatic
Video format:	NTSC
Camera Ø:	10 mm
Camera lighting:	2 LEDs, white
Gooseneck Length:	approx. 90 cm
Power input:	max. 200 mA
Operating temperature:	0 °C to +45 °C

PACKAGE CONTENT

Endoscope // Magnet attachment // Hook attachment // Case // Video cable // Operating instructions

This data sheet is published by Voltcraft®, Lindenweg 15, D-92242 Hirschau / Germany, Phone +49 180 586 582 7. The data sheet reflects the current technical specifications at time of print. We reserve the right to change the technical or physical specifications.