




BluePhase Synthesizer

Ultra Low Phase Noise Frequency Synthesizer

WA5200

(100 MHz Input from Source Model 5000 with Option 2)

Outputs: 100, 200, 300, 400, 500, 600, 700, 800, 900 MHz, 1 GHz



OUTPUTS

POWER	+12 dBm $\pm$ 2 dB into 50 Ω with +13 dBm input					
HARMONICS	$\leq$ -25 dBc					
SUB-HARMONICS	$\leq$ -60 dBc					
SPURIOUS	$\leq$ -80 dBc,					
PHASE NOISE L(F)	10 Hz	100 Hz	1 KHz	10 KHz	100 KHz	
100 MHz	-100 dBc	-130 dBc	-156 dBc	-172 dBc	-173 dBc	
200 MHz	-94 dBc	-124 dBc	-150 dBc	-166 dBc	-167 dBc	
300 MHz	-90 dBc	-120 dBc	-146 dBc	-162 dBc	-163 dBc	
400 MHz	-88 dBc	-118 dBc	-144 dBc	-160 dBc	-161 dBc	
500 MHz	-86 dBc	-116 dBc	-142 dBc	-158 dBc	-159 dBc	
600 MHz	-84 dBc	-114 dBc	-140 dBc	-156 dBc	-157 dBc	
700 MHz	-83 dBc	-113 dBc	-139 dBc	-155 dBc	-156 dBc	
800 MHz	-82 dBc	-112 dBc	-138 dBc	-154 dBc	-155 dBc	
900 MHz	-81 dBc	-111 dBc	-137 dBc	-153 dBc	-154 dBc	
1000 MHz	-80 dBc	-110 dBc	-136 dBc	-152 dBc	-153 dBc	

REFERENCE INPUT

100 MHz +13 dBm $\pm$ 2 dB into 50 Ω (rear input)

ENVIRONMENT

Laboratory Environment
0 to +50°C Operating Temperature

MECHANICAL

Size	Standard 19" rack mount, 22 deep, 5.25" high
RF Connectors	SMA female
AC Connector	IEC-320, EMI filtered, switched, and fused

POWER

Warm-up Time	1 hour, maximum; 15 minutes, typical (@ +25°C)
AC Power Supply	115 VAC, 50/60 Hz

Wenzel Associates, Inc. • 2215 Kramer Lane. • Austin, Texas 78758 USA

512-835-2038 • fax 512-719-4086

<http://www.wenzel.com> • e-mail: sales@wenzel.com

Model

WA5200

Rev.

—