

Fleet Power 2500

xantrex



Provides 2500 continuous watts of silent and efficient AC household power from your vehicle's DC batteries

Reliable AC Power for Service and Utility Vehicles

Fleet Power 2500 provides 2500 continuous watts of silent and efficient AC household power from your vehicle's DC batteries. When plugged into an electrical outlet, a built-in 130-amp, 3-stage charger automatically charges your batteries without the risk of overcharge. It comes with a transfer switch that automatically selects either an external or inverter power source. It is ideal for powering loads such as motors with high surge.

Built for hands-off operation, the Fleet Power can be used with the optional Fleet Power Remote for on/off control and basic system monitoring. For advanced system monitoring and control, Fleet Power 2500 can be paired with optional Link instrumentation.

Product Features

- ▶ 2500-watt inverter (7500-watt surge)
- ▶ 130 A automatic 3-stage battery charger
- ▶ Built-in transfer switch automatically transfers between inverter power and incoming AC power
- ▶ Power sharing increases available AC during charging
- ▶ GFCI receptacle and hardwire connections
- ▶ High surge capability
- ▶ Durable design and easy to install horizontally or vertically in compact spaces
- ▶ One year warranty

Protection Features

- ▶ Over voltage and under voltage protection
- ▶ Over-temperature protection
- ▶ Overload protection
- ▶ Short circuit protection

Accessories

- ▶ Fleet Power Remote (optional)
- ▶ Link 1000 or 2000 (optional)
- ▶ Battery cables (included)



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5
800 670 0707 Toll Free
604 420 1591 Fax

5916 195th Street NE
Arlington, Washington
USA 98223
800 446 6180 Toll Free
360 925 5143 Fax

www.xantrex.com

Fleet Power 2500 - 2500 Watt Inverter/Charger

Electrical Specifications - Inverter

Output power	2500 W
Surge rating	7500 W
Output frequency regulation	60 Hz +/- 0.05%
Inverter voltage regulation	120 V +/-5% true RMS
Output waveform	Modified sine wave
Efficiency	86%
Peak efficiency	94%
Battery voltage (nominal)	12 VDC
DC input voltage range	10 – 15.5 VDC
Low battery cutout	10 VDC
AC outputs	GFCI and hardwire
AC transfer switch	30 A

Electrical Specifications - Charger

Charge rate	130 A
AC input voltage range	90 – 130 VAC
Battery voltage range	10.0 – 15.5 VDC
AC input current	27 A AC
Input voltage	120 VAC
Bulk charge voltage	14.4 VDC
Float charge voltage	13.5 VDC
Equalize charge voltage	16.3 VDC
Charge control	3-stage
Equalization stage	Manual
Compatible battery types	Wet / Gel
DC outputs	1

General Specifications

Optional remotes	Freedom Basic Remote or Link
Battery cables	Included (4')
Dimensions (H x W x L)	8.75 x 11.5 x 12.0" (222 x 292 x 305 mm)
Weight	56 lb (25 kg)
Warranty	One year
Part numbers	81-0262-12
	82-0108-01 (optional Fleet Power remote)
	84-2019-02 (Link 1000)
	84-2000-06 (Link 2000)

Regulatory Approvals

UL and cUL listed to UL 458 and CSA C22.2 No. 107.1

Note: Specifications subject to change without notice.