

Xantrex™ XW System Control Panel



The Xantrex™ XW System Control Panel (XW SCP) features a graphical, backlit LCD display that provides system configuration and diagnostic information for devices connected to the Xanbus™-enabled network. The XW SCP gives a single point of control to setup and monitor an entire system, which may consist of multiple XW Inverter/Chargers, XW Solar Charge Controllers and other components.

The XW System Control Panel can be flush-mounted or surface-mounted. Mounting brackets are provided for each.

Operational Features

- ▶ Compatibility – connects to additional Xanbus™-enabled XW System devices without requiring additional hubs, control cards, or other device-specific control panels
- ▶ Internal clock – keeps time for the entire system
- ▶ Audible alarm – when enabled, alerts users when a fault condition arises
- ▶ Low power consumption – automatically turns off backlight after a period of inactivity
- ▶ Non-volatile memory – preserves System Control Panel settings if network power is interrupted or network communication is disrupted

Product Features

- ▶ Graphical 128 x 64 pixel, backlit LCD screen
- ▶ Large, tactile keypad buttons
- ▶ Intuitive onscreen menu system (basic and advanced)
- ▶ Xanbus™-enabled

Xantrex Technology Inc.

Customer Service/Technical Support

customerservice@xantrex.com

Toll free: 1-800-670-0707

www.xantrex.com

Xantrex™ XW System Control Panel

Electrical Specifications

Display	128 x 64 pixel LCD with white LED backlight
---------	---

Mechanical Specifications

Dimensions (H x W x D)	6 x 4 x 1 9/16" (152 x 103 x 40 mm)
Weight	0.46 lb (207 kg)
Mounting	Flush or surface mount, hardware included
Shipping weight	1.72 lb (0.78 kg)
Dimensions (shipping)	10.5 x 8.5 x 2.5" (267 x 216 x 64 mm)
Standard warranty	Five years
Part number	865-1050

Environmental Specifications

Operating temperature range (full power)	-4 to 122°F (-20 to 50°C)
Storage temperature	-40 to 185°F (-40 to 85 °C)

Regulatory Compliance

Safety	CSA certified to CSA 107.1-01 and UL 458 including Marine Supplement
EMC	FCC Part 15B Class B Industry Canada ICES-0003 Class B

Optional Accessories

Network cables:

3 feet (0.9 m)	809-0935
5 feet (1.5 m)	809-0936
7 feet (2.0 m)	809-0937
10 feet (3.0 m)	809-0938
14 feet (4.3 m)	809-0939
25 feet (7.6 m)	809-0940
50 feet (15.2 m)	809-0941
75 feet (22.9 m)	809-0942

Network terminators:

Male (two per pack): 809-0901
Female (two per pack): 809-0905

Specifications subject to change without notice.

For more information on the XW System please visit www.xantrex.com/xw