

DURACELL®

DIGITAL INVERTER 400

Portable Power



Converts Power from your Vehicle to Run & Recharge AC Devices

Duracell® Digital Inverter 400 is designed to power electronics on the go, this compact digital inverter combines innovative industrial design with an advanced interactive LED display. This provides the user with instant feedback on input and output voltage, and valuable troubleshooting guidance. The digital inverter converts 12-volt DC battery power from a vehicle into 120-volt household AC electricity. It includes two three-prong household AC outlets, allowing you to operate and recharge a wide range of mobile devices. The Duracell® Digital Inverter 400 provides a convenient and powerful means of accessing AC power.

Product Features:

- ▶ 320 watts of continuous power with 700 watts surge
- ▶ Digital display technology providing valuable instant feedback
- ▶ Automatic shutdown protection against overload, over-temperature and low/high battery conditions
- ▶ DC terminals for lighter socket or direct battery connection
- ▶ Two, three-prong grounded AC outlets
- ▶ Fault-code display makes troubleshooting easier
- ▶ Audible alarm signals low-battery condition

Product Applications:

- ▶ Entertainment electronics: camcorder, video game console, stereo system, 13" TV/VCR combo, 27" TV/VCR combo
- ▶ Office equipment: cell phone, laptop computer, portable work light



Portable power in your vehicle



Retail Package



www.duracellpower.com

Product Specifications

AC

AC output power (continuous)	320 W
AC output power (5 minutes)	400 W
AC output surge power (maximum)	640 W
AC output voltage (nominal)	115 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Battery drain with no AC load	0.3 A (at 12 V input)
Efficiency (maximum)	90%
DC input voltage range	10.5 - 15.5 Vdc
Low-battery alarm trigger point (nominal)	11.0 V
Low-battery shutdown point (nominal)	10.5 V
High battery shutdown point (nominal)	15.5 V

General Specifications


Part number	813-0400-07
Unit dimensions (L x W x H)	6.125 x 4.125 x 2.2" (15.6 x 10.5 x 5.6 cm)
Unit weight	0.9 lb (0.4 kg)
Warranty	One year
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	32°F to 104°F (0°C to 40°C)

Packaging Specifications

	Retail Package*	Inner Carton	Master Carton*	Pallet
Size (LxWxH)	6.5 x 3.625 x 9.25" (16.5 x 9.2 x 23.5 cm)	18.75 x 7.25 x 10.5" (47.6 x 18.4 x 26.7 cm)	19.25 x 15.25 x 11.25" (48.9 x 38.7 x 28.6 cm)	40 x 48 x 71.3" (101.6 x 121.9 x 180.9 cm)
Count	1	5	10	240
Weight	2.1 lb (0.95 kg)	11 lb (4.99kg)	24.2 lb (11 kg)	N/A
Volume	N/A	N/A	3,303 cu.in.	N/A
UPC number	715535890186			

* Box

Specifications subject to change without notice



Xantrex Technology Inc.

Headquarters	5916 195th Street NE
8999 Nelson Way	Arlington, Washington
Burnaby, British Columbia	USA 98223
Canada V5A 4B5	