

DURACELL®

INVERTER 1000 & 1500

Portable Power



Heavy Duty Portable Power for Work, Play, and Emergencies

Duracell® Inverters convert 12-volt DC battery power to 120-volt AC household electricity so you can operate appliances, electronics and tools onboard your minivan, truck, RV or boat. These Inverters are also suitable for contractors who want to operate small power tools from their work vehicle, and are designed for easy installation and operation.

Product Features:

- ▶ Portable power for AC products
- ▶ Two AC outlets for connecting multiple loads
- ▶ High surge capacity for products that require more power to start
- ▶ High efficiency – converts virtually all of the battery's available power to AC
- ▶ Mounting brackets for convenient installation
- ▶ Heavy duty stud-connection mounting

Product Applications:

- ▶ Handheld power tools: drills, jigsaws, sanders and buffers
- ▶ Household appliances: compact microwave ovens, bread makers, food processors, small bar refrigerators, small vacuum cleaners, fluorescent and incandescent lights, sewing machines and fans
- ▶ Entertainment electronics: televisions, VCRs, video games, stereos, musical instruments and satellite equipment
- ▶ Office equipment: computers with 17" monitors, fax machines

Protection Features:

- ▶ Overload and over-temperature shutdown
- ▶ Over-voltage protection (15.0 Vdc)
- ▶ Low-voltage alarm (11.0 Vdc)
- ▶ Low-voltage cut-out (10.5 Vdc)



Retail Package



www.duracellpower.com

Duracell® Inverter 1000 VLI

Product Specifications	
AC	
AC output surge capacity (peak)	2000 W
AC output power (max. continuous)	1000 W
AC output voltage	115 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Optimum efficiency	90%
No-load current draw	< 0.3 Aac
Input voltage range	10.5 - 15.0 Vdc
AC receptacle	Two

General Specifications	
Part number	813-1000-07
Unit dimensions (L x W x H)	12 x 6 x 3" (30.5 x 15.2 x 7.6 cm)
Unit weight	4.2 lb (1.0 kg)
Warranty	Six months
Operating temperature range	32°F to 104°F (0°C to 40°C)
Storage temperature	-4°F to 140°F (-20°C to 60°C)

Duracell® Inverter 1500 VLI

Product Specifications	
AC	
AC output surge capacity (peak)	3000 W
AC output power (max. continuous)	1500 W
AC output voltage	115 V
AC output frequency	60 Hz
AC output waveform	Modified sine wave
Optimum efficiency	90%
No-load current draw	< 0.3 Adc
Input voltage range	10.5 - 15.0 Vdc
AC receptacle	Two

General Specifications	
Part number	813-1500-07
Unit dimensions (L x W x H)	14.5 x 6 x 3" (36.8 x 15.2 x 7.6 cm)
Unit weight	5.6 lb (2.5 kg)
Warranty	Three months
Operating temperature range	32°F to 104°F (0°C to 40°C)
Storage temperature	-4°F to 140°F (-20°C to 60°C)

Packaging Specifications - Duracell® Inverter 1000 VLI

	Retail Package*	Master Carton	Pallet
Size (L x W x H)	14 x 5.25 x 8.25" (35.6 x 13.3 x 21 cm)	17 x 14.5 x 11.75" (43.2 x 36.8 x 29.8 cm)	40 x 48 x 74.5" (101.6 x 121.9 x 189.2 cm)
Count	1	4	144
Weight	5.3 lb (2.4 kg)	24 lb (10.9 kg)	N/A
Volume	N/A	2,897 cu.in.	N/A
UPC number	715535890131		


* Box

Packaging Specifications - Duracell® Inverter 1500 VLI

	Retail Package*	Master Carton	Pallet
Size (L x W x H)	16.25 x 5.25 x 8.25" (41.3 x 13.3 x 21 cm)	17.25 x 17 x 11.375" (43.8 x 43.2 x 28.9 cm)	40 x 48 x 72.3" (101.6 x 121.9 x 183.5 cm)
Count	1	1	96
Weight	8.4 lb (3.8 kg)	36.3 lb (16.4 kg)	N/A
Volume	N/A	3,336 cu.in.	N/A
UPC number	715535890148		

* Box

Specifications subject to change without notice



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5

5916 195th Street NE
Arlington, Washington
USA 98223