



Heavy-Duty Power for Trucks, Boats and RVs

The XPower™ Inverter 5000 is a powerful, modified sine wave inverter that connects easily to a 12-volt battery to provide up to 5000 watts of AC power for demanding applications. This inverter is ideal for customers requiring power to operate heavy duty and multiple applications. Designed with a small footprint and for easy installation in your truck, service vehicle, RV, or boat. The XPower Inverter 5000 is the most powerful model in the XPower inverter lineup.

Product Features

- ▶ Portable power for AC products rated up to 5000 watts
- ▶ Four GFCI AC outlets, each equipped with a 20-amp breaker
- ▶ High surge capacity for products with demanding startup requirements
- ▶ High efficiency – converts virtually all the battery's available power to AC
- ▶ Easy-to-read digital display shows battery voltage, current, and AC power
- ▶ Easy to access AC hardware
- ▶ Heavy duty input bolt connectors
- ▶ Remote on/off switch

Protection Features

- ▶ Overload and over-temperature shutdown
- ▶ AC backfeed
- ▶ Output short circuit
- ▶ Over-voltage protection
- ▶ Low-voltage alarm and cut-out

Product Applications

Household Appliances: microwave ovens, bread makers, food processors, toasters, coffee makers, refrigerators, vacuum cleaners, fluorescent, and incandescent lights, sewing machines, and fans

Power Tools: drills, jigsaws, sanders, buffers, circular saws, and grinders

Entertainment Electronics: 36" televisions, DVD players, video game consoles, stereos, musical instruments, and satellite equipment



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5
800 670 0707 Toll Free
604 420 1591 Fax

www.xantrex.com

XPower™ Inverter 5000

Product Specifications

Models	Inverter 5000
AC output surge capacity (peak)	10000 W
AC output power (continuous)	5000 W
AC output voltage	120 Vac
AC output frequency	60 Hz
Output wave form	Modified sine wave
No load draw	< 0.6 A
Input voltage range	10.5 to 15.5 Vdc
Peak efficiency	90%


General Specifications

Operating temperature	0°C to 40°C
Storage temperature	-20°C to 60°C
AC outlets	Four GFCI receptacles
Unit weight	24.1 lb (10.9 kg)
Unit dimensions (L x W x H)	19.5 x 8.0 x 6.25" (52 x 20.5 x 16 cm)
Warranty	Twelve months
Part number	813-5000

Packaging Specifications

	Retail Package	Master Carton
Size (L x W x H)	23.5 x 10.25 x 12" (59.6 x 26 x 30.4 cm)	24 x 11 x 13" (60.9 x 27.9 x 33.0 cm)
Weight	27 lb (12.2 kg)	30 lb (13.6 kg)
UPC number	715535890452	

Note: Specifications subject to change without notice.



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5