

DURACELL®

POWERSOURCE MINI

DC to DC Lithium-Ion Battery Pack



Rechargeable Portable Power

Power on the Go

The Duracell® PowerSource Mini gives you power to stay productive and entertained when you're on the go, by recharging your cell phone, BlackBerry®, iPod®, or PSP®. The PowerSource Mini features a mini USB pivot arm so you can connect it directly to your BlackBerry® and new Motorola® phones such as the Razr®, Rokr® and more. A second USB port is also featured so you can power two devices at once. The 0.5 amp USB PowerSource Mini's internal lithium-ion battery can be recharged at home through a lightweight AC charger, through a vehicle's DC socket, or at your computer from its USB port.

The PowerSource Mobile Mini is sleek, lightweight and powerful, and it fits easily into your laptop bag or purse, so you're never without power when you're on the go.

Product Features

- ▶ Mini USB connector with pivoting arm for direct connection to mobile devices
- ▶ USB charge port
- ▶ Blue LED On/Off indicator
- ▶ LED battery status/charge status indicator
- ▶ Recharges from a standard wall outlet, a vehicle, or a computer
- ▶ One year warranty

Protection Features

- ▶ Low battery voltage shutdown (2.5 volts DC with automatic reset)

Retail Package



Visit www.duracellpower.com
(will be posted in Q2)

Product Specifications

DC

| | |
|---------------------------|---------|
| Internal battery type | Li-ion |
| Internal battery capacity | 3 Ah |
| Internal battery voltage | 3.7 Vdc |

General Specifications

| | |
|-----------------------------|---|
| Part number | 852-0257 |
| Unit Dimensions (L x W x H) | 2.6 x 0.95 x 3.25" (6.7 x 2.4 x 8.2 cm) |
| Unit Weight | 0.3 lb (0.12 kg) |
| Warranty | One year |
| Operating Temperature | 32°F to 104°F (0°C to 40°C) |
| Storage Temperature | 32°F to 86°F (0°C to 30°C) |

Charging Time

| | | | | |
|--|-------|-------|-------|-------|
| Battery Discharge Levels | 100% | 75% | 50% | 25% |
| Recharging time (from 120 Vac or 12 Vdc) | 3.4 h | 2.6 h | 1.9 h | 1.1 h |

*Maximum charging time occurs when battery is completely discharged

Packaging Specifications

| Packaging | Individual (Blister Pack) | Inner Carton | Master Carton |
|------------------|---|---|--|
| Count | 1 | 10 | 20 |
| Size (L x H x D) | 6.6 x 3.3 x 7.6" (16.7 x 8.5 x 19.4 cm) | 7.5 x 21.3 x 8" (19.1 x 54.2 x 20.4 cm) | 8.5 x 21.9 x 16.5" (21.5 x 55.5 x 42 cm) |
| Weight | 0.68 lb (0.31 kg) | 7.38 lb (3.56 kg) | 17.5 lb (7.95 kg) |
| UPC | 71553589568 | | |


Specifications subject to change without notice.

Charging System

| | |
|----------------------------------|---------|
| AC charger bulk charging current | 0.8 A |
| Peak charging voltage | 5.5 Vdc |
| Charge restart voltage | 3.5 V |
| Charger input socket current | 0.25 A |

Application Charge Times

| | |
|--------------|-------|
| iPod® | 3 h |
| Mini iPod® | 2.5 h |
| iPod® Nano | 3 h |
| palmOne™ PDA | 3.5 h |
| BlackBerry® | 3.5 h |



Xantrex Technology Inc.

Headquarters
8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5

www.xantrex.com