


# GPIB-M Multichannel Interface

Digital Interface For Multiple Unit Programming, Control, and Auto Sequencing




Front and rear views of a Xantrex XDC 6 kW, XFR 2.8 kW and 1.2 kW, XHR 1 kW, XPD 500 W, and an HPD 300 W configured with GPIB-M.

## Conveniently Connects Multiple Units

The Xantrex GPIB-M multichannel interface is a full-featured, IEEE 488.2 SCPI compatible interface option usable with all Xantrex programmable DC power supplies from 60 W to 12 kW. GPIB-M offers the flexibility to remotely control up to 50 supplies - each with a GPIB-M or CANbus communications link installed - by multichannel addressing from a single GPIB address.

## Provides Auto Sequence Capability

GPIB-M uses the functionality from the Xantrex Digital Controlled power supply (XDC Series) and makes it available for other Xantrex products - the XFR, XHR, XPD, HPD, and XT Series. The auto sequencing capability enables test sequences, which have been programmed externally via GPIB, to be launched with a GPIB command. Up to ten different test programs, each with up to 99 voltage level steps ranging from milliseconds to days, can be executed by a GPIB command or an external trigger. This sequencing capability can be used for a variety of applications including constructing simple voltage ramps, battery charging and simulation of battery voltage at engine start-up, component testing, and MIL 704E testing.



## Product Features

- ▶ High speed 16-bit programming and readback of voltage and current
- ▶ Programmable soft limits for voltage and current
- ▶ Software calibration
- ▶ Programmable auxiliary status lines
- ▶ Local Lockout capability
- ▶ Remote interlock and trigger lines
- ▶ Selectable standby, programmed sequence and other power-on defaults
- ▶ Extensive SCPI command set for control and status monitoring
- ▶ Support of legacy Xantrex GPIB commands

## Protection Features

- ▶ Programmable over voltage, under voltage, and current protection
- ▶ Shutdown or warning for over/under-programmed trip points

## Xantrex Technology Inc.

Headquarters  
8999 Nelson Way  
Burnaby, British Columbia  
Canada V5A 4B5  
800 670 0707 Toll Free  
604 420 1591 Fax

5916 195th Northeast  
Arlington, Washington  
USA 98223  
800 446 6180 Toll Free  
360 925 5144 Fax

# GPIB-M Multichannel Interface

Digital Interface For Multiple Unit Programming, Control, and Auto Sequencing

## Typical Specifications With GPIB-M or CANbus Installed

<b>XFR 2.8 kW</b>		<b>7.5-300</b>	<b>12-220</b>	<b>20-130</b>	<b>33-85</b>	<b>40-70</b>	<b>60-46</b>	<b>100-28</b>	<b>150-18</b>	<b>300-9</b>	<b>600-4</b>
<b>Program Resolution</b>	<b>Voltage (mV)</b>	0.13	0.2	0.34	0.55	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	5.04	3.69	2.18	1.50	1.17	0.77	0.47	0.3	0.15	0.07
<b>Program Accuracy</b>	<b>Voltage (mV) (0.2% + 10 mV)</b>	25	34	50	76	90	130	210	310	610	1210
	<b>Current (mA) (0.3% +10 mA)</b>	910	670	400	265	220	148	94	64	37	22
<b>Readback Resolution</b>	<b>Voltage (mV)</b>	0.13	0.2	0.34	0.55	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	5.04	3.69	2.18	1.50	1.17	0.77	0.47	0.3	0.15	0.07
<b>Readback Accuracy</b>	<b>Voltage (mV) (0.2% + 20 mV)</b>	35	44	60	86	100	140	220	320	620	1220
	<b>Current (mA) (0.3% +20 mA)</b>	920	680	410	275	230	158	104	74	47	32

<b>XFR 1.2 kW</b>		<b>6-200</b>	<b>7.5-140</b>	<b>12-100</b>	<b>20-60</b>	<b>35-35</b>	<b>40-30</b>	<b>60-20</b>	<b>100-12</b>	<b>150-8</b>	<b>300-4</b>	<b>600-2</b>
<b>Program Resolution</b>	<b>Voltage (mV)</b>	0.10	0.13	0.2	0.34	0.59	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	3.36	2.35	1.68	1.01	0.59	0.5	0.34	0.2	0.13	0.07	0.03
<b>Program Accuracy</b>	<b>Voltage (mV) (0.2% + 10 mV)</b>	22	25	34	50	80	90	130	210	310	610	1210
	<b>Current (mA) (0.3% +10 mA)</b>	610	430	310	190	115	100	70	46	34	22	16
<b>Readback Resolution</b>	<b>Voltage (mV)</b>	0.10	0.13	0.2	0.34	0.59	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	3.36	2.35	1.68	1.01	0.59	0.5	0.34	0.2	0.13	0.07	0.03
<b>Readback Accuracy</b>	<b>Voltage (mV) (0.2% + 20 mV)</b>	32	35	44	60	90	100	140	220	320	620	1220
	<b>Current (mA) (0.3% +20 mA)</b>	620	440	320	200	125	110	80	56	44	32	26

<b>XHR 1 kW</b>		<b>7.5-130</b>	<b>20-50</b>	<b>33-33</b>	<b>40-25</b>	<b>60-18</b>	<b>100-10</b>	<b>150-7</b>	<b>300-3.5</b>	<b>600-1.7</b>
<b>Program Resolution</b>	<b>Voltage (mV)</b>	0.13	0.34	0.55	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	2.18	0.84	0.55	0.42	0.3	0.17	0.12	0.06	0.03
<b>Program Accuracy</b>	<b>Voltage (mV) (0.2% + 10 mV)</b>	25	50	76	90	130	210	310	610	1210
	<b>Current (mA) (0.3% +10 mA)</b>	400	160	109	85	64	40	31	21	15
<b>Readback Resolution</b>	<b>Voltage (mV)</b>	0.13	0.34	0.55	0.67	1.01	1.68	2.52	5.04	10.1
	<b>Current (mA)</b>	2.18	0.84	0.55	0.42	0.3	0.17	0.12	0.06	0.03
<b>Readback Accuracy</b>	<b>Voltage (mV) (0.2% + 20 mV)</b>	35	60	86	100	140	220	320	620	1220
	<b>Current (mA) (0.3% +20 mA)</b>	410	170	119	95	74	50	41	31	25

<b>XPD 500 W</b>		<b>7.5-67</b>	<b>18-30</b>	<b>33-16</b>	<b>60-9</b>	<b>120-4.5</b>
<b>Program Resolution</b>	<b>Voltage (mV)</b>	0.13	0.30	0.55	1.01	2.01
	<b>Current (mA)</b>	1.12	0.50	0.27	0.15	0.08
<b>Program Accuracy</b>	<b>Voltage (mV) (0.2%+10 mV)</b>	25	46	76	130	250
	<b>Current (mA) (0.3%+10 mA)</b>	211	100	58	37	23.5
<b>Readback Resolution</b>	<b>Voltage (mV)</b>	0.13	0.30	0.55	1.01	2.01
	<b>Current (mA)</b>	1.12	0.50	0.27	0.15	0.08
<b>Readback Accuracy</b>	<b>Voltage (mV) (0.2%+20 mV)</b>	35	56	86	140	260
	<b>Current (mA) (0.3%+20 mA)</b>	221	110	68	47	33.5

<b>HPD 300 W and XT 60 W</b>		<b>HPD</b>	<b>15-20</b>	<b>30-10</b>	<b>60-5</b>	<b>XT</b>	<b>7-6</b>	<b>15-4</b>	<b>20-3</b>	<b>30-2</b>	<b>60-1</b>	<b>120-0.5</b>	<b>250-0.25</b>
<b>Program Resolution</b>	<b>Voltage (mV)</b>		0.25	0.5	1.01		0.12	0.25	0.34	0.5	1.01	2.01	4.2
	<b>Current (mA)</b>		0.34	0.17	0.08		0.1	0.07	0.05	0.03	0.02	0.01	0.01
<b>Program Accuracy</b>	<b>Voltage (mV) (0.2%+10 mV)</b>		40	70	130		24	40	50	70	130	250	510
	<b>Current (mA) (0.3%+10 mA)</b>		70	40	25		28	22	19	16	13	11.5	10.8
<b>Readback Resolution</b>	<b>Voltage (mV)</b>		0.25	0.5	1.01		0.12	0.25	0.34	0.5	1.01	2.01	4.2
	<b>Current (mA)</b>		0.34	0.17	0.08		0.1	0.07	0.05	0.03	0.02	0.01	0.01
<b>Readback Accuracy</b>	<b>Voltage (mV) (0.2%+20 mV)</b>		50	80	140		34	50	60	80	140	260	520
	<b>Current (mA) (0.3%+20 mV)</b>		80	50	35		38	32	29	26	23	21.5	21

Note: Specifications subject to change without notice.

For more information, call 800 667 8422 or visit [www.xantrex.com](http://www.xantrex.com).