XS12-200 Sealed Battery

Features

- 12-volt, 200 amp-hour battery
- easily configured for battery banks of higher capacity or voltage
- sealed, non-spillable VRLA design
- · heavy-duty lead calcium grids

- 10-year standby service life design
- maintenance free (no water to add)
- wide temperature range of operation
- threaded insert terminals
- durable high grade ABS plastic case with built in lifting handles



XS12-200 Sealed Battery

A 12-volt, 200-amp hour, AGM battery designed for backup and solar applications.

The XS12-200 battery is an ideal building block for commercial/ residential backup power systems. It is a maintenance free, valve regulated, lead acid battery (VRLA) using the latest recombinant technology, virtually eliminating battery gassing in normal operations. The XS series has been designed for a 10-year service life under optimal standby conditions.

This battery can be used on its own for small 12-volt systems or in multiples for higher voltage/capacity banks. Stackable, powder-coated, steel battery enclosures are also available to house your batteries.

Meets Recognized Safety Standards

UL recognized and meets the requirements of the International Air Transport Association's "Non-Dangerous Goods" classification (41st edition, section 4.4, special provision A67). This non-spillable battery is suitable for indoor use and is ideal for standby backup power systems, uninterruptible power supplies (UPS), emergency lighting, alarm systems, and solar/alternative energy systems.





XS12-200 **Sealed Battery**

Specifications


Model XS12-200 Sealed Battery	Part No. 808-7014		
Electrical Specifications			
Voltage	12 volt		
Capacity	200 amp-hour (<i>10 hr.</i>)		
Mechanical Specifications			
Dimensions (L x W x H)	20.55"L x 9.37"W x 8.78"H (522mm L x 238mm W x 223mm H)		
Weight	141 lbs. (<i>64 kg</i>)		
Construction	ABS high impact plastic case 94HB rated		
Terminals	Threaded insert to fit M8 bolt, 8mm depth		
Optional Accessories	Model number	Part number	
x-Bus 250-amp flexible bus bar	FB-250	808-7008	
x-Bus 450-amp flexible bus bar	FB-450	808-7009	
Battery Enclosure	BE	808-7012	accommodates two XS12-200 batteries


Specifications subject to change without notice.






Dimensional Views









Xantrex Technology Inc. 8587 Baxter Place Burnaby, BC Canada V5A 4V7

t: 800-667-8422 604-415-4600 **f:** 604-415-4674 www.xantrex.com