

# DURACELL®

## POWERPACK 300

Portable & Emergency  
Power



### Provides Portable Emergency Power

The Duracell® Powerpack 300 is easy to use and ready when you need it most. It gives you the power to jump-start your vehicle or inflate tires during roadside emergencies. Its detachable ultra bright LED flashlight makes a power outage easier to deal with. Combine this with 300 watts of portable AC power to operate small appliance or recharge electronics, and you have the power to be prepared anytime, anywhere.

### Product Features:

- ▶ 300 watts of household power
- ▶ 250 psi air compressor
- ▶ 200 amps to jumpstart your vehicle
- ▶ Detachable ultra bright LED flashlight
- ▶ Reverse-polarity detector to safely jump-start your vehicle
- ▶ Jump-start clips designed for easy storage on the unit
- ▶ Overload and over-temperature protection to ensure longer inverter life

### Product Applications:

- ▶ Charges cordless & cellular phones
- ▶ Powers two-way radio sets
- ▶ Jump-starts your car (200 CCA)
- ▶ Inflates vehicle tires
- ▶ Powers camcorders, video games, stereos and digital cameras
- ▶ Runs fans, laptops and clock radios



Vehicle jump-starter



Detachable flashlight

### Retail Package



[www.duracellpower.com](http://www.duracellpower.com)

Product Specifications

AC		DC	
AC output power (max. continuous)	240 W	Internal battery type	Sealed lead-acid, AGM
AC output power (peak)	300 W	Internal battery capacity	14 Ah, 120 CCA
AC output surge capacity (peak)	480 W	Internal battery voltage	12 Vdc
AC output voltage (nominal)	120 V	DC power socket (circuit breaker)	12 A (automatic reset)
AC output frequency	60 Hz		
AC output waveform	Modified sine wave		
Inverter no-load current	< 0.20 amps (battery drain with no load on inverter)		
Inverter low-battery alarm	11.0 V		
Inverter low-battery shutdown	10.5 V		

General Specifications

Part number	852-0307	Jump-start cables	24" (610 mm), 8 AWG
Unit dimensions (L x W x H)	12.5 x 9.25 x 8" (31.8 x 23.5 x 20.3 cm)	Air compressor	250 psi
Unit weight	14.3 lb (6.5 kg)	Flashlight	LED (rechargeable)
Warranty	Six months		
Operating temperature	32°F to 104°F (0°C to 40°C)		
Storage temperature	32°F to 86°F (0°C to 30°C)		

Charging System

AC charger bulk charging current	500 mA (maximum)
Peak charging voltage	14.2 V (nominal)
Charge restart voltage	12.9 V (nominal)
Float charge current	1 mA (nominal)
Charger input socket current	3 A (maximum)

Charging Time

From AC outlet	Max. 24 hours*
From DC outlet	Max. 2.5 hours*


\*Maximum charging time occurs when battery is completely discharged

Packaging Specifications

	Retail Package*	Master Carton	Pallet
Size (L x W x H)	14.6 x 10.4 x 10" (37 x 26.5 x 25.5 cm)	15 x 10.75 x 10.5" (38.1 x 27.3 x 26.7 cm)	40 x 48 x 77.5" (101.6 x 121.9 x 196.8 cm)
Count	1	1	63
Weight	17 lb (7.7 kg)	19 lb (8.6 kg)	N/A
Volume	N/A	1,693 cu.in.	N/A
UPC number	7 15535889001 8		

\* Box

Specifications subject to change without notice



Xantrex Technology Inc.

Headquarters  
8999 Nelson Way  
Burnaby, British Columbia  
Canada V5A 4B5

5916 195th Street NE  
Arlington, Washington  
USA 98223