Changing the printer's name

This procedure lets you change the printer's name. The printer's name has the following characteristics:

- Is printed on the printer's startup and configuration pages.
- Is used by both LocalTalk and EtherTalk to identify the printer.
- Can be up to 31 characters long, and may contain any printable characters except @ (at sign) and : (colon).
- The default printer name is Phaser 480X.
- A name change is persistent across printer power cycles.
- Appears in the Chooser on a Macintosh.
- On a Macintosh, if more than one printer with the same name appears in the same zone, numbers are appended to the names of the printers added later, for example Phaser 480X-1 and Phaser 480X-2.

To change the printer's name, use one of the following files depending on your computer type.

Macintosh file name	PC file name
LaserWriter Utility	PRNTNAME.PS

Directions for Macintosh

Directions for PC/Workstations

Macintosh users

- 1. Select the printer in the **Chooser**.
- 2. Locate the *LaserWriter Utility* in the *Phaser 480X Utilities* folder on the Phaser 480X CD-ROM (*Utilities* folder) or on the Macintosh Printer Utilities diskette.
- 3. Copy the LaserWriter Utility to your hard disk.
- 4. Double-click on the **LaserWriter Utility** icon to start the application.
- 5. Select **Name Printer** from the **Utilities** menu. The currently selected printer is listed in the dialog box.
- 6. Type the new name in the edit box.
- 7. Click the **Rename** button.
- 8. At the confirmation dialog box, click **OK**.
- 9. Open the **Chooser** to reselect the printer with its new name.

PC and workstation users

Note Some text editors add a carriage return or line feed after the last Control-D character in a file you are editing. If your computer is connected to the printer through the parallel port or the serial port, the extra characters will start a new job causing the printer to time out after a few minutes. To avoid this situation, copy the CTRLD.PS file to the printer after you send the PRNTNAME.PS file.

- 1. Locate the *PRNTNAME.PS* file in the *PHSR480X* directory either on the Phaser 480X CD-ROM (*UTILS* directory) or on the Windows 3.1 Driver and Printer Utilities diskette.
- Copy the file to your hard disk for editing.
- 3. View the PRNTNAME.PS file in a text editor.
- 4. Edit the file to substitute a different printer name for (My Printer Name) in the /PrinterName line.
- 5. To send the file to the printer:
 - **PC users**: Use the DOS **COPY** command to send the *PRNTNAME.PS* file to the printer. Or, use the **Copy** command in Windows **File Manager** to send the *PRNTNAME.PS* file to the printer.
 - **Workstation users:** Send the *PRNTNAME.PS* file to the printer as you would any PostScript file.