

# C Printer Specifications

## Physical Specifications

### Printer

- Width: 644 mm (25.4 in.)
- Depth: 715 mm (28.1 in.)
- Height: 493 mm (19.4 in.)
- Weight: 91 kg (200 lb.)

### Optional 1500-Sheet Lower Tray Deck

- Width: 644 mm (25.4 in.)
- Depth: 682 mm (26.9 in.)
- Height: 364 mm (14.3 in.)

### Optional 2500-Sheet High-Capacity Feeder

- Width: 644 mm (25.4 in.)
- Depth: 682 mm (26.9 in.)
- Height: 364 mm (14.3 in.)

## Environmental Specifications

### Temperature

- Storage: -20° to 50° C / -4° to 122° F
- Operating: 10° to 32° C / 50° to 90° F:

### Relative Humidity

- Storage: 30% to 55% (non-condensing)
- Operating: 10% to 85%
- Optimal: 25% to 70%

## Electrical Specifications

Available in four (4) configurations: 7750B, 7750DN, 7750GX, 7750DXF

- 110-127 VAC, 50/60 Hz
- 220-240 VAC, 50/60 Hz
- ENERGY STAR qualified printer

## Performance Specifications

### Resolution

- 600 x 600 dpi
- 1200 x 600 dpi
- 1200 x 1200 dpi

### Print Speed

- Up to 35 pages per minute (ppm)

## Controller Specifications

715 MHz processor

### Memory

- 256 MB PC133 DRAM standard on the Phaser 7750B Color Laser Printer
- 384 MB PC133 DRAM standard on the Phaser 7750DN Color Laser Printer
- 512 MB PC133 DRAM standard on the Phaser 7750GX Color Laser Printer
- 512 MB PC133 DRAM standard on the Phaser 7750DXF Color Laser Printer
- Upgradable to a maximum of 1024 MB

### Page Description Languages (PDL)

- PCL5c
- Adobe PostScript 3
- Adobe PDF-Direct

### Residential Fonts

- 137 PostScript Type 1
- 81 PCL5c

### Interfaces

- Ethernet 10BaseT and 100BaseTx
- USB versions 1.0, 1.1, and 2.0