

C Printerspecificaties (Engelstalig)

Physical Specifications

Width: 422 mm (16.3 in.)

Depth: 514 mm (21 in.)

Height: 368 mm (14.5 in.)

Weight: 28 kg (60 lbs.)

Optional 525-Sheet Feeder

- Width: 422 mm (16.6 in.)

- Depth: 514 mm (20.3 in.)

- Height: 132 mm (5.2 in.)

Environmental Specifications

Temperature

- Storage: -30° to 60° C / -22° to 140° F

- Operating: 10° to 32° C / 50° to 90° F

Relative Humidity

- Storage: 10% to 95%

- Operating: 10% to 80%

Electrical Specifications

Available in four (4) models:

- 110-120 VAC, 60 Hz

- 220 VAC, 50 Hz

ENERGY STAR qualified printer (ES Option)

Performance Specifications

Print Speed

- Up to 24 pages per minute (ppm)

Controller Specifications

500 MHz processor

Memory

- 128 Mbytes PC133 DRAM standard on the Phaser® 8400B Color Printer
- 128 Mbytes PC133 DRAM standard on the Phaser® 8400N Color Printer
- 256 Mbytes PC133 DRAM standard on the Phaser® 8400BD Color Printer
- 256 Mbytes PC133 DRAM standard on the Phaser® 8400DP Color Printer
- 256 Mbytes PC133 DRAM standard on the Phaser® 8400DX Color Printer
- Upgradable to a maximum of 512 Mbytes

Resolution

2400 FinePoint

Page Description Languages (PDL)

- PCL5c
- Adobe PostScript 3

Residential Fonts

- 137 PostScript Type 1
- 81 PCL5c

Interfaces

- IEEE 1284 parallel
- Ethernet 10BaseT and 100BaseTx (only for N, DP, and DX configurations)
- USB