# User's Manual

## **DAQSTATION CX2000**

Please make the following alterations to the User's Manual IM 04L31A01-01E (see underlined text).

### ■ Page i "Electronic Manuals Provided on the Accompanying CD-ROM"

	Manual Title	Manual No.	Description		
DAQSTANDARD IM 04L41B01-61E Describs the functions and operating procedure of the software "DA		Describs the functions and operating procedure of the software "DAQSTANDARD"			
			that comes with the package.		

### ■ Page v "Standard Accessories"

No.	Name	Part Number/Model	Q'ty	Note
3	DAQSTANDARD	DXA120	1	CD-ROM used to install "DAQSTANDARD", a software for
				setting the CX and displaying data.

#### ■ Page vi "Structure of the Manual"

For details on the communications functions and the software "<u>DAQSTANDARD</u>" provided with the package, see the respective manuals (IM 04L31A01-17E and <u>IM 04L41B01-61E</u>).

### ■ Page 14-17 "Safety and EMC Standards"

Safety

CSA Certified by CSA22.2 No. 61010.1, Installation category II<sup>\*1</sup>, Pollution degree 2<sup>\*2</sup>,

Measurement category II\*3

UL Certified by <u>UL61010-1</u> (CSA NRTL/C)

CE Complies with EN61010-1

- \*1 "Installation category (Overvoltage category)" describes a number which defines a transient overvoltage condition. It implies the regulation for impulse withstand voltage. "II" applies to electrical equipment which is supplied from the fixed installation like distribution board.
- \*2 "Pollution degree" describes the degree to which a solid, liquid, or gas which deteriorates dielectric strength or surface resistivity is adhering. "2" applies to normal indoor atmosphere. Normally, only nonconductive pollution occurs.
- \*3 "Measurement category II" applies to measuring circuits connected to low voltage installation, and electrical instruments supplied with power from fixed equipment such as electric switchboards.

#### **EMC Conformity standards**

<u>CE</u> <u>EN61326-1 Class A, Table 2 (For use in industrial locations)</u>

EN61326-2-3

EN55011 Class A, Group1

EN61000-3-2 Class A

EN61000-3-3

C-tick EN55011 Class A, Group1

The instrument continues to operate at a measurement accuracy of within ±10% of the range during testing.

