



# Coliseum CM1260

12-inch Passive Wedge Monitor

## Features:

- ▷ 150 Watt Wedge Monitor
- ▷ 40° x 60° Waveguide Horn
- ▷ 12-inch Woofer with 1-inch Mylar HF Driver
- ▷ Inset input-jack plates
- ▷ Binding post and 1/4" phone connectors
- ▷ 15mm 11-ply Birch Cabinet Construction
- ▷ Two-year Unconditional Warranty\*

\*Warranty valid in Canada and the United States only



## Overview:

The 150-Watt CM1260 contains a single 12" speaker and horn. Each enclosure features a 1" Mylar, high frequency driver firing through a 40° x 60° for unsurpassed sonic clarity. Time-tested passive crossover networks (12 dB per octave) ensure sonic accuracy and CTL™ protection circuitry guards against damage to the high frequency drivers.

In the lower frequency range the rugged custom design woofer combines solid performance with outstanding reliability. The enclosures feature inset input-jack plates, which contain binding post and 1/4" phone connectors. The enclosures are painted with a white two-part epoxy and incorporate curved, anti-resonance speaker grille constructed of perforated 16-gauge steel. Both enclosure and grille can be easily refinished and feature a grille clip attachment system for easy removal and recovering. Painstaking attention to details of design is taken while the enclosures are constructed of highly rigid 15mm (.5906") Baltic birch plywood.

## Coliseum Series Overview:

After years of experience with enclosure design, it was logical for Yorkville to apply its knowledge to the design of a range of speaker cabinets that have been specifically designed for installation purposes. The knowledge that we gained while developing the TX, élite, Pulse and Performance series enclosures was applied to yield a series of practical yet cost effective installation enclosures. The combination of custom designed woofers and compression drivers mounted on Yorkville's exclusive ABS horns, and less complex crossover networks has proven to be an excellent compromise between performance and price.

All wooden Coliseum series enclosures are now constructed of highly rigid 15mm (.59") Baltic Birch plywood. Although the standard, rugged white epoxy finish is clean and attractive, all Coliseum series enclosures are also available by special order in Black Ultrathane or unpainted Birch (significant delivery times may apply). Their trapezoidal shape is conducive to array mounting and minimizes lobing difficulties. Flypoints are steel reinforced and engineered to allow easy, flexible and safe enclosure suspension.

All enclosures and grilles can be easily refinished and feature a grille clip attachment system for easy removal and recovering. Painstaking attention to design details is evident by features such as the safety screw hidden under the embossed Yorkville logo, which ensures that the grille does not inadvertently come loose.

### CM1260 Specifications:

Model	CM1260
SYSTEM TYPE	Passive 2-Way Monitor
PROGRAM POWER (watts)	150
IMPEDANCE (ohms)	8
FREQ. RESPONSE (Hz +/-3dB)	80 - 16k
SENSITIVITY (dB@1W/1m)	100
MAXIMUM SPL (dB)	121
X-OVER FREQUENCY (Hz)	4000
LF DRIVER(S)	12"
HF HORN	Waveguide
HF DRIVER	1" Mylar
HF HORN THROAT DIAMETER	1"
HF DISPERSION (H° x V°)	40 x 60
HF PROTECTION	CTL™
CONSTRUCTION	15mm 11-ply Birch
STOCK FINISH	White Painted
GRILLE	Perforated Metal
INPUTS (1/4" / Binding Post)	2 / 1 pair
FLYWARE TYPE / QUANTITY	-
FLYWARE LOCATIONS	-
OPTIONAL ACCESSORIES	-
DIMENSIONS (DxWxHxBW inches)	15 x 21 x 18
DIMENSIONS (DxWxHxBW cm)	38 x 55 x 46
WEIGHT (lbs / kg)	37 / 17