

<sup>3</sup> McCullough, G. B., "The effect of Reynolds number on the stalling characteristics and pressure distributions of four moderately thin airfoil sections," NACA TN 3524 (1955).

<sup>4</sup> Ewans, W. T. and Mort, K. W., "Analysis of computed flow parameters for a set of sudden stalls in low-speed two-dimensional flow," NASA TND-85 (1959).

<sup>5</sup> Woods, P. and Ericsson, L. E., "Aeroelastic considerations in a slender blunt-nose, multistage rocket," *Aerospace Eng.* **21**, 42-51 (May 1962).

<sup>6</sup> Ericsson, L. E. and Reding, J. P., "Analysis of flow separation effects on the dynamics of a large space booster," *J. Spacecraft Rockets* **2**, 481-490 (1965).

<sup>7</sup> Ericsson, L. E., "Aeroelastic instability caused by slender payloads," *J. Spacecraft Rockets* **4**, 69-73 (1967).

<sup>8</sup> Lambourne, N. C., "Experiment on an airfoil at  $M = 0.75$  reported by W. P. Jones in the 1961 Minta Martin Lecture, research on unsteady flow," *J. Aerospace Sci.* **29**, 249-263 (March 1962).

<sup>9</sup> Ericsson, L. E., "Separated flow effects on the static and dynamic stability of blunt nosed cylinder flare bodies," Lockheed Missiles & Space Co., LMSC/667991 (1965).

## Erratum: "Thrust Performance of Suppressor Nozzles"

JOHN E. POSTLEWAITE\*

*The Boeing Company, Renton, Wash.*

[*J. Aircraft* **3**, 587-588 (1966)]

THE statement between Eqs. (5) and (6) should read: "The peak velocity coefficient of Eq. (2) is represented in terms of the maximum velocity coefficient  $c_{vs}$  of the standard convergent nozzle by replacing  $D$  with  $D_{he} = 1$  and  $4\theta$  with  $1 - c_{vs}/(D_{he})^n$ ."

Received May 22, 1967.

\* Research Engineer, Propulsion Research, Commercial Airplane Division. Member AIAA.

## Announcement: Change in Style for References in AIAA Publications

The Committee of Engineering Society Editors, of the Engineers Joint Council, has recommended a standard style for references in engineering publications. In the interest of reducing the burden on authors and editors and minimizing confusion, the AIAA Publications Department has decided to follow the recommended style. Examples of the new style will be found below and on the inside back cover of all AIAA journals. The changes will be effective with manuscripts scheduled for the January 1968 issues and thereafter.

### Example—Journals

Walker, R. E., Stone, A. R., and Shandor, M., "Secondary Gas Injection in a Conical Rocket Nozzle," *AIAA Journal*, Vol. 1, No. 2, Feb. 1963, pp. 334-338.

### Examples—Books

Turner, M. J., Martin, H. C., and Leible, R. C., "Further Development and Applications of Stiffness Method," *Matrix*

*Methods of Structural Analysis*, 1st ed., Vol. 1, Macmillan, New York, 1964, pp. 203-266.

Segrè, E., ed., *Experimental Nuclear Physics*, 1st ed., Vol. 1, Wiley, New York, 1953, pp. 6-10.

### Example—Reports

Book, E. and Bratman, H., "Using Compilers to Build Compilers," SP-176, Aug. 1960, Systems Development Corp., Santa Monica, Calif.

### Example—Transactions or Proceedings

Soo, S. L., "Boundary Layer Motion of a Gas-Solid Suspension," *Proceedings of the Symposium on Interaction between Fluids and Particles*, Institute of Chemical Engineers, Vol. 1, 1962, pp. 50-63.