

Sensitivity-Based Scaling for Approximating Structural Response

Kwan J. Chang*

Lockheed Engineering and Science Company, Hampton, Virginia 23666

Raphael T. Haftka†

Virginia Polytechnic Institute and State University, Blacksburg, Virginia 24061

Gary L. Giles‡

NASA Langley Research Center, Hampton, Virginia 23681

and

Pi-Jen Kao§

Analytical Services and Materials, Inc., Hampton, Virginia 23666

This article presents a sensitivity-based linearly varying scale factor used to reconcile results from simple and refined models for analysis of the same structure. The improved accuracy of the linear scale factor compared to a constant scale factor, as well as the commonly used tangent approximation, is demonstrated. A wing-box structure is used as an example, with displacements, stresses, and frequencies correlated. The linear scale factor could permit the use of a simplified model in an optimization procedure during preliminary design to approximate the response given by a refined model over a considerable range of design changes.

Introduction

THE design optimization of an engineering system typically requires hundreds of analyses of that system. The use of approximations to the objective function and constraints during portions of the design process is quite common,¹ because of the high computational cost of these detailed analyses. Such design approximations can be divided into two classes. First there are local, derivative-based approximations such as the linear approximation based on a Taylor-series expansion about a design point. These approximations are typically based on an accurate model to obtain the system response and its derivatives. Second, there are global approximations that try to capture the behavior of the objective function or constraints over the entire design domain. Such approximations can be based on a response surface which is constructed on the basis of many analyses.² However, global approximations are often based on a simplified theory, a coarser model, or both.³ Such global approximations are referred to here as simple-model approximations. Local approximations are typically very accurate near the design point where they are generated, but since they are based on an extrapolation procedure their accuracy can deteriorate catastrophically at a distance. Simple-model approximations are intended to capture the physics of the problem at some lower, but acceptable level of accuracy over the entire design domain. Therefore, at a particular design point the simple-model approximations are generally less accurate than local approximations, but on the other hand, they typically do not experience the cata-

strophic deterioration in accuracy if significant design changes are made.

There has been much research into improving local approximations to extend their region of usefulness. In structural optimization the use of intervening variables and intervening response quantities⁴ has been found to be effective. For example, for many structural design problems (such as stress optimization) it was found that the linear approximation in the reciprocal of the design variables is more accurate than the ordinary linear approximation.⁵ Similarly, it was found that forces are approximated better than stresses,⁶ so that a linear approximation of element forces followed by an explicit calculation of stresses is more accurate than a linear approximation of the stresses. Similarly, in aerodynamics there have been efforts (such as coordinate stretching⁷), to improve local approximations for aerodynamic drag. Another approach for extending the range of local approximations is to use information at additional points.⁸

There has also been some research into improving simple-model approximations. One active area is the use of the so-called reduced-basis approximations in structural dynamics. There, the order of the structural model is reduced by retaining only a small number of deformation shapes (e.g., vibration modes) and assuming that the structural response can be approximated as a linear combination of these shapes. Research has focused on the best selection of these shapes⁹ as well as on methods that improve accuracy for a given set of shapes.¹⁰ The most commonly used simple approximations, however, are based on coarser discretizations or less computationally expensive theoretical models for the same problem. For example, in the optimization of wing structures, plate models have been used to replace the more expensive built-up finite-element models.^{11–13}

It may be expected that the advantages of local approximations and simple-model approximations can be combined. In fact, multigrid analysis methods¹⁴ have demonstrated the utility of working simultaneously with coarse and refined approximations. In Ref. 15 a method called the "global-local approximation" was proposed which uses sensitivity information from both a refined and a coarse model of the structure to construct an approximation that combines the advantages of local and global approximations. The method was used with coarse and refined finite-element models of a simple

Presented as Paper 91-0925 at the AIAA/ASME/ASCE/AHS/ASC 32nd Structures, Structural Dynamics, and Materials Conference, Baltimore, MD, April 8–10, 1991; received Aug. 14, 1991; revision received Feb. 17, 1992; accepted for publication March 11, 1992. Copyright © 1991 by the American Institute of Aeronautics and Astronautics, Inc. No copyright is asserted in the United States under Title 17, U.S. Code. The U.S. Government has a royalty-free license to exercise all rights under the copyright claimed herein for Governmental purposes. All other rights are reserved by the copyright owner.

*Staff Engineer.

†Professor. Associate Fellow AIAA.

‡Senior Research Engineer. Associate Fellow AIAA.

§Research Scientist. Member AIAA.

beam structure. The objective of the present article is to show that the method can be used for better correlation of results obtained with models based on different analytical formulations. In particular, the method is applied to equivalent-plate and finite-element models of a candidate wing structure for a supersonic transport.

Sensitivity-Based Scaling Approximation

Scaling factors have been used in the past¹⁶ for the correlation of simplified and refined models. The use of a scale factor involves comparing results from a coarse model or simplified approximation at a given design point, to results from a more refined approximation or to the exact result, if available. The ratio of results from the refined approximation to results from the coarse approximation is a scaling factor that is used to multiply the coarse approximation results at other points in the design domain. Recall that the coarse approximation is viewed as a global approximation. The scaling factor, therefore, introduces some local flavor into the process in that it is most effective near the point in the design domain where the factor is calculated. It is possible, in cases where the value of the scaling factor changes considerably over the design domain, that the local improvement comes at the expense of reduced accuracy of the scaled coarse approximation far from the point where the scale factor is calculated.

The newly developed sensitivity-based correlation approach refines the conventional constant scaling factor by using a linearly varying scaling factor. The method can be viewed as a combination of the local aspect of derivative-based approximations with the global aspect of coarse-model approximations. For simplicity, consider a structural response from a refined analysis that is a function of a single design variable $f_R(x)$, which is approximated by a simplified analysis as $f_S(x)$, and define a scaling factor β calculated at a design point x_0 as

$$\beta(x_0) = f_R(x_0)/f_S(x_0) \quad (1)$$

The scaling factor at any other design point can be approximated as

$$\beta(x) = \beta(x_0) + (x - x_0)\beta'(x_0) \quad (2)$$

where the prime symbol denotes the derivative with respect to x . Taking the derivative of the expression for the scale factor β in Eq. (1) and substituting into Eq. (2) gives a sensitivity based correlation factor as

$$\beta(x) = \beta(x_0)\{1 + (x - x_0)[f'_R(x_0)/f_R(x_0) - f'_S(x_0)/f_S(x_0)]\} \quad (3)$$

and approximations to the global response using constant and linear scaling are given respectively by

$$f_{SRC}(x) = \beta(x_0)f_S(x) \quad \text{and} \quad f_{SRL}(x) = \beta(x)f_S(x) \quad (4)$$

This approach is applicable to a vector of design variables with the approximation to β in Eq. (2) being replaced by the first-order Taylor series expansion of β .

Wing-Box Example

The proposed method is tested on a wing-box model of a high-speed civil transport shown in Fig. 1. The simplified-model of the wing box is analyzed using the equivalent-plate analysis method described in Refs. 12 and 13. The simplified model (Fig. 1a) is composed of 3 equivalent plates, referred to as panels I, II, and III, and 22 spar caps (not shown on figure). The cross-sectional geometry of the equivalent plate is given by the location of the midcamber surface and depth which are both defined as polynomial functions over the plan-form of the wing. The thicknesses of the upper and lower




Fig. 1 Simplified and refined models of wing-box structure.

Table 1 Initial variables of the equivalent plates

Panel no.	Coefficient, ft			
	C_0	C_1	C_2	C_3
I	0.008	-0.001	-0.001	-0.001
II	0.007	-0.001	-0.001	-0.001
III	0.006	-0.001	-0.001	-0.001

Table 2 Comparison of analysis results for simplified and refined models

	Displacement, ft	von Mises stress, $\times 10^6$ psf	First frequency, Hz
Simplified model	13.30	7.48	1.80
Refined model	13.40	8.53	1.74

cover skins in each panel are given in polynomial form as

$$t = C_0 + C_1\xi + C_2\eta + C_3\xi\eta \quad (5)$$

where ξ and η are the fraction of chord and fraction of span of each panel, and C_0 , C_1 , C_2 , and C_3 are thickness coefficients which are used as design variables. The initial design point

Table 3 Derivatives of displacement, stress, and first frequency of the simplified and refined models

Panel no.	D.V.	Simplified model			Refined model		
		Displ. $\times 10^2$	Stress $\times 10^8$	Freq. $\times 10^1$	Displ. $\times 10^2$	Stress $\times 10^8$	Freq. $\times 10^1$
I	C_0	-1.4223	-1.3133	1.680	-1.1872	-0.8295	1.425
	C_1	-1.1413	-1.1691	1.255	-0.9186	-0.7299	1.093
	C_2	-0.7116	-1.1691	0.913	-0.5993	-0.4185	0.718
	C_3	-0.5406	-0.7014	1.079	-0.4591	-0.3648	0.546
II	C_0	-8.5849	-9.2335	7.533	-9.2122	-11.8865	7.931
	C_1	-4.5124	-3.9660	3.619	-4.7968	-10.5304	3.946
	C_2	-4.9821	-3.8871	3.950	-5.2868	-4.8955	4.089
	C_3	-2.4329	-1.2359	2.083	-2.5387	-3.9610	1.808
III	C_0	-8.0685	0.3918	-6.616	-7.8034	-0.0943	-6.997
	C_1	-3.9299	0.1940	-3.633	-3.8369	-0.0492	-4.137
	C_2	-3.0114	-0.0733	-5.843	-2.9355	-0.0116	-5.557
	C_3	-1.4479	-0.0072	-2.981	-1.4237	-0.0063	-3.074

for the equivalent plate model has thickness coefficients for the three panels given in Table 1.



The refined analysis is performed with a finite-element program¹⁷ using a built-up model, shown in Fig. 1b, containing 60 membrane elements, 70 shear webs, and 180 bar elements to represent rib and spar caps and vertical posts between the covers. The thickness coefficients of the simplified model are used to generate the thickness of the membrane elements in the upper and lower skins in the finite-element model by averaging plate thickness values corresponding to the four nodes of each finite element. Both models are loaded by two 25,000-lb loads in the z direction at the two extreme points of the tip of the models (nodes 1 and 7 in Fig. 1). The wing is assumed to be made of silicon carbide fiber in a titanium metal matrix (SCS6/Ti) stacked into a quasi-isotropic laminate. The material properties used here are a Young's modulus of 21.32×10^6 psi, Poisson's ratio of 0.325, shear modulus of 8.0×10^6 psi, and a density of 0.144 lb/in.³

Values for the nominal displacements, stresses, and lowest frequencies of the two models are given in Table 2 with the locations of the displacement and stress values shown in Fig. 1. These results indicate that the agreement between the calculated structural responses from the two models at the initial design point is quite good. The corresponding derivatives of tip displacement, stress value at the specified location, and lowest frequency, with respect to the thickness coefficients in each panel, are given in Table 3 for both models. These derivatives are needed to calculate the linearly varying scale factor, f_{SRL} . The values of the derivatives given by the simplified and refined models have a reasonable level of agreement with the largest differences being in the stress derivatives.

Approximation Results and Discussion

The accuracy of the scaling methods are tested by making changes in the values of thickness coefficients and evaluating the structural responses given by the various approximations. The approximations are evaluated as the ratios of the thickness coefficients are increased up to factors of $C_i/C_0^0 = 5$, where the superscript 0 denotes the original value. Results are presented for a subset of the design variables listed in Table 3. The coefficient C_0 , the constant term in the thickness polynomial of Eq. 5, is selected for many of the results because the derivatives of the structural response quantities with respect to C_0 are large compared to derivatives with respect to other coefficients. The coefficient C_2 is also used for some cases to illustrate the change of a linear term in the thickness polynomial.

A comparison of values of normalized tip displacement (again refer to Fig. 1) are shown in Figs. 2 and 3 for changes in C_0 in panel I and C_2 in panel II. In these figures f_R represents results from the refined (finite-element) analysis, f_S are results from the simplified (equivalent-plate) analysis, and f_{SRC} and

**Fig. 2** Approximations to wing tip displacement.**Fig. 3** Approximations to wing tip displacement.

f_{SRL} are the constant and linearly scaled approximations, respectively. The displacements are normalized by the value of the refined model at the initial design. The two figures show that for this example the error associated with the simple model increases as the design variables move away from the initial design. The factor corresponding to the constant scale approximation f_{SRC} is close to one, since the agreement between the two models is quite good at the initial design and this factor contributes very little to correcting the error at

points away from the initial design. The linear scale factor approximation f_{SRL} on the other hand, almost completely eliminates the error due to change in design. The linear tangent and reciprocal Taylor series approximations commonly used in optimization are also shown in Figs. 2 and 3. It is clear that the tangent approximation is less accurate for the displacement here than either scale factor approximation. To keep an expanded scale on Fig. 2, the tangent approximation is not extended to the point at $C_i/C_i^0 = 5$. The reciprocal approximation is quite accurate in Fig. 2 and quite poor in Fig. 3. The reciprocal approximation is not shown on subsequent figures. However, for problems where the reciprocal approximation is known to be superior to the linear approximation, it is possible to reformulate Eqs. (2-4) in terms of reciprocal variables.

Figures 4 and 5 show the same approximations applied to the stress at the point shown in Fig. 1 for changes in C_0 for panel I as before, and C_0 instead of C_2 for panel II. For changes in C_0 for panel I (Fig. 4), the relative ranking of the approximations remains the same. The errors in f_S are much larger, so that the improvement due to scaling is more evident. This time, however, it appears that although the linearly varying scaling is much better than a tangent approximation, the constant scale factor is about the same. For changes in C_0 for panel II (Fig. 5) the situation is different. In this case, the linearly varying scale factor is the most accurate approximation only near the initial design. This is an example where the local nature introduced by using derivatives asserts itself.

Further away from the initial design the constant scale factor is slightly better. Note, however, that even in this case, both scaling methods are better than the tangent approximation at a distance from the initial design.

Figures 6 and 7 show the approximations applied to the first (lowest) natural frequency of the structure. As with the tip displacement, the frequencies of the refined and simple models are almost the same at the initial design. Therefore, very little improvement in accuracy is provided by the constant scale factor approximation. Again, the linear scale factor approximation is very accurate and much better than the tangent approximation.

The previous figures show the effect of changing only one design variable at a time. These results do not check the effect of design variable interaction on the quality of the approximation. This effect was studied by changing a selected combination of design variables. Four design variables were simultaneously changed as follows:

$$\begin{aligned} C_0 &= C_0^0(1 + \delta) \quad \text{in panel I} \\ C_0 &= C_0^0(1 - \delta) \quad \text{in panel II} \\ C_2 &= C_2^0(1 + \delta) \quad \text{in panel II} \\ C_0 &= C_0^0(1 + \delta) \quad \text{in panel III} \end{aligned} \quad (6)$$

Note that the fractional design variable change δ was applied in the negative direction for C_0 in panel II. Figures 8-




Fig. 4 Approximations to von Mises stress at node 59.




Fig. 5 Approximations to von Mises stress at node 59.




Fig. 6 Approximations to first frequency.




Fig. 7 Approximations to first frequency.

10 show the effect of such a combined design variable change on displacement, stress, and frequency. Again, the same general trend of the linear scale factor giving better correlation than the constant scale factor is observed. However, for large design changes, even the linear scale factor accounts for only

about half the difference between the simplified and refined analysis results. Again, both scaling methods give better correlation than the tangent approximation at a large distance from the initial design.

Implications for Design Optimization

Design optimization of complex structures is currently carried out based on procedures which solve a sequence of approximate optimization problems.¹ The approximate problems typically use derivative-based approximations to what is considered here as the refined model. In the new "local-global" approach presented in Ref. 15 and further studied here, the approximation is based on a simplified analysis which is computationally efficient. However, the approximate results are scaled periodically to reflect the more accurate results from a refined analysis which is computationally expensive.

Either constant or linear scale factors can be used to scale the results. A constant scale factor requires only a single analysis of the refined model, so that the cost of derivatives needed for derivative-based approximations is saved. Constructing a linear scale factor requires an analysis plus derivative calculation of the refined model, so that a linear scale-factor approximation can be slightly more expensive than a derivative-based approximation (such as the reciprocal approximation). For effective structural design, it is desirable to use the new approximations in a way that will lead to the lowest computational cost of the overall optimization process. The actual selection of constant or linear scaling factors and the frequency of scaling (or move limits) are problem dependent. When the scale factor does not vary much over the design space, the constant scale factor will be more effective because it does not require the calculation of expensive derivatives of the refined model. If the scale factor does vary substantially over the design space, then the linear approximation is needed and is a valuable tool to provide the desired level of accuracy over a considerable region of the design domain. Actual experience in applying these scaling methods to a variety of problems is needed to establish guidelines for selecting the most effective approximation for a particular design problem. However, such applications are beyond the scope of this article.

Concluding Remarks

A new sensitivity-based scaling method for correlating structural response from different analytical models is studied. Two different formulations are used to analyze the same structure: 1) a simplified representation using an equivalent-plate analysis method; and 2) a refined representation using a conventional finite-element analysis program. A wing-box structure is used as an example, with displacements, stresses, and frequencies correlated. The accuracy of the approximate responses given by the constant and linear varying scale factors, as well as the commonly used tangent method, are compared. In most cases presented, the linearly varying scale factor gave better correlation than the constant scale factor. Both scaling methods gave results that were superior to the tangent approximation at a distance away from the initial design point. The linear scale factor was demonstrated to give good correlation with the refined analysis results over a considerable range of changes in design variables (up to a factor of 5 change).

Thus, the linear scaling method is expected to be effective when used in overall design optimization procedures. Moreover, the method is not limited to structural applications and can be used by other disciplines to correlate responses from different analytical models.

Acknowledgment

The work of R. T. Haftka was sponsored by NASA Grant NAG-1-224.




Fig. 8 Approximations to wing tip displacement for combined changes of variables [see Eq. (6)].




Fig. 9 Approximations to von Mises stress for combined changes of variables [see Eq. (6)].






Fig. 10 Approximations to the first frequency for combined changes of variables [see Eq. (6)].

References

- ¹Haftka, R. T., Gurdal, Z., and Kamat, M. P., *Elements of Structural Optimization*, 2nd ed., Kluwer Academic Publishers Group, Dordrecht, The Netherlands, 1990.
- ²Brown, R. T., and Nachlas, J. A., "Structural Optimization of Laminated Conical Shells," *AIAA Journal*, Vol. 23, No. 5, 1985, pp. 781-787.
- ³Barthelemy, J.-F., and Haftka, R. T., "Recent Advances in Approximations for Optimum Structural Design," NASA TM-104032, March 1991.
- ⁴Thomas, H. L., Sepulveda, A. E., and Schmit, L. A., Jr., "Improved Approximations for Control Augmented Structural Synthesis," *AIAA Journal*, Vol. 30, No. 1, 1992, pp. 171-179.
- ⁵Storaasli, O. O., and Sobieszcanski, J., "On the Accuracy of the Taylor Approximation for Structure Resizing," *AIAA Journal*, Vol. 12, No. 2, 1974, pp. 231-233.
- ⁶Vanderplaats, G. N., and Salajeghah, E., "A New Approximation Method for Stress Constraints in Structural Synthesis," *AIAA Journal*, Vol. 27, No. 3, 1989, pp. 352-358.
- ⁷Joh, C.-Y., Grossman, B., and Haftka, R. T., "Efficient Optimization Procedures for Transonic Airfoil Design," ASME Winter Annual Meeting, San Francisco, CA, Dec. 1989.
- ⁸Rasmussen, J., "Accumulated Approximations—A New Method for Structural Optimization by Iterative Improvements," *Proceedings of the Third Air Force/NASA Symposium on Recent Advances in Multidisciplinary Analysis and Optimization*, San Francisco, CA, Sept. 24-26, 1990, pp. 253-258.
- ⁹Skelton, R. E., Hughes, P. C., and Hablani, H. B., "Order Reduction for Models of Space Structures with Modal Cost Analysis," *Journal of Guidance, Control, and Dynamics*, Vol. 5, No. 4, 1982, pp. 351-357.
- ¹⁰Camarda, C. J., Haftka, R. T., and Riley, M. F., "An Evaluation of Higher-Order Modal Methods for Calculating Transient Structural Response," *Computers and Structures*, Vol. 27, No. 1, 1987, pp. 89-101.
- ¹¹McCullers, L. A., and Lynch, R. W., "Composite Wing Design for Aeroelastic Requirements," *Proceedings of Symposium on Fibrous Composites in Flight Vehicle Design*, AFFDL-TR-72-130, Dayton, OH, Sept. 1972, pp. 951-972.
- ¹²Giles, G. L., "Equivalent Plate Analysis of Aircraft Wing Box Structures with General Planform Geometry," *Journal of Aircraft*, Vol. 23, No. 11, 1986, pp. 859-864.
- ¹³Giles, G. L., "Further Generalization of an Equivalent Plate Representation for Aircraft Structural Analysis," *Journal of Aircraft*, Vol. 26, No. 1, 1989, pp. 67-74.
- ¹⁴Brandt, A., "Multi-Level Adaptive Solutions to Boundary-Value Problems," *Mathematics of Computation*, Vol. 31, No. 138, 1977, pp. 333-390.
- ¹⁵Haftka, R. T., "Combining Global and Local Approximations," *AIAA Journal*, Vol. 29, No. 9, 1991, pp. 1523-1525.
- ¹⁶Ricketts, R. H., and Sobieszcanski-Sobieski, J., "Simplified and Refined Structural Modeling for Economical Flutter Analysis and Design," AIAA/ASME/SAE 18th Structures, Structural Dynamics, and Materials Conf., AIAA Paper 77-421, San Diego, CA, March 1977.
- ¹⁷Stewart, C. B., "The Computational Structural Mechanics Testbed User's Manual," NASA TM-100644, Oct. 1989.



SAVE TIME — SUBMIT YOUR MANUSCRIPT DISKS



All authors of journal papers prepared with a word-processing program are required to submit a computer disk along with their

final manuscript. AIAA now has equipment that can convert virtually any disk (3½-, 5¼-, or 8-inch) directly to type, thus avoiding rekeyboarding and subsequent introduction of errors.

Please retain the disk until the review process has been completed and final revisions have been incorporated in your paper. Then send the Associate Editor all of the following:

- Your final version of the double-spaced hard copy.
- Original artwork.
- A copy of the revised disk (with software identified).

Retain the original disk.

If your revised paper is accepted for publication, the Associate Editor will send the entire package just described to the AIAA Editorial Department for copy editing and production.

Please note that your paper may be typeset in the traditional manner if problems arise during the conversion. A problem may be caused, for instance, by using a "program within a program" (e.g., special mathematical enhancements to word-processing programs). That potential problem may be avoided if you specifically identify the enhancement and the word-processing program.

The following are examples of easily converted software programs:

- PC or Macintosh T_EX and L^AT_EX
- PC or Macintosh Microsoft Word
- PC WordStar Professional
- PC or Macintosh FrameMaker

If you have any questions or need further information on disk conversion, please telephone:

Richard Gaskin
AIAA R&D Manager
202/646-7496



American Institute of
Aeronautics and Astronautics