

# Technical Comments

## Reply to Robert L. Glick's Comment: Physicality of Core Flow Models in Rocket Motors

Joseph Majdalani\*

Marquette University, Milwaukee, Wisconsin 53233

THE following exposition is intended to clarify the fundamental issues raised in Glick's commentary.<sup>1</sup> Despite the commentary's focus on one individual study,<sup>2</sup> the multiple questions that were raised apply just as easily to most theoretical, numerical, and experimental simulations of idealized motors based on simplified geometric configurations and smooth porous walls. In fact, all reported core flow studies have so far relied, to some extent, on idealistic conditions.

The main concern by Glick<sup>1</sup> is that mathematical models may be inadequate as vehicles for physical understanding, especially that burning surfaces in production rocket motors are rough, heterogeneous, and pliable. From this perspective, a core flow that does not account for all conceivable features, including surface vibrations and complex boundary conditions, may be deemed impractical or uncertain. Unfortunately, Glick's commentary does not explore the physical benefits of mathematical models nor does it recognize the role, scope, objectives, and recent successes of core flow idealizations. These have been motivated by important technological applications that will now be overviewed.

As a problem of real concern in rocket motors and large gas turbines, aeroacoustic instabilities have received much scrutiny in the propulsion community. Models of these instabilities have invariably pointed to the importance of providing judicious assessments of corresponding core flow details.<sup>3–8</sup> The desire for explicit flow models has also been motivated by the need to understand physically the intricate coupling between unsteady pressure waves and gas motions.<sup>9–12</sup> As ultimately suggested by repeated tests, not only does this inevitable pairing provoke unsteady burning, but it also generates intense sound-pressure levels and boundary-driven vortices.

This delicate interplay of underpinning core flow mechanisms has inspired over the years several capable theoreticians to seek physical idealizations. The goal has been generally set to isolate carefully the intricate mechanisms by parametric linearization or vector decomposition. In the midst of this unusually complex problem, the quest for basic answers has often become a central focus.

Pioneered by Culick<sup>13–19</sup> and Flandro,<sup>3–8</sup> theoretical studies similar to the one under consideration<sup>2</sup> have elucidated a number of physical features in rocket motors. Among them were the multidimensional spatial and temporal velocity, vorticity, and stress distributions along the length of simulated motors.<sup>20</sup> Points exhibiting maximum and minimum stress disturbances were identified, and the acoustic character in the chamber was being disclosed.<sup>21–27</sup> These analyses have been accomplished by first unraveling the problem's principal convection-diffusion equations and their un-

derlying multiscale structure. The latter exhibited nonlinear characteristic lengths, whose resolution required a separate mathematical treatment.

The presence of dissimilar scales in the resulting Navier-Stokes equations (see Ref. 28) has spurred on the development of two mathematical procedures appropriate of a class of boundary-value problems with nonlinear scales. The first was a variant of the derivative-expansion method and was dubbed, for want of a better name, the composite-scaling technique (CST).<sup>29,30</sup> The second was a more general, space-reductive approach based on Prandtl's principle of least singular behavior. The second was coined the generalized-scaling technique (GST) because of its ability to preclude guesswork in the identification of inner coordinate transformations.<sup>21–24</sup> Its outcome coincided with the traditional Wentzel, Kramers, Brillouin and Jeffreys solution for problems in which both methods were suitable. In view of the wide applicability of the convection-diffusion equations precipitated by core flow models, the presentation of CST and GST space-reductive techniques became an important result in its own right.

As suitably put by von Kármán (as quoted by Sears<sup>31</sup>) "it was the simple but powerful mathematical statement, preferably a differential one, that held the key to the whole complicated affair." In this spirit, with the realization of differentially accurate approximations, implications on core acoustics could be diligently pursued.<sup>6,7</sup> In the process, new destabilizing sources of energy could be uncovered mainly due to interactions with the transpiring surfaces.<sup>12</sup> In actuality, incorporation of these additional sources by Flandro have markedly improved our predictive capability before motor development.<sup>6,7</sup> As shown in his 1995 paper,<sup>7</sup> a favorable agreement with laboratory measurements could be obtained when vortical corrections were included. In the same context, the embodiment of unsteady rotational effects at the forefront of the energy balance equations could actually give rise to several new energy-related terms that were discounted previously.<sup>32</sup> These corrective terms could explain, in part, the presence of parietal vortex coupling<sup>33,34</sup> and turbulent interactions with the mean and unsteady flow components. While analytical solutions were sought for simple geometric shapes, a complete integral formulation of the stability integrals was provided by Chibli et al.<sup>35</sup> to analyze realistic solid rocket motors with arbitrary grain configurations.

While the roadmap for flame zone analysis was being sketched by Flandro,<sup>8</sup> approximate asymptotic solutions for the temperature contours within the motor were under development (see Ref. 36). Despite their intrinsic simplicity (reflected in the use of a "super-heat source"), the asymptotically derived analytical solutions could be calibrated to emulate isotherms acquired from detailed numerical simulations.<sup>36</sup> The key resided in the heat source attributes that could mimic the heat of reaction above the burning surface. The reader may find particularly interesting the recent numerical simulations of the burning zone by Chu et al.<sup>37</sup> These simulations have confirmed the presence of a virtually nonreactive, isothermal region above the flame where analytical approximations, such as the ones under scrutiny, become very effective in describing the gas dynamics. Because the outer region constitutes 98% of the chamber volume, the practicality of analytical solutions is evident.

A departure from the ideal model can, of course, be expected due to external vibration, flight acceleration, particle debouching, and nonuniform injection velocity at the chamber walls. However, because these mechanisms occur at random frequencies, the acoustic disturbances that they produce only help to excite the natural frequencies of the chamber; by so doing, they serve to sustain the source of acoustic waves that is already assumed to exist in theoretical models. Also note that these studies are based on velocity boundary conditions at the porous walls. They are not concerned

Received 1 April 2002; revision received 16 September 2002; accepted for publication 16 September 2002. Copyright © 2002 by Joseph Majdalani. Published by the American Institute of Aeronautics and Astronautics, Inc., with permission. Copies of this paper may be made for personal or internal use, on condition that the copier pay the \$10.00 per-copy fee to the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923; include the code 0748-4658/03 \$10.00 in correspondence with the CCC.

\*Assistant Professor, Department of Mechanical and Industrial Engineering. Member AIAA.

with the level of external pressure that is required to impart a given injection velocity. The porosity of the walls becomes immaterial so long as the incoming flow is sufficiently uniform. Nevertheless, porosity does not elude theoretical idealizations. It is recognized and described by Zhou and Majdalani<sup>38</sup> as the agent in control of the wall injection coefficient. For the oscillating pressure forces, only in the case of resonant burning does the fluid–structure interaction become a concern. In other instances, this coupling may be safely ignored. Furthermore, insofar as rockets operate under choked nozzle conditions, the influence of external noise propagating back into the chamber is insignificant. The isobaric outlet conditions selected in some theoretical models are used to mimic nozzleless motor simulations conducted in controlled laboratory environments.

In support of theoretical approximations, equally appreciable laminar and turbulent segments have been identified in a series of studies conducted by Apte and Yang,<sup>39,40</sup> Liou and Lien,<sup>41</sup> and Beddini and Roberts.<sup>42,43</sup> These teams have simultaneously concurred that turbulent simulations in the downstream sections of long motors tended to exhibit convincing similarities with corresponding basic laminar flow results. In view of this important realization, the unsteady flow solutions derived by Flandro<sup>7</sup> or Majdalani and Van Moorhem<sup>10</sup> have been used to approximate the basic deterministic features observed in turbulent flow results (see Refs. 44 and 45). Additionally, they have been used to provide accurate predictions along the forward half of the motor where laminar conditions are known to prevail.

Aside from these sequential contributions, note that recent efforts have been successful in producing analytical core flow solutions that are sensitive to the movement of transpiring boundaries. The reader is referred, in that regard, to the planar and axisymmetric solutions presented by Zhou and Majdalani<sup>38,46</sup> or Majdalani et al.<sup>47,48</sup> Therein, wall regression is accounted for alongside viscous and rotational features. When a mass balance is applied across the receding interface, the dependence of thrust on propellant morphology and density variation is unraveled. Work is currently underway to simulate motor chambers with arbitrary taper.<sup>49</sup> It is hoped that these incremental advancements in theoretical models will bring us closer to an idealized motor with varying cross section and grain shape. Incorporation of swirling effects has also been accomplished in a forthcoming report by Vyas and Majdalani. Analytical solutions have been useful in providing limiting-process case studies against which detailed numerical simulations could be immediately compared (R. A. Fiedler, private communication, Center for Simulation of Advanced Rockets, University of Illinois at Urbana–Champaign, 2001).

With regard to the role of mathematical solutions in gaining deeper physical insight, the technical examples already recounted may perhaps suffice. According to Sears,<sup>31</sup> it was always “the fundamental differential relationship, when it succinctly described the important phenomenon, that von Kármán always sought.” For what could outperform analytical tools in exposing the basic interdependencies in a problem? Consider the Shvab–Zeldovich equations, for example. Despite their unrealistically simple sets of assumptions, they remain perhaps the most pivotal in elucidating the physics of combustion in standard surveys (see Ref. 50). According to von Kármán, as quoted by Sears,<sup>31</sup> that was “the best of applied mathematics.”

The mathematical models described earlier can never be substituted for multistage, multimodule, fully coupled numerical simulations that could be supported by extensive experimentation. Such computational capabilities are currently under development by a number of dedicated scientists, including Dick, Heath, Balachandar, Moser, Fiedler, Najjar and others at the Center for Simulation of Advanced Rockets [(CSAR) see Refs. 51–54]. There is no doubt that the efforts expended by this body of scientists stand to provide the best diagnostic and predictive tools in the history of rocket development. However, their efforts are not without challenges either.

According to Dick et al.,<sup>51</sup> their efforts require the integration of “approximately thirty-five faculty members, thirty research scientists and programmers, and forty graduate students from a dozen

academic departments.” To provide meaningful data, the integrated modules have to be executed in parallel on 512 processors on a CrayT3E. Discretization requirements are obviously enormous, encompassing millions of fluid cells and several hundred thousand structural elements. Therein, the propellant surface is assumed to ignite everywhere at the beginning of the simulation. However, “regression of the propellant due to burning [is] neglected because of the short physical time reached in the simulation, 0.1 sec after 10 days of wall clock time.” Based on their experience with the integrated code, Dick et al.<sup>51</sup> remark that “a high fidelity simulation of the RSRM [Reusable Solid Rocket Motor] over the entire two minute burn time would require a prohibitive amount of execution time, even on the largest and fastest platforms available now or in the near future.” Rather than allow these challenges to deter their activities, one must acknowledge that the CSAR scientists have chosen the course of continual improvement in their quest for a systemic code. In the absence of suitable experimental data for validation purposes, these investigators<sup>55</sup> have resorted to expeditious, limiting-process verifications based on the approximate solution obtained by Majdalani and Van Moorhem.<sup>10</sup> This solution is identical in scope to the one under scrutiny. For the fundamental and first harmonic oscillations modes that dominate in acoustic instability assessment, analytical solutions and computational results obtained at CSAR were virtually indistinguishable.

To justify the modern need to pursue an analytical side to a full-scale investigation, a plethora of convincing arguments may be offered. One example can be derived from a propulsion related-study of international repute. In investigating aeroacoustic technologies to reduce the excess noise of Concorde jet engines during takeoff and landing, the use of applied mathematics by Williams<sup>56,57</sup> has proven invaluable to the comprehensive Anglo–French research endeavor. Despite the obvious dissimilarities between turbulent shear layers surrounding the propulsive Rolls–Royce jets and the simplistic laminar models based on acoustic analogies, the use of powerful mathematical techniques has unraveled the means to suppress the ensuing sound and vibration. When the jet was seeded with sound upstream of the nozzle, a coherent turbulent structure could be promoted in a manner to reduce the jet noise without impairing thrust and the aircraft’s ability to climb. Thus, by deliberately superimposing an aeroacoustic source whose troughs coincided with the pressure peaks of an existing acoustic environment, a quieter combination could be precipitated. The degree of suppression obtained in this way depended, of course, on the accuracy of the active cancellation models that were suggested analytically and then refined via numerical and experimental simulations. Similar analyses have recently provided multiple-scale solutions for modal sound transmission through turbofan aircraft engines with both hard and acoustically treated inlet walls.<sup>58,59</sup> These solutions by Rienstra<sup>58</sup> and Rienstra and Eversman<sup>59</sup> have closely agreed with output data gathered from finite element codes.

In regard to the ability to provide more realistic models, note that efforts in this direction are constantly underway. Examples include current analytical abilities to account for wall regression, unsteady vorticity, viscous diffusion, bore taper, varying cross sections, and nonuniform injection. In the past, propellant morphology and heterogeneity, however, were shown to be more relevant to the physico-chemistry of combustion than to the acoustic environment within the chamber. As a matter of record, these aspects are treated separately outside the core flow module in the detailed simulations by CSAR. In fact, despite our earnest desire to account for surface vibrations and motor irregularities (due to inhibitors, igniters, submerged nozzles, interface gaps, O-rings, conocyls and slots<sup>60</sup>) the added complexities that accompany these geometric disparities need to be handled one piece at a time. Nonetheless, approximate solutions of the type we have described remain fairly useful in relaying the basic physical aspects of the problem while helping to validate more elaborate numerical simulations. In the case of wall regression that was particularly pointed out, recent findings have indicated its small influence on the overall acoustic field.<sup>38,46,47</sup> This could perhaps justify its dismissal in many laboratory, computational, and theoretical investigations.

In the recent CSAR simulations by Venugopal et al.,<sup>53</sup> the rocket motor is idealized as a plane channel with wall injection across two smooth porous walls separated by a distance of  $2\delta$ . This configuration resembles the one adopted by the French scientists in their *Veine d'Études de la Couche Limite Acoustique* apparatus and the geometry used in the paper under consideration.<sup>2</sup> Nonetheless, to homogenize the Navier–Stokes equations in the streamwise direction, these researchers have assumed that turbulent fluctuations vary over a length scale of  $\mathcal{O}(1)$  and that turbulent amplitudes grow over a larger length scale of  $\mathcal{O}(1/\varepsilon)$ . To take into account the nonuniform variations over these two rational length scales, slow and fast variables are introduced via  $x_s = \varepsilon x$  and  $x_f = x$ . A two-variable multiple-scale expansion is then carried out before numerical simulations could be broken into a number of discrete solutions at user-prescribed stations, namely, one for each value of  $\varepsilon$ .

Note that, throughout this two-scale analysis, the perturbation parameter is taken to be  $\varepsilon = \delta/x$ , where  $x$  is measured from the head end of the simulated rocket. Because  $\delta$  represents the half-height of the porous channel, each streamwise location in the rocket motor could be identified with a particular value of  $\varepsilon$ . Specifically, the primary perturbation parameter  $\varepsilon$  appears as a variable, whereas the slow scale  $x_s = \varepsilon x$  ( $= \delta = \text{const}$ ) is used to represent an artificial coordinate. Venugopal et al.<sup>53</sup> later indicate that, because their analysis assumes  $\varepsilon$  to be small, their model will “be strictly valid only at streamwise locations close to the nozzle of the rocket motor.” Because it is applicable to downstream motor sections, their work complements the basic relations derived by Flandro<sup>7</sup> and Majdalani and Van Moorhem.<sup>20</sup> The latter provide closed-form solutions that are valid everywhere except near the nozzle, where turbulence and compressibility effects become eminent. Also note that, based on the CSAR simulations,<sup>53</sup> the mean flow is found to be approximately isobaric, a feature that has been exploited to linearize the pressure response as part of the analytical framework.<sup>20</sup>

With regard to the elements of uncertainty and practicality in mathematical models, these ailments are also of much concern in both computational and experimental procedures. The test of validity is always whether or not predictions represent adequate approximations to the problem under consideration. The reader is invited to consult with Ref. 23, wherein theoretical solutions are shown to agree very closely with computational data acquired totally independently by Roh and Culick.<sup>61</sup> In the same study, asymptotics are shown to provide fair predictions of experimental measurements.

With regard to element of uncertainty in propellant composition, the most illuminating discussion could perhaps be borrowed from Buckmaster et al.<sup>62</sup> After a terrific simulation of time-accurate propellant burning, these researchers quite elegantly state the following in their 2001 conclusions:

The specific model that we have used here is a simple one, indeed over-simple, and one that omits much physics. In a word, it is false. But unless we have made numerical errors, our results are not wrong. Indeed, “right” and “wrong” is not the correct dichotomy within which to evaluate the results. What is important is the extent to which they imitate the burning of real propellants, and there are things to be learnt from both its failures and its successes in this respect. We anticipate an evolutionary process in which new ingredients will be added, and existing ingredients modified, and we are confident that there will be useful successes despite the fact that for such a complex problem the model will be *eternally false*.

These realistic statements seem to apply equally well to mathematical models under development. As alluded to by Buckmaster et al.,<sup>62</sup> current pursuits may be likened to the efforts of alchemists in 18th century Europe. Despite their confrontation with numerous challenges and hopelessly complicated successions of obscure trials, alchemists never doubted that a relative simplicity lurked behind the apparent complexities, for example, Culick’s mean flow profile.<sup>14</sup> Thus, in their efforts to transmute copper into gold, they discovered a large number of useful substances including ammoniac, alcohol, and mineral acids on the basis of which modern chemistry and rocketry would later be founded. As for the crisp analytical formulations de-

bated earlier, the main point in obtaining them is, perhaps, to thwart the claim by alchemists that all true knowledge is to be repeatedly found and lost.

## Acknowledgment

The author wishes to thank the editor, Daniel J. Dorney for his helpful suggestions, unending patience, and genuine care while overseeing this technical debate.

## References

- <sup>1</sup>Glick, R. L., “Technical Comment on ‘Vorticity Dynamics in Isobarically Closed Porous Channels, Part 1: Standard Perturbations,’” *Journal of Propulsion and Power*, Vol. 19, No. 1, 2003, p. 155.
- <sup>2</sup>Majdalani, J., “Vorticity Dynamics in Isobarically Closed Porous Channels, Part 1: Standard Perturbations,” *Journal of Propulsion and Power*, Vol. 17, No. 2, 2001, pp. 355–362.
- <sup>3</sup>Flandro, G. A., “Solid Propellant Acoustic Admittance Corrections,” *Journal of Sound and Vibration*, Vol. 36, No. 3, 1974, pp. 297–312.
- <sup>4</sup>Flandro, G. A., “Nonlinear Combustion of a Solid Propellant with Velocity Coupling,” AIAA Paper 83-1269, June 1983.
- <sup>5</sup>Flandro, G. A., “Effects of Vorticity Transport on Axial Acoustic Waves in a Solid Propellant Rocket Chamber,” *Combustion Instabilities Driven by Thermo-Chemical Acoustic Sources*, Vol. NCA 4, HTD 128, American Society of Mechanical Engineers, New York, 1989, pp. 53–61.
- <sup>6</sup>Flandro, G. A., “Effects of Vorticity on Rocket Combustion Stability,” *Journal of Propulsion and Power*, Vol. 11, No. 4, 1995, pp. 607–625.
- <sup>7</sup>Flandro, G. A., “On Flow Turning,” AIAA Paper 95-2530, July 1995.
- <sup>8</sup>Flandro, G. A., “Nonlinear Unsteady Solid Propellant Flame Zone Analysis,” AIAA Paper 98-3700, July 1998.
- <sup>9</sup>Majdalani, J., Flandro, G. A., and Roh, T. S., “Implications of Unsteady Analytical Flowfields on Rocket Combustion Instability,” AIAA Paper 98-3698, July 1998.
- <sup>10</sup>Majdalani, J., and Van Moorhem, W. K., “Improved Time-Dependent Flowfield Solution for Solid Rocket Motors,” *AIAA Journal*, Vol. 36, No. 2, 1998, pp. 241–248.
- <sup>11</sup>Majdalani, J., “Boundary-Layer Structure in Cylindrical Rocket Motors,” *AIAA Journal*, Vol. 37, No. 4, 1999, pp. 505–508.
- <sup>12</sup>Majdalani, J., Flandro, G. A., and Roh, T. S., “Convergence of Two Flowfield Models Predicting a Destabilizing Agent in Rocket Combustion,” *Journal of Propulsion and Power*, Vol. 16, No. 3, 2000, pp. 492–497.
- <sup>13</sup>Culick, F. E. C., “Rotational Axisymmetric Mean Flow and Damping of Acoustic Waves in a Solid Propellant Rocket,” *AIAA Journal*, Vol. 4, No. 8, 1966, pp. 1462–1464.
- <sup>14</sup>Culick, F. E. C., “Acoustic Oscillations in Solid Propellant Rocket Chambers,” *Astronautica Acta*, Vol. 12, No. 2, 1966, pp. 113–126.
- <sup>15</sup>Culick, F. E. C., “Stability of Longitudinal Oscillations with Pressure and Velocity Coupling in a Solid Propellant Rocket,” *Combustion Science and Technology*, Vol. 2, No. 4, 1970, pp. 179–201.
- <sup>16</sup>Culick, F. E. C., “Non-Linear Growth and Limiting Amplitude of Acoustic Oscillations in Combustion Chambers,” *Combustion Science and Technology*, Vol. 3, No. 1, 1971, pp. 1–16.
- <sup>17</sup>Culick, F. E. C., “The Stability of One-Dimensional Motions in a Rocket Motor,” *Combustion Science and Technology*, Vol. 7, No. 4, 1973, pp. 165–175.
- <sup>18</sup>Culick, F. E. C., “Rotational Axisymmetric Mean Flow and Damping of Acoustic Waves in a Solid Propellant Rocket,” *Journal of Propulsion and Power*, Vol. 5, No. 6, 1989, pp. 657–664.
- <sup>19</sup>Culick, F. E. C., “Some Recent Results for Nonlinear Acoustics in Combustion Chambers,” *AIAA Journal*, Vol. 32, No. 1, 1994, pp. 146–168.
- <sup>20</sup>Majdalani, J., and Van Moorhem, W. K., “Laminar Cold-Flow Model for the Internal Gas Dynamics of a Slab Rocket Motor,” *Journal of Aerospace Science and Technology*, Vol. 5, No. 3, 2001, pp. 193–207.
- <sup>21</sup>Majdalani, J., and Roh, T. S., “The Oscillatory Channel Flow with Large Wall Injection,” *Proceedings of the Royal Society, Series A: Mathematical and Physical Sciences*, Vol. 456, No. 1999, 2000, pp. 1625–1657.
- <sup>22</sup>Majdalani, J., “The Oscillatory Channel Flow with Arbitrary Wall Injection,” *Journal of Applied Mathematics and Physics*, Vol. 52, No. 1, 2001, pp. 33–61.
- <sup>23</sup>Majdalani, J., and Flandro, G. A., “The Oscillatory Pipe Flow with Arbitrary Wall Injection,” *Proceedings of the Royal Society, Series A: Mathematical and Physical Sciences*, Vol. 458, No. 2022, 2002, pp. 1621–1651.
- <sup>24</sup>Majdalani, J., and Rienstra, S. W., “Two Asymptotic Forms of the Rotational Solution for Wave Propagation inside Viscous Channels with Transpiring Walls,” *Quarterly Journal of Mechanics and Applied Mathematics*, Vol. 55, No. 1, 2002, pp. 141–162.
- <sup>25</sup>Majdalani, J., “Vortical and Acoustical Mode Coupling inside a Two-Dimensional Cavity with Transpiring Walls,” *Journal of the Acoustical Society of America*, Vol. 106, No. 1, 1999, pp. 46–56.

- <sup>26</sup>Majdalani, J., "Asymptotic Formulation for an Acoustically Driven Field inside a Rectangular Cavity with a Well-Defined Convective Mean Flow Motion," *Journal of Sound and Vibration*, Vol. 223, No. 1, 1999, pp. 73–95.
- <sup>27</sup>Majdalani, J., "Improved Solution for the Vortical and Acoustical Mode Coupling inside a Two-Dimensional Cavity with Porous Walls," *Journal of the Acoustical Society of America*, Vol. 109, No. 2, 2001, pp. 475–479.
- <sup>28</sup>Culick, F. E. C., "Combustion Instabilities: Mating Dance of Chemical, Combustion, and Combustor Dynamics," AIAA Paper 2000-3178, July 2000.
- <sup>29</sup>Majdalani, J., "A Hybrid Multiple Scale Procedure for Boundary Layers Involving Several Dissimilar Scales," *Journal of Applied Mathematics and Physics*, Vol. 49, No. 6, 1998, pp. 849–868.
- <sup>30</sup>Majdalani, J., and Van Moorhem, W. K., "A Multiple-Scales Solution to the Acoustic Boundary Layer in Solid Rocket Motors," *Journal of Propulsion and Power*, Vol. 13, No. 2, 1997, pp. 186–193.
- <sup>31</sup>Sears, W. R., "Some Recollections of Theodore Von Kármán," *SIAM Journal on Applied Mathematics*, Vol. 13, No. 1, 1965, pp. 175–182.
- <sup>32</sup>Flandro, G. A., and Majdalani, J., "Aeroacoustic Instability in Rockets," AIAA Paper 2001-3868, July 2001.
- <sup>33</sup>Lupoglazoff, N., and Vuillot, F., "Numerical Simulations of Parietal Vortex-Shedding Phenomenon in a Cold-Flow Set-Up," AIAA Paper 98-3220, July 1998.
- <sup>34</sup>Lupoglazoff, N., and Vuillot, F., "Parietal Vortex Shedding as a Cause of Instability for Long Solid Propellant Motors. Numerical Simulations and Comparisons with Firing Tests," AIAA Paper 96-0761, Jan. 1996.
- <sup>35</sup>Chibli, H. A., Majdalani, J., and Flandro, G. A., "Fundamental Growth Rate Corrections in Rocket Motor Stability Calculations," AIAA Paper 2002-3610, July 2002.
- <sup>36</sup>Vyas, A. B., Majdalani, J., and Flandro, G. A., "Asymptotic Formulation of the Mean Temperature in a Solid Rocket Motor," AIAA Paper 2001-3872, July 2001.
- <sup>37</sup>Chu, W.-W., Yang, V., Vyas, A. B., and Majdalani, J., "Premixed Flame Response to Acoustic Waves in a Porous-Walled Chamber with Surface Mass Injection," AIAA Paper 2002-3609, July 2002.
- <sup>38</sup>Zhou, C., and Majdalani, J., "Improved Mean Flow Solution for Slab Rocket Motors with Regressing Walls," *Journal of Propulsion and Power*, Vol. 18, No. 3, 2002, pp. 703–711.
- <sup>39</sup>Apte, S., and Yang, V., "Unsteady Flow Evolution in a Porous Chamber with Surface Mass Injection, Part 1: Free Oscillation," *AIAA Journal*, Vol. 39, No. 8, 2001, pp. 1577–1586.
- <sup>40</sup>Apte, S., and Yang, V., "Effect of Acoustic Oscillation on Flow Development in a Simulated Nozzleless Rocket Motor," *Solid Propellant Chemistry, Combustion, and Motor Interior Ballistics*, edited by V. Yang, T. B. Brill, and W.-Z. Ren, Progress in Astronautics and Aeronautics, Vol. 185, AIAA, Reston, VA, 2000, pp. 791–822.
- <sup>41</sup>Liou, T.-M., and Lien, W.-Y., "Numerical Simulations of Injection-Driven Flows in a Two-Dimensional Nozzleless Solid-Rocket Motor," *Journal of Propulsion and Power*, Vol. 11, No. 4, 1995, pp. 600–606.
- <sup>42</sup>Beddini, R. A., and Roberts, T. A., "Turbularization of an Acoustic Boundary Layer on a Transpiring Surface," *AIAA Journal*, Vol. 26, No. 8, 1988, pp. 917–923.
- <sup>43</sup>Beddini, R. A., and Roberts, T. A., "Response of Propellant Combustion to a Turbulent Acoustic Boundary Layer," *Journal of Propulsion and Power*, Vol. 8, No. 2, 1992, pp. 290–296.
- <sup>44</sup>Lee, Y., and Beddini, R. A., "Acoustically Induced Turbulent Transition in Solid Propellant Rocket Chamber Flowfields," AIAA Paper 99-2508, June 1999.
- <sup>45</sup>Lee, Y., and Beddini, R. A., "Effect of Solid Rocket Chamber Pressure on Acoustically Induced Turbulent Transition," AIAA Paper 2000-3802, July 2000.
- <sup>46</sup>Zhou, C., and Majdalani, J., "Improved Mean Flow Solution for Slab Rocket Motors with Regressing Walls," AIAA Paper 2000-3191, July 2000.
- <sup>47</sup>Majdalani, J., Vyas, A. B., and Flandro, G. A., "Higher Mean-Flow Approximation for a Solid Rocket Motor with Radially Regressing Walls," AIAA Paper 2001-3870, July 2001.
- <sup>48</sup>Majdalani, J., Vyas, A. B., and Flandro, G. A., "Higher Mean-Flow Approximation for a Solid Rocket Motor with Radially Regressing Walls," *AIAA Journal*, Vol. 40, No. 9, 2002, pp. 1780–1788.
- <sup>49</sup>Clayton, C. D., "Flowfields in Solid Rocket Motors with Tapered Bores," AIAA Paper 96-2643, July 1996.
- <sup>50</sup>Turns, S. R., *An Introduction to Combustion: Concepts and Applications*, 2nd ed., McGraw-Hill, New York, 1996.
- <sup>51</sup>Dick, W. A., Heath, M. T., and Fiedler, R. A., "Integrated 3-D Simulation of Solid Propellant Rockets," AIAA Paper 2001-3949, 2001.
- <sup>52</sup>Fiedler, R. A., Jiao, X., Namazifard, A., Haselbacher, A., Najjar, F. M., and Parsons, I. D., "Coupled Fluid-Structure 3-D Solid Rocket Motor Simulations," AIAA Paper 2001-3954, July 2001.
- <sup>53</sup>Venugopal, P., Najjar, F. M., and Moser, R. D., "Numerical Simulations of Model Solid Rocket Motor Flows," AIAA Paper 2001-3950, July 2001.
- <sup>54</sup>Ferry, J., and Balachandar, S., "Multiphase Flow Research and Implementation at CSAR," AIAA Paper 2001-3951, July 2001.
- <sup>55</sup>Wasistho, B., Haselbacher, A., Najjar, F. M., Tafti, D., Balachandar, S., and Moser, R. D., "Direct and Large Eddy Simulations of Compressible Wall-Injection Flows in Laminar, Transitional, and Turbulent Regimes," AIAA Paper 2002-4344, July 2002.
- <sup>56</sup>Williams, J. E. F., "Aeroacoustics," *Aeronautical Journal*, Vol. 100, No. 1000, 1996, pp. 531–537.
- <sup>57</sup>Williams, J. E. F., "David Crighton 1942–2000: A Commentary on His Career and His Influence on Aeroacoustic Theory," *Journal of Fluid Mechanics*, Vol. 437, 2001, pp. 1–11.
- <sup>58</sup>Rienstra, S. W., "Sound Transmission in Slowly Varying Circular and Annular Lined Ducts with Flow," *Journal of Fluid Mechanics*, Vol. 380, 1999, pp. 279–296.
- <sup>59</sup>Rienstra, S. W., and Eversman, W., "A Numerical Comparison between the Multiple-Scales and Finite-Element Solution for Sound Propagation in Lined Flow Ducts," *Journal of Fluid Mechanics*, Vol. 2001, No. 437, 2001, pp. 367–384.
- <sup>60</sup>Sabnis, J. S., and Eagar, M. A., "Evolution of Internal Flow in a Solid Rocket Motor with Radial Slots," *Journal of Propulsion and Power*, Vol. 12, No. 4, 1996, pp. 632–637.
- <sup>61</sup>Roh, T. S., and Culick, F. E. C., "Transient Combustion Response of Homogeneous Propellants to Acoustic Oscillations in Axisymmetric Rocket Motors," AIAA Paper 97-3325, July 1995.
- <sup>62</sup>Buckmaster, J., Jackson, T. L., and Ulrich, M., "Numerical Modeling of Heterogeneous Propellant Combustion," AIAA Paper 2001-3579, July 2001.