

Technical Comments

Comment on "Experimental Investigation of a Cylindrical Resonator"

Eric Brocher* and Christian Maresca†

Institut de Mecanique des Fluides, ‡ Marseille, France

IN a recent and interesting paper, Wu et al.¹ have described experiments on what may be termed as an axisymmetrical configuration of a Hartmann-Sprenger tube. The purpose of this Note is to comment on the theoretical and experimental values of the frequency reported by these authors.

First of all, it can be noted that, neglecting boundary effects, the flow in a segment of the axisymmetrical configuration is equivalent to the flow in a tapered Hartmann-Sprenger tube. This latter configuration has been investigated by several authors^{2,3} and it has been found that the oscillation frequency of a tube with infinite tapering ratio is roughly 50% higher than that of an untapered tube. The ratio of the acoustical frequency given by the authors for their configuration ($f=c/2.615 r_o$) to the acoustical frequency of an untapered tube ($f=c/4 r_o$) where r_o represents the tube length in that case, is $4/2.615=1.530$, in close agreement with the ratio experimentally found with tapered Hartmann-Sprenger tubes.

The dependance of the frequency with the pressure ratio observed by Wu et al. may be explained in the following way: the cycle of a resonator is made of four waves, an incident compression wave (or shock wave), a reflected compression wave, an incident expansion wave, and a reflected expansion wave. For an untapered Hartmann-Sprenger tube, Maresca⁴ has shown that the frequency decreases with increasing pressure ratio π if the flow oscillations are at their maximum amplitude, that is, when the limit cycle described in Ref. 5 is reached. In that case, the amplitude of the pressure oscillation Δp is increasing with π . This means that the frequency decreases with increasing amplitude Δp . In the tube fixed coordinates, the speed of the incident shock is supersonic and increases with Δp , whereas, the speed of the reflected shock is subsonic and decreases with Δp . The average speed of these two waves decreases only very slightly with Δp . What causes the frequency to decrease is that the time required for the expansion phase of the cycle increases with Δp . For a pressure ratio of 2 for instance, the frequency is about 12% lower than the acoustical frequency. This trend will very likely not be affected by the tapering of the tube. Now, in the experiments reported by Wu et al. (see their Fig. 5) above the critical pressure ratio of 3.76, the pressure amplitude Δp decreases with increasing π and this explains the increase of frequency observed with increasing pressure ratio.

References

- ¹Wu, J. H. T., Ostrowski, P. P., Neemeh, R. A., and Lee, P. H. W., "Experimental Investigation of a Cylindrical Resonator," *AIAA Journal*, Vol. 12, Aug. 1974, pp. 1076-1078.
- ²McAlevy, R. F., III and Pavlak, A., "Tapered Resonance Tubes: Some Experiments," *AIAA Journal*, Vol. 8, March 1970, pp. 571-572.
- ³Brocher, E. and Maresca, C., "Phenomenes aerodynamiques et thermiques dans un tube d'Hartmann-Sprenger a parois convergentes," *Comptes Rendus de l'Academie des Sciences, (Paris)*, Vol. 273, Dec. 1971, pp. 1303-1306.
- ⁴Maresca, C., "Etude des phenomenes aerodynamiques et thermiques intervenant dans les tubes de resonance," Ph.D. thesis Université de Provence, Marseille, France, May 1971.
- ⁵Brocher, E., Maresca, C., and Bournay, M-H., "Fluid Dynamics of the Resonance Tube," *Journal of Fluid Mechanics*, Vol. 43, Part 2, 1970, pp. 369-384.

Reply by Authors to E. Brocher and C. Maresca

J. H. T. Wu,* P. P. Ostrowski,† R. A. Neemeh,‡
and P. H. W. Lee§

McGill University, Montreal, Canada

E. BROCHER and C. Maresca have attempted to explain the frequency characteristics of the cylindrical cavity resonator by reasoning that a decrease in pressure amplitude leads to a reduction in the duration of the expansion phase of the resonant cycle. In other words, the period of outflow at the mouth of the resonator is reduced which in turn leads to higher oscillation frequencies. This interpretation appears to be the correct one.

However, considering a segment of the cylindrical resonator to be equivalent to a tapered tube resonator is not strictly valid since it is well known that in the latter, reflected waves will be generated at the walls as the shock propagates inwards.¹ For the cylindrical cavity resonator, no such reflections should occur, at least in the ideal case. This is the reason for examining such a configuration in the first place. Ideally, the converging cylindrical shock can achieve significantly greater shock amplification over its plane wave counterpart. The present investigation shows some promise in this regard.

References

- ¹Setchell, R. E., Storm, E., and Sturterant, B., "An Investigation of Shock Strengthening in a Conical Convergent Channel," *Journal of Fluid Mechanics*, Vol. 56, pt. 3, Dec. 1972, pp. 505-522.

Received December 5, 1974.

Index categories: Shock Waves and Detonation; Nonsteady Aerodynamics; Nozzle and Channel Flow.

*Associate Professor, Department of Mechanical Engineering.

†Research Engineer; presently, Assistant Professor, Department of Mechanical Engineering, University of Maryland, College Park, Md.

‡Research Engineer; also Assistant Professor, Concordia University, Montreal, Canada.

§Research Assistant.

Received October 3, 1974.

Index categories: Nonsteady Aerodynamics; Shock Waves and Detonations.

*Maitre de Recherche, Centre National de la Recherche Scientifique.

†Charge de Recherche, Centre Nationale de la Recherche Scientifique.

‡Laboratoire de Recherche Aérospatiale belonging to the Université d'Aix-Marseille II, associated with the Centre Nationale de la Recherche Scientifique (CNRS).