

NOTE ON GREEN'S FUNCTION FOR A SEMICIRCULAR PLATE

J. BOERSMA

Department of Mathematics, Eindhoven University of Technology, Eindhoven, The Netherlands

(Received 27 May 1980; in revised form 11 August 1980)

Abstract—A. K. Naghdi's [1] closed-form Green's function for a semicircular plate, clamped around the curved edge and simply supported along its diameter, is re-derived by the method of images.

Consider a semicircular plate of radius R which is simply supported along its diameter and clamped around its curved edge. In terms of dimensionless polar coordinates $\rho = r/R$ and θ , the plate is described by $0 \leq \rho \leq 1$, $0 \leq \theta \leq \pi$. The plate is acted upon by a transverse concentrated force P at the point (ρ_0, θ_0) , where $0 < \rho_0 < 1$, $0 < \theta_0 < \pi$. The resulting transverse displacement w of the plate is given by

$$w = \frac{PR^2}{D} G(\rho, \theta; \rho_0, \theta_0) \quad (1)$$

where D is the flexural rigidity of the plate and G is the biharmonic Green's function for the semicircular plate. The latter function is to be determined as a solution of the differential equation

$$\left. \begin{aligned} \nabla^2 \nabla^2 G &= \frac{\delta(\rho - \rho_0)}{\rho_0} \delta(\theta - \theta_0), \quad 0 < \rho < 1, \quad 0 < \theta < \pi, \\ \nabla^2 &= \frac{\partial^2}{\partial \rho^2} + \frac{1}{\rho} \frac{\partial}{\partial \rho} + \frac{1}{\rho^2} \frac{\partial^2}{\partial \theta^2}, \end{aligned} \right\} \quad (2)$$

subject to the boundary conditions

$$G = 0, \quad \frac{\partial G}{\partial \rho} = 0, \quad \text{at } \rho = 1, \quad 0 \leq \theta \leq \pi; \quad (3)$$

$$G = 0, \quad \nu \frac{\partial^2 G}{\partial \rho^2} + \frac{1}{\rho} \frac{\partial G}{\partial \rho} + \frac{1}{\rho^2} \frac{\partial^2 G}{\partial \theta^2} = 0 \quad \text{at } 0 \leq \rho \leq 1, \quad \theta = 0, \quad \theta = \pi. \quad (4)$$

In (4), ν denotes Poisson's ratio. A closed-form result for the Green's function G was recently obtained by Naghdi ([1], eqn 33). In this note Naghdi's result is re-derived in a simpler manner using the method of images.

In our approach the Green's function G is continued to the full circular region $0 \leq \rho \leq 1$, $-\pi \leq \theta \leq \pi$, by defining

$$G(\rho, \theta; \rho_0, \theta_0) = -G(\rho, -\theta; \rho_0, \theta_0), \quad 0 \leq \rho \leq 1, \quad -\pi \leq \theta \leq 0. \quad (5)$$

Then the continued function G will satisfy the differential equation

$$\nabla^2 \nabla^2 G = \frac{\delta(\rho - \rho_0)}{\rho_0} \delta(\theta - \theta_0) - \frac{\delta(\rho - \rho_0)}{\rho_0} \delta(\theta + \theta_0), \quad 0 \leq \rho < 1, \quad -\pi \leq \theta \leq \pi \quad (6)$$

and the boundary conditions

$$G = 0, \quad \frac{\partial G}{\partial \rho} = 0 \quad \text{at } \rho = 1, \quad -\pi \leq \theta \leq \pi. \quad (7)$$

For reasons of symmetry the solution of the problem (6), (7) will automatically satisfy the boundary conditions (4). Clearly, the function G represents the deflection of a clamped circular plate due to opposite concentrated loads at the points $(\rho_0, \pm \theta_0)$. Hence, G can be expressed in terms of the Green's function G_0 for a circular plate clamped around its edge, viz.

$$G(\rho, \theta; \rho_0, \theta_0) = G_0(\rho, \theta; \rho_0, \theta_0) - G_0(\rho, \theta; \rho_0, -\theta_0). \tag{8}$$

The Green's function G_0 is well known from early investigations by Michell[2] and Melan[3],

$$G_0(\rho, \theta; \rho_0, \theta_0) = \frac{1}{8\pi}(\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)) \log \left[\frac{\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)}{1 + \rho^2\rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)} \right]^{1/2} + \frac{1}{16\pi}(1 - \rho^2)(1 - \rho_0^2). \tag{9}$$

Thus we obtain as our final result

$$G(\rho, \theta; \rho_0, \theta_0) = \frac{1}{8\pi}(\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)) \log \left[\frac{\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)}{1 + \rho^2\rho_0^2 - 2\rho\rho_0 \cos(\theta - \theta_0)} \right]^{1/2} - \frac{1}{8\pi}(\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta + \theta_0)) \log \left[\frac{\rho^2 + \rho_0^2 - 2\rho\rho_0 \cos(\theta + \theta_0)}{1 + \rho^2\rho_0^2 - 2\rho\rho_0 \cos(\theta + \theta_0)} \right]^{1/2}. \tag{10}$$

It is readily seen that $G = 0$ and $\partial^2 G / \partial \theta^2 = 0$ at $0 \leq \rho \leq 1, \theta = 0, \theta = \pi$; hence, our solution does satisfy the boundary conditions (4) as already predicted above. The present closed-form result for the Green's function G is in accordance with ([1], eqn 33) after some re-arrangement of terms.

Finally, it is pointed out that the method of images can also be used to construct the Green's function G_n for a plate sector of angle $\pi/n, n = 1, 2, 3, \dots$, clamped around its curved edge and simply supported along its boundaries $\theta = 0$ and $\theta = \pi/n$. For example, in the cases $n = 2$ and $n = 3$ corresponding to a quarter sector and a 60°-sector, respectively, it is easily found that the Green's functions G_2 and G_3 are given by

$$G_2(\rho, \theta; \rho_0, \theta_0) = G_0(\rho, \theta; \rho_0, \theta_0) - G_0(\rho, \theta; \rho_0, -\theta_0) - G_0(\rho, \theta; \rho_0, -\theta_0 + \pi) + G_0(\rho, \theta; \rho_0, \theta_0 - \pi), \tag{11}$$

$$G_3(\rho, \theta; \rho_0, \theta_0) = G_0(\rho, \theta; \rho_0, \theta_0) - G_0(\rho, \theta; \rho_0, -\theta_0) - G_0(\rho, \theta; \rho_0, -\theta_0 + 2\pi/3) + G_0(\rho, \theta; \rho_0, \theta_0 - 2\pi/3) + G_0(\rho, \theta; \rho_0, \theta_0 + 2\pi/3) - G_0(\rho, \theta; \rho_0, -\theta_0 - 2\pi/3). \tag{12}$$

For general $n, n = 1, 2, 3, \dots$, the Green's function G_n can be expressed as

$$G_n(\rho, \theta; \rho_0, \theta_0) = \sum_{k=0}^{n-1} [G_0(\rho, \theta; \rho_0, \theta_0 + 2k\pi/n) - G_0(\rho, \theta; \rho_0, -\theta_0 - 2k\pi/n)], \tag{13}$$

where it has been used that $G_0(\rho, \theta; \rho_0, \theta_0)$ is periodic in θ_0 with period 2π .

REFERENCES

1. A. K. Naghdi, *Green's function for a semicircular plate. Int. J. Solids Structures* 16, 329-335 (1980).
2. J. H. Michell, *The flexure of a circular plate. Proc. London Math. Soc.* 34, 223-228 (1902).
3. E. Melan, *Die Durchbiegung einer exzentrisch durch eine Einzellast belastete Kreisplatte. Der Eisenbau* 11, 190-192 (1920).