

## QUADRATIC EXTREMUM PRINCIPLES FOR FINITE STRAIN RIGID-VISCOPLASTIC DYNAMICS OF CONTINUA

A. CARINI and O. DE DONATO

Dipartimento di Ingegneria Strutturale, Politecnico di Milano, Piazza Leonardo da Vinci, 32,  
20133 Milan, Italy

(Received 27 March 1986; in revised form 16 October 1986)

**Abstract**—Two quadratic extremum principles for finite strains of rigid-viscoplastic continua with piecewise linear constitutive laws are derived from and formulated using both the Eulerian and Lagrangian descriptions of the continuum motion. The principles generalize to finite strains two previous extremum properties of the dynamic solution of rigid-plastic small-strain, large displacement bodies found by Capurso. Stolarsky and Belytschko's recent non-quadratic theorem is shown to be a special form of one of the two theorems when the functional dependence from a variable is implicitly expressed.

### I. INTRODUCTION

The problem of determining the large displacement dynamic response of a body under a given high intensity loading has found, on the widely accepted assumption that the elastic strains are small as compared to total strains, a fundamental hypothesis for the development of a number of methods and numerical techniques forming an important part of the more recent developments the plastic body theory.

In this context Tamuzh's[1] extremum principle, which gives the acceleration field of a rigid-plastic solid at a given time, the velocity field as well as body and surface forces being known, was extended by Capurso[2] with two extremum principles to the large displacement (small strain) case in the presence of a rigid-viscoplastic solid with a piecewise-linear yield surface. In these extensions the functionals to optimize involve the acceleration and stress field, or the acceleration and plastic multiplier acceleration field, respectively.

A corresponding quadratic programming formulation was also derived by the same author in a finite element context.

More recently, Stolarsky and Belytschko[3] extended Tamuzh's principle to the more general case of large strains with a smooth yield surface and presented the results of an application to the particular case of rod structures, using a numerical procedure to determine the rigid-plastic response by solving a series of quadratic programming problems.

In this paper Capurso's principles are extended to cover the general case of finite strains and the two corresponding principles obtained involve the same pair of functions. They are both derived by the Eulerian and Lagrangian descriptions of the deformations (kinematic description) and of stresses (kinetic description).

In Section 2 the general formulation of the constitutive laws of rigid-plastic materials on the assumption of a piecewise-linear yield surface and finite strains, is given for both descriptions considering the need to refer to objective quantities in order to provide a description independent of the reference system.

Section 3 is concerned with the formulation of the problem using both the Lagrangian and Eulerian approaches, while in Section 4 extremum principles are derived.

Finally, Section 5 deals with the particularization of the new principles to the previous ones by Capurso (large displacements with small strains) and to the derivation of Stolarsky and Belytschko's formulation.

## 2. CONSTITUTIVE LAWS

## 2.1. Eulerian approach

Reference is made in the following to the Eulerian description of the kinetics and kinematics. In a Cartesian orthogonal reference system let  $x_i$  be the current position occupied by a particle at time  $t$  and let  $a_i$  be its original position at time  $t = 0$ . The components  $u_i$  of the finite displacement vector of the particle are then given by

$$u_i = x_i - a_i. \quad (1)$$

In this context the strain field will be described by the Almansi strain tensor defined by

$$e_{ij} = \frac{1}{2}(u_{ij} + u_{ji} - u_{k/i}u_{k/j}). \quad (2)$$

The stress field will be described in the following through the Cauchy stress tensor  $\sigma_{ij}$  the components of which refer to the strained state of the body. Besides, the assumption is made of rigid-viscoplastic hardening and associated material behaviour with yield domain, delimited, in the stress space  $\sigma_{ij}$ , by  $n$  planes

$$\varphi_\alpha = N_{\alpha ik}^n \sigma_{ik} - k_\alpha \leq 0 \quad (\alpha = 1, \dots, n) \quad (3)$$

where  $N_{\alpha ik}^n$  are the  $n$  outward unit vectors normal to the  $n$  yield planes, and

$$k_\alpha = r_\alpha + \sum_{\beta} H_{\alpha\beta} \dot{\lambda}_\beta \quad (4)$$

where  $r_\alpha$  defines the yield polyhedron plane distances from the origin in the original (virgin) state of the material, the interaction coefficients  $H_{\alpha\beta}$  define the hardening rule, and  $\dot{\lambda}_\beta$  denotes the plastic multiplier rates. In what follows  $r_\alpha$ ,  $H_{\alpha\beta}$  are assumed to be independent of  $\dot{\lambda}$  and matrix  $H_{\alpha\beta}$  to be symmetric definite positive.

In order to ensure the invariance of the yield function with respect to any rigid body motion of the material particle, the yield condition, eqn (3), must be expressed as a function of the corotational stress tensor

$$\hat{\sigma}_{ij} = R_{ni} \sigma_{nk} R_{kj} \quad (5)$$

where  $R_{ni}$ , defining the rigid body motion of the particle, is obtained by decomposing the deformation gradient

$$F_{ij} = \frac{\partial x_i}{\partial a_j} = \delta_{ij} + \frac{\partial u_i}{\partial a_j} \quad (6)$$

into the product of the rotation tensor  $R_{ik}$  and a (right) stretch tensor  $U_{kj}$  in the form

$$F_{ij} = R_{ik} U_{kj} \quad (7)$$

being

$$R_{ik} R_{jk} = \delta_{ij} \quad \text{and} \quad R_{ki} R_{kj} = \delta_{ij}. \quad (8)$$

Then the yield condition, eqn (3), becomes

$$\varphi_\alpha = \hat{N}_{\alpha ij} \hat{\sigma}_{ij} - k_\alpha \leq 0 \quad (3')$$

where

$$\hat{N}_{zij} = R_{ni} N_{znh}^{\sigma} R_{kj} \tag{9}$$

is invariant in the corotational reference system, and

$$N_{zij}^{\sigma} = R_{ih} \hat{N}_{znh} R_{jk} \tag{10}$$

In order to describe the associated flow rule the Almansi strain tensor is used as a measure of deformations. However, the rate

$$\dot{e}_{ij} = \frac{1}{2}(\dot{u}_{i,j} + \dot{u}_{j,i}) - (e_{ik} L_{kj} + L_{ki} e_{kj}) \tag{11}$$

is not conjugate to Cauchy stress (their scalar product does not give work) and the rate

$$D_{ij} = \frac{1}{2}(\dot{u}_{i,j} + \dot{u}_{j,i}) \tag{12}$$

(called "rate of deformation tensor") will be used. Then, through eqn (3), the associated flow rule becomes

$$D_{ij} = \sum_x \dot{\lambda}_x \frac{\partial \varphi_x}{\partial \sigma_{ij}} = \sum_x \dot{\lambda}_x N_{zij}^{\sigma} \tag{13}$$

under the constraints

$$\varphi_x \leq 0, \dot{\lambda}_x \geq 0, \varphi_x \dot{\lambda}_x = 0. \tag{14}$$

Limitation to the acceleration field  $\ddot{v}_{ij}$  must then be derived from eqns (13) and (14) equally involving objective quantities. However, from the material derivative of eqn (13), the following is obtained :

$$\dot{D}_{ij} = \sum_x \ddot{\lambda}_x \frac{\partial \varphi_x}{\partial \sigma_{ij}} + \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\partial \varphi_x}{\partial \sigma_{ij}} \right) \tag{15}$$

where

$$\dot{D}_{ij} = \frac{1}{2}(\ddot{u}_{i,j} + \ddot{u}_{j,i}) - \frac{1}{2}(\dot{u}_{ik} \dot{u}_{l,k} + \dot{u}_{kl} \dot{u}_{j,k}) \tag{16}$$

can be easily shown to be frame dependent. In order that objective quantities appear in the first member of eqn (15) the following relation can be used[4] :

$$\dot{D}_{ij} = D_{ij}^0 + W_{ik} D_{kj} - D_{ik} W_{kj} \tag{17}$$

where  $W_{ij} = \frac{1}{2}(\dot{u}_{i,j} - \dot{u}_{j,i})$  is the spin tensor and

$$D_{ij}^0 = \dot{D}_{ij} - W_{ik} D_{kj} + D_{ik} W_{kj} = \frac{1}{2}(\ddot{u}_{i,j} + \ddot{u}_{j,i}) - \frac{1}{2}(\dot{u}_{i,k} \dot{u}_{k,l} + \dot{u}_{k,l} \dot{u}_{j,k} + \dot{u}_{l,k} \dot{u}_{j,k} - \dot{u}_{k,l} \dot{u}_{k,i}) \tag{18}$$

(referred to as the "corotational derivative of  $D_{ij}$ ") may be easily proved to be frame independent. As a result eqn (15) becomes

$$D_{ij}^0 = \sum_x \ddot{\lambda}_x \frac{\partial \varphi_x}{\partial \sigma_{ij}} + \sum_x \dot{\lambda}_x \left[ \frac{d}{dt} (N_{zij}^{\sigma}) - W_{ik} N_{zkh}^{\sigma} + N_{zkh}^{\sigma} W_{kj} \right] \tag{19}$$

where the plastic multiplier accelerations  $\ddot{\lambda}_x$  are subjected to the constraints

$$\begin{aligned}
 \dot{\lambda}_x &= 0 & \text{if } \varphi_x < 0 \text{ and } \dot{\lambda}_x = 0 \\
 \dot{\lambda}_x &\geq 0 & \text{if } \varphi_x = 0 \text{ and } \dot{\lambda}_x = 0 \\
 \dot{\lambda}_x &\text{ free} & \text{if } \varphi_x = 0 \text{ and } \dot{\lambda}_x > 0
 \end{aligned}
 \tag{20}$$

which may be expressed as follows in a more compact form:

$$\begin{aligned}
 \varphi_x \dot{\lambda}_x &= 0 \text{ and } \dot{\lambda}_x \geq 0 & \text{if } \varphi_x \leq 0 \text{ and } \dot{\lambda}_x = 0 \text{ (} V_R \text{)} \\
 \varphi_x \dot{\lambda}_x &= 0 \text{ and } \dot{\lambda}_x \text{ free} & \text{if } \varphi_x = 0 \text{ and } \dot{\lambda}_x > 0 \text{ (} V_P \text{)}.
 \end{aligned}
 \tag{21}$$

In eqn (19) the second term of the second member always vanishes. In fact, when the material point lies in a rigid region,  $\dot{\lambda}_x = 0$ ; besides, considering that[4]

$$\frac{d}{dt}(R_{ij}) = \dot{R}_{ij} = W_{ik} R_{kj}
 \tag{22}$$

we have

$$\begin{aligned}
 \frac{d}{dt}(N_{xij}^\sigma) &= \frac{d}{dt}(R_{ih} \hat{N}_{xhk} R_{jk}) = W_{is} R_{sh} \hat{N}_{xhk} R_{jk} + R_{ih} \hat{N}_{xhk} W_{jr} R_{rk} \\
 &= W_{is} N_{xij}^\sigma + N_{xir}^\sigma W_{jr} = W_{is} N_{xij}^\sigma - N_{xir}^\sigma W_{rj}
 \end{aligned}
 \tag{23}$$

thus, in the plastic region too (where  $\dot{\lambda}_x > 0$ ) the second term of the second member of eqn (19) vanishes. This implies that the plastic multiplier accelerations are always governed by the condition

$$D_{ij}^0 = \sum_x \dot{\lambda}_x \frac{\partial \varphi_x}{\partial \sigma_{ij}} = \sum_x \dot{\lambda}_x N_{xij}^\sigma
 \tag{24}$$

stating the normality of the corotational derivative of the rate of the deformation tensor to the field surface.

In conclusion, the rigid-viscoplastic constitutive laws for large strains in the *Eulerian approach* can be summarized in the following relationships:

$$\varphi_x = N_{xik}^\sigma \sigma_{ik} - k_x \leq 0
 \tag{25}$$

$$D_{ij} = \sum_x \dot{\lambda}_x N_{xij}^\sigma
 \tag{26}$$

$$\dot{\lambda}_x \geq 0, \quad \varphi_x \dot{\lambda}_x = 0
 \tag{27}$$

$$D_{ij}^0 = \sum_x \ddot{\lambda}_x \frac{\partial \varphi_x}{\partial \sigma_{ij}} = \sum_x \ddot{\lambda}_x N_{xij}^\sigma
 \tag{28}$$

$$\varphi_x \dot{\lambda}_x = 0 \text{ and } \dot{\lambda}_x \geq 0 \quad \text{if } \varphi_x \leq 0 \text{ and } \dot{\lambda}_x = 0 \text{ (} V_R \text{)}
 \tag{29}$$

$$\varphi_x \dot{\lambda}_x = 0 \text{ and } \dot{\lambda}_x \text{ free} \quad \text{if } \varphi_x = 0 \text{ and } \dot{\lambda}_x > 0 \text{ (} V_P \text{)}
 \tag{30}$$

where eqns (29) and (30) define the rigid  $V_R$  and plastic  $V_P$  regions, respectively, and  $k_x$  is given by eqn (4).

## 2.2. Lagrangian approach

Let the assumed independent variables be the positions  $a_i$  occupied by a particle at time  $t = 0$ , i.e.

$$x_i = x_i(a_i) = a_i + u_i(a_i, t) \tag{31}$$

and let the stress and strain fields be described by Kirchhoff's and Green's tensors  $S_{ij}$ ,  $E_{ij}$ , respectively. The yield domain, eqn (25), becomes

$$\varphi_x = N_{xhk}^S S_{hk} - k_x \leq 0 \tag{32}$$

where

$$\begin{aligned} S_{hk} &= \frac{\rho_0}{\rho} \frac{\partial a_h}{\partial x_i} \frac{\partial a_k}{\partial x_j} \sigma_{ij} \\ \sigma_{ij} &= \frac{\rho}{\rho_0} \frac{\partial x_i}{\partial a_h} \frac{\partial x_j}{\partial a_k} S_{hk} \end{aligned} \tag{33}$$

$\rho_0$  and  $\rho$  being the initial and final density, and where, using eqn (25) once again

$$\begin{aligned} N_{xhk}^S &= \frac{\rho}{\rho_0} \frac{\partial x_i}{\partial a_h} \frac{\partial x_j}{\partial a_k} N_{xij}^\sigma \\ N_{xij}^\sigma &= \frac{\rho_0}{\rho} \frac{\partial a_h}{\partial x_i} \frac{\partial a_k}{\partial x_j} N_{xhk}^S. \end{aligned} \tag{34}$$

The flow rule, eqn (26), is transformed into

$$\dot{E}_{ij} = \sum_x \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \tag{35}$$

as can be easily shown starting from eqn (26) where  $N_{xhk}^\sigma$  is replaced by  $N_{xhk}^S$  using eqns (34) and taking into account the relation[4]

$$\dot{E}_{ij} = D_{hk} \frac{\partial x_h}{\partial a_i} \frac{\partial x_k}{\partial a_j} = \frac{\partial \dot{x}_k}{\partial a_i} \frac{\partial x_k}{\partial a_j} = \dot{F}_{ki} F_{kj}. \tag{36}$$

By a time derivative of eqn (35) we have finally

$$\ddot{E}_{ij} = \sum_x \ddot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S + \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right). \tag{37}$$

Equation (37) shows that  $\ddot{E}_{ij}$  is not normal to the yield surface. Taking into account eqns (A21), the last term of eqn (37) can be transformed as follows (denoting  $\partial/\partial a_j$  with  $/\bar{j}$ ):

$$\sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) = \sum_x \dot{\lambda}_x \hat{N}_{xrs} \frac{d}{dt} (x_{h/\bar{r}} x_{k/\bar{j}} R_{hr} R_{ks}) \tag{37'}$$

and then using eqns (22), (10), (13), and (12) and remembering that  $W_{ij} = \frac{1}{2}(\dot{u}_{ij} - \dot{u}_{ji})$

$$\begin{aligned} \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) &= \sum_x \dot{\lambda}_x [N_{xhk}^\sigma (\dot{u}_{h/\bar{r}} x_{k/\bar{j}} + x_{h/\bar{r}} \dot{u}_{k/\bar{j}}) \\ &\quad + N_{xmk}^\sigma x_{h/\bar{r}} x_{k/\bar{j}} W_{hm} + N_{xhn}^\sigma x_{h/\bar{r}} x_{k/\bar{j}} W_{kn}] \\ &= \frac{1}{2} (\dot{u}_{k/\bar{r}} \dot{u}_{k/\bar{j}} + \dot{u}_{h/\bar{k}} x_{h/\bar{r}} \dot{u}_{k/\bar{j}} + \dot{u}_{k/\bar{h}} \dot{u}_{h/\bar{r}} x_{k/\bar{j}} \\ &\quad + \dot{u}_{k/\bar{m}} x_{h/\bar{r}} x_{k/\bar{j}} \dot{u}_{h/\bar{m}}). \end{aligned} \tag{38}$$

In conclusion, the rigid-viscoplastic constitutive laws for large strains in the *Lagrangian approach* can be summarized in the following relations :

$$\varphi_x = N_{xhk}^S S_{hk} - k_x \leq 0 \quad (39)$$

$$\dot{E}_{ij} = \sum_x \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \quad (40)$$

$$\dot{\lambda}_x \geq 0, \quad \varphi_x \dot{\lambda}_x = 0 \quad (41)$$

$$\ddot{E}_{ij} = \sum_x \ddot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S + \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) \quad (42)$$

$$\varphi_x \dot{\lambda}_x = 0 \text{ and } \dot{\lambda}_x \geq 0 \text{ if } \varphi_x \leq 0 \text{ and } \dot{\lambda}_x = 0 \text{ (} V_{R0} \text{)} \quad (43)$$

$$\varphi_x \dot{\lambda}_x = 0 \text{ and } \dot{\lambda}_x \text{ free if } \varphi_x = 0 \text{ and } \dot{\lambda}_x > 0 \text{ (} V_{P0} \text{)} \quad (44)$$

where eqns (43) and (44) define the rigid  $V_{R0}$  and plastic  $V_{P0}$  regions, respectively, and  $k_x$  is given by eqn (4).

### 2.3. Determination of plastic multiplier rates

A problem ever encountered when solving a rigid-viscoplastic dynamic problem is find out whether at a given time  $t$ , a particular point with a known deformation gradient  $D_{ij}$  or  $\dot{E}_{ij}$  lies in the plastic or rigid region. This can be accomplished simply by determining the plastic multiplier rate  $\dot{\lambda}_x$  corresponding to that particular  $D_{ij}$ , as  $\dot{\lambda}_x$  is positive in the plastic region only, whereas it vanishes in the rigid one.

With reference to the *Eulerian approach*, through the same proof used in Ref. [2] but replacing the flow rule by the condition

$$D_{ij} = \sum_x N_{xij}^a \dot{\lambda}_x \quad (45)$$

it is possible to derive the following statement : the quadratic functional

$$\Omega(\dot{\lambda}_x^*) = \frac{1}{2} \sum_{\alpha\beta} H_{\alpha\beta} \dot{\lambda}_\alpha^* \dot{\lambda}_\beta^* + \sum_x r_x \dot{\lambda}_x^* \quad (46)$$

defined for all plastic multiplier rates  $\dot{\lambda}_x^*$  satisfying the conditions

$$D_{ij} = \frac{1}{2} (\dot{u}_{i/j} + \dot{u}_{j/i}) = \sum_x N_{xij}^a \dot{\lambda}_x^* \quad (47)$$

$$\dot{\lambda}_x^* \geq 0$$

attains an absolute minimum for the real value of the plastic multiplier rate  $\dot{\lambda}_x$ .

If the hardening coefficients  $H_{\alpha\beta}$  define a positive definite hardening matrix, the solution  $\dot{\lambda}_x$  will be unique.

The stress state  $\sigma_{ij}$  corresponding to the deformation tensor  $D_{ij}$  not always can be determined uniquely. In fact, the only limitations on the stresses  $\sigma_{ij}$  are set by conditions (27), i.e.

$$N_{xij}^a \sigma_{ij} - k_x = 0 \text{ if } \dot{\lambda}_x > 0$$

$$N_{xij}^a \sigma_{ij} - k_x \leq 0 \text{ if } \dot{\lambda}_x = 0 \quad (47')$$

which may not be sufficient to determine  $\sigma_{ij}$  univocally.

Finally, using the *Lagrangian approach* the above statements still hold after replacing the normality condition (47) by the new one

$$\begin{aligned} \dot{E}_{ij} &= \sum_x \dot{\lambda}_x^* \frac{\rho_0}{\rho} N_{xij}^S \\ \dot{\lambda}_x^* &\geq 0. \end{aligned} \tag{47''}$$

3. FORMULATION OF THE DYNAMIC-LOADING PROBLEM

3.1. *Eulerian approach*

Let us assume that, at a given time  $t$ , the current configuration  $u_i$  of a body having volume  $V$  and surface  $S$ , the density  $\rho$ , the field of velocities  $\dot{u}_i$ , the surface tractions  $T_i$  on a part  $S_T$  of  $S$ , the surface accelerations  $\ddot{U}_i$  over the remaining part  $S_u = S - S_T$  of the surface, and the body forces  $X_i = \rho F_i$  are known.

The dynamic-loading problem consists in determining the stress field  $\sigma_{ij}$  and the acceleration field  $\ddot{u}_i$  for the same instant  $t$ . From the solution of this problem, when dealing with time-dependent known quantities  $X_i(t)$ ,  $T_i(t)$ ,  $u_i(t)$ ,  $\dot{u}_i(t)$  and  $\ddot{U}_i(t)$ , the whole dynamic history, i.e. the unknown functions  $\ddot{u}_i(t)$ ,  $\sigma_{ij}(t)$  can be obtained simply by an incremental process over time  $t$ .

All the conditions governing the dynamic-loading problem at a generic instant  $t$  are given below.

(a) Equilibrium equations

$$\begin{aligned} \sigma_{ij,j} + \rho F_i &= \rho \ddot{u}_i \quad \text{in } V \\ \sigma_{ij} n_j &= T_i \quad \text{on } S_T \end{aligned} \tag{48}$$

where  $\sigma_{ij}$  are the components of the Cauchy stress tensor.

(b) Compatibility equations

$$\begin{aligned} e_{ij} &= \frac{1}{2}(u_{ij} + u_{ji} - u_{k,i}u_{k,j}) \\ \dot{e}_{ij} &= \frac{1}{2}(\dot{u}_{ij} + \dot{u}_{ji}) - (e_{ik}\dot{u}_{k,j} + \dot{u}_{k,i}e_{kj}) \\ \ddot{e}_{ij} &= \dot{D}_{ij} - (D_{ik}\dot{u}_{k,j} - e_{ih}\dot{u}_{h,k}\dot{u}_{k,j} - \dot{u}_{h,i}e_{hk}\dot{u}_{k,j} \\ &\quad + e_{ik}(\ddot{u}_{k,j} - \dot{u}_{h,j}\dot{u}_{k,h}) + e_{kj}(\ddot{u}_{k,i} - \dot{u}_{h,i}\dot{u}_{k,h}) \\ &\quad + \dot{u}_{k,i}D_{kj} - \dot{u}_{k,i}e_{kh}\dot{u}_{h,j} - \dot{u}_{k,i}\dot{u}_{h/k}e_{hj}) \quad \text{in } V \\ \ddot{u}_j &= \ddot{U}_j \quad \text{on } S_u \end{aligned} \tag{49}$$

where  $e_{ij}$  are the components of the Almansi strain tensor ; besides

$$\dot{D}_{ij} = \frac{1}{2}(\ddot{u}_{ij} + \ddot{u}_{ji}) - \frac{1}{2}(\dot{u}_{k,j}\dot{u}_{i/k} + \dot{u}_{k,i}\dot{u}_{j/k}) \tag{50}$$

and the objective derivatives  $D_{ij}$  of  $e_{ij}$  and  $D_{ij}^0$  of  $\dot{e}_{ij}$  are

$$\begin{aligned} D_{ij} &= \frac{1}{2}(\dot{u}_{ij} + \dot{u}_{ji}) \\ D_{ij}^0 &= \frac{1}{2}(\ddot{u}_{ij} + \ddot{u}_{ji}) - \frac{1}{2}(\dot{u}_{k,j}\dot{u}_{i/k} + \dot{u}_{k,i}\dot{u}_{j/k} + \dot{u}_{i/k}\dot{u}_{j/k} - \dot{u}_{k,i}\dot{u}_{k,j}). \end{aligned} \tag{51}$$

(c) Constitutive laws, given by eqns (25)–(30). The velocity field  $\dot{\lambda}_x$  appearing in the above equations can be obtained as indicated in Section 2.3 from the known field  $\dot{u}_i$  (which define  $D_{ij}$  according eqn (51)<sub>1</sub>).

### 3.2. Lagrangian approach

All the equations governing the dynamic loading problem at a generic instant  $t$  are given below.

(a) Equilibrium equations

$$\begin{aligned} \frac{\partial}{\partial a_j} \left( S_{jk} \frac{\partial x_i}{\partial a_k} \right) + \rho_0 F_{0i} &= \rho_0 \ddot{u}_i \quad \text{in } V_0 \\ S_{jk} \frac{\partial x_i}{\partial a_k} n_{0j} &= T_{0i} \quad \text{on } S_{0T} \end{aligned} \quad (52)$$

where  $S_{ij}$  are the components of the Kirchhoff symmetric stress tensor.

(b) Compatibility equations (denoting  $\partial/\partial a_j$  with  $/j$ )

$$\begin{aligned} E_{ij} &= \frac{1}{2}(u_{ij} + u_{ji} + u_{k/i} u_{k/j}) \\ \dot{E}_{ij} &= \frac{1}{2}(\dot{u}_{ij} + \dot{u}_{ji} + \dot{u}_{k/i} u_{k/j} + u_{k/i} \dot{u}_{k/j}) \\ \ddot{E}_{ij} &= \frac{1}{2}(\ddot{u}_{ij} + \ddot{u}_{ji} + \ddot{u}_{k/i} u_{k/j} + u_{k/i} \ddot{u}_{k/j}) + \dot{u}_{k/i} \dot{u}_{k/j} \quad \text{in } V_0 \\ \ddot{u}_i &= \ddot{U}_{i0} \quad \text{on } S_{0u} \end{aligned} \quad (53)$$

where  $E_{ij}$  are the components of the Green strain tensor and  $\dot{E}_{ij}$  and  $\ddot{E}_{ij}$  are objective by definition.

(c) Constitutive laws, given by eqns (39)–(44). The velocity field  $\dot{\lambda}_x$  appearing in the above equations can be obtained as indicated in Section 2.3 from the known fields  $u_i$  and  $\dot{u}_i$  (which define  $\dot{E}_{ij}$  according eqn (53)<sub>2</sub>).

## 4. MINIMUM PRINCIPLES

### 4.1. Eulerian approach

*Theorem 1. The functional*

$$\begin{aligned} \Phi(\sigma_{ij}^*, \ddot{u}_j^*) &= \frac{1}{2} \int_V \rho \ddot{u}_j^* \ddot{u}_j^* \, dV + \frac{1}{2} \int_V \sigma_{ij}^* [\dot{u}_{i/j} \dot{u}_{k/l} + \dot{u}_{k/l} \dot{u}_{j/i} + \dot{u}_{i/k} \dot{u}_{j/l} - \dot{u}_{k/l} \dot{u}_{i/j}] \, dV \\ &\quad - \int_{S_u} \sigma_{ij}^* n_i \dot{U}_j \, dS_u \end{aligned} \quad (54)$$

defined for all stresses  $\sigma_{ij}^*$  and accelerations  $\ddot{u}_j^*$  satisfying the conditions

$$\begin{aligned} \sigma_{ij/i} + \rho F_j &= \rho \ddot{u}_j^* \quad \text{in } V \\ \sigma_{ij}^* n_i &= T_j \quad \text{on } S_T \\ N_{\alpha ik}^a \sigma_{ik}^* - k_\alpha &= 0 \quad \text{in } V_P \\ N_{\alpha ik}^a \sigma_{ik}^* - k_\alpha &\leq 0 \quad \text{in } V_R \end{aligned} \quad (55)$$

attains an absolute minimum for the actual stress  $\sigma_{ij}$  and accelerations  $\ddot{u}_j$  fields,  $V_P$  and  $V_R$  being the plastic and rigid regions defined by conditions (29) and (30), respectively.

*Proof.* In order to prove the theorem, it suffices to show that the difference

$$\Delta\Phi = \Phi(\sigma_{ij}^*, \ddot{u}_j^*) - \Phi(\sigma_{ij}, \ddot{u}_j) \quad (56)$$

is always nonnegative for any arbitrary  $\sigma_{ij}^*, \ddot{u}_j^*$  satisfying conditions (55). Assuming



$$\begin{aligned}\Delta\sigma_{ij} &= \sigma_{ij}^* - \sigma_{ij} \\ \Delta\ddot{u}_j &= \ddot{u}_j^* - \ddot{u}_j\end{aligned}\tag{57}$$

the difference, eqn (56), becomes

$$\begin{aligned}\Delta\Phi &= \frac{1}{2} \int_V \rho \Delta\ddot{u}_j \Delta\ddot{u}_j \, dV + \int_V \rho \Delta\ddot{u}_j \ddot{u}_j \, dV + \frac{1}{2} \int_V \Delta\sigma_{ij} [\dot{u}_{i,k} \dot{u}_{k,j} + \dot{u}_{k,i} \dot{u}_{j,k} + \dot{u}_{i,k} \dot{u}_{j,k} - \dot{u}_{k,i} \dot{u}_{k,j}] \, dV \\ &\quad - \int_{S_u} \Delta\sigma_{ij} n_i \dot{U}_j \, dS_u.\end{aligned}\tag{58}$$

Using Gauss's theorem and eqns (55)<sub>1</sub> and (55)<sub>2</sub>

$$\int_V \rho \Delta\ddot{u}_j \ddot{u}_j \, dV = \int_V \Delta\sigma_{ij,i} \ddot{u}_j \, dV = - \int_V \Delta\sigma_{ij} \ddot{u}_{j,i} \, dV + \int_{S_u} \Delta\sigma_{ij} n_i \dot{U}_j \, dS_u + \int_{S_T} \Delta\sigma_{ij} n_i \dot{U}_j \, dS_T\tag{59}$$

where the last term of the second member vanishes because  $\Delta\sigma_{ij} = 0$  on  $S_T$ . Then the difference, eqn (56), becomes

$$\begin{aligned}\Delta\Phi &= \frac{1}{2} \int_V \rho \Delta\ddot{u}_j \Delta\ddot{u}_j \, dV - \int_V \Delta\sigma_{ij} \ddot{u}_{j,i} \, dV + \frac{1}{2} \int_V \Delta\sigma_{ij} [\dot{u}_{i,k} \dot{u}_{k,j} + \dot{u}_{k,i} \dot{u}_{j,k} + \dot{u}_{i,k} \dot{u}_{j,k} - \dot{u}_{k,i} \dot{u}_{k,j}] \, dV\end{aligned}\tag{60}$$

where the second integral, owing to the symmetry of the Cauchy stress tensor, may be written in the form

$$- \int_V \Delta\sigma_{ij} \ddot{u}_{j,i} \, dV = - \frac{1}{2} \int_V \Delta\sigma_{ij} (\ddot{u}_{i,j} + \ddot{u}_{j,i}) \, dV\tag{61}$$

and the difference  $\Delta\Phi$ , by virtue of eqn (18), becomes

$$\Delta\Phi = \frac{1}{2} \int_V \rho \Delta\ddot{u}_j \Delta\ddot{u}_j \, dV - \int_V \Delta\sigma_{ij} D_{ij}^0 \, dV.\tag{62}$$

The first term on the right-hand side is always positive for any non-vanishing  $\Delta\ddot{u}_j$ , and equal to zero if and only if

$$\ddot{u}_i^* = \ddot{u}_i \quad \text{in } V.\tag{62'}$$

Using eqn (28) the second term becomes

$$- \int_V \Delta\sigma_{ij} D_{ij}^0 \, dV = - \sum_{\alpha} \int_V \Delta\sigma_{ij} N_{\alpha ij}^* \dot{\lambda}_{\alpha} \, dV.\tag{63}$$

In region  $V_p$  (where  $\varphi_{\alpha} = 0$  and  $\dot{\lambda}_{\alpha} > 0$ ), from eqns (55)<sub>3</sub> and (30) it can be stated that

$$-\sum_x \int_V \Delta \sigma_{ij} N_{xi}^x \dot{\lambda}_x \, dV = \sum_x \int_V (N_{xi}^x \sigma_{ij} - k_x) \dot{\lambda}_x \, dV = \sum_x \int_V \varphi_x \dot{\lambda}_x \, dV = 0. \quad (64)$$

In the remaining region  $V_R$  (where  $\dot{\lambda}_x = 0$ ), from the condition

$$\varphi_x \dot{\lambda}_x = (N_{xi}^x \sigma_{ij} - k_x) \dot{\lambda}_x = 0 \quad (65)$$

we can write eqn (63) in the form

$$-\sum_x \int_V \Delta \sigma_{ij} N_{xi}^x \dot{\lambda}_x \, dV = -\sum_x \int_V (N_{xi}^x \sigma_{ij}^* - k_x) \dot{\lambda}_x \, dV \quad (66)$$

which will never be negative as a result of condition (55)<sub>3</sub> and of the nonnegativity of  $\dot{\lambda}_x$  in  $V_R$  stated in eqn (29). It will be equal to zero if and only if

$$N_{xi}^x \sigma_{ij}^* - k_x = 0 \quad \text{where } \dot{\lambda}_x > 0. \quad (66')$$

This proves that

$$\Phi(\sigma_{ij}^*, \ddot{u}_j^*) \geq \Phi(\sigma_{ij}, \ddot{u}_j) \quad (67)$$

for any stress  $\sigma_{ij}^*$  and acceleration  $\ddot{u}_j^*$  fields satisfying conditions (55), the equality sign holding if and only if the accelerations  $\ddot{u}_j^*$  satisfy eqn (62') and stresses  $\sigma_{ij}^*$  satisfy eqn (66').

This proves the theorem. It follows from this proof that the actual acceleration field  $\ddot{u}_j$  is univocally defined; on the contrary, the actual stress field  $\sigma_{ij}$  may not be determined univocally because the only limitations that we must respect are

$$\begin{aligned} N_{xi}^x \sigma_{ij}^* - k_x &= 0 && \text{in } V_p \\ N_{xi}^x \sigma_{ij}^* - k_x &= 0 && \text{if } \dot{\lambda}_x > 0 \text{ in } V_R \\ N_{xi}^x \sigma_{ij}^* - k_x &\leq 0 && \text{if } \dot{\lambda}_x = 0 \text{ in } V_R \end{aligned} \quad (67')$$

which may not always be sufficient to determine  $\sigma_{ij}^*$  univocally.

*Theorem II. The functional*

$$\Psi(\ddot{u}_j^*, \dot{\lambda}_x^*) = \frac{1}{2} \int_V \rho \ddot{u}_j^* \ddot{u}_j^* \, dV - \int_V \rho F_j \ddot{u}_j^* \, dV - \int_{S_r} T_j \ddot{u}_j^* \, dS_r + \sum_x \int_V k_x \dot{\lambda}_x^* \, dV \quad (68)$$

defined for all accelerations  $\ddot{u}_j^*$  and plastic multiplier accelerations  $\dot{\lambda}_x^*$  satisfying the conditions

$$\begin{aligned} \ddot{u}_j^* &= \ddot{U}_j && \text{on } S_u \\ \sum_x N_{xi}^x \dot{\lambda}_x^* &= \frac{1}{2} (\ddot{u}_{ij}^* + \ddot{u}_{ji}^*) - \frac{1}{2} (\dot{u}_{k,i} \dot{u}_{j,k} + \dot{u}_{k,j} \dot{u}_{i,k} + \dot{u}_{i,k} \dot{u}_{j,k} - \dot{u}_{k,i} \dot{u}_{k,j}) = D_{ij}^{0*} && \text{in } V \\ \dot{\lambda}_x^* &\geq 0 && \text{in } V_R \end{aligned} \quad (69)$$

attains an absolute minimum for the actual accelerations  $\ddot{u}_j$  and plastic multiplier accelerations  $\dot{\lambda}_x$ ,  $V_R$  being the rigid region as defined by eqn (29).

*Proof.* The following proves that the difference

$$\Delta \Psi = \Psi(\ddot{u}_j^*, \dot{\lambda}_x^*) - \Psi(\ddot{u}_j, \dot{\lambda}_x) \quad (70)$$

is always nonnegative for any arbitrary  $\ddot{u}_j^*, \dot{\lambda}_x^*$  satisfying conditions (69). Assuming

$$\begin{aligned} \Delta \ddot{u}_j &= \ddot{u}_j^* - \ddot{u}_j \\ \Delta \dot{\lambda}_x &= \dot{\lambda}_x^* - \dot{\lambda}_x \end{aligned} \tag{71}$$

the above difference becomes

$$\Delta \Psi = \frac{1}{2} \int_V \rho \Delta \ddot{u}_j \Delta \ddot{u}_j \, dV + \int_V \rho \ddot{u}_j \Delta \ddot{u}_j \, dV - \int_V \rho F_j \Delta \ddot{u}_j \, dV - \int_{S_T} T_j \Delta \ddot{u}_j \, dS_T + \sum_x \int_V k_x \Delta \dot{\lambda}_x \, dV. \tag{72}$$

Using the equilibrium equations, eqns (48), and Gauss's theorem we obtain

$$\begin{aligned} \int_V \rho \ddot{u}_j \Delta \ddot{u}_j \, dV &= \int_V \sigma_{ij,i} \Delta \ddot{u}_j \, dV + \int_V \rho F_j \Delta \ddot{u}_j \, dV \\ &= \int_{S_T} T_j \Delta \ddot{u}_j \, dS_T - \int_V \sigma_{ij} \Delta \ddot{u}_{j,i} \, dV + \int_V \rho F_j \Delta \ddot{u}_j \, dV \end{aligned} \tag{73}$$

and consequently the difference  $\Delta \Psi$  reduces to

$$\Delta \Psi = \frac{1}{2} \int_V \rho \Delta \ddot{u}_j \Delta \ddot{u}_j \, dV - \int_V \sigma_{ij} \Delta \ddot{u}_{j,i} \, dV + \sum_x \int_V k_x \Delta \dot{\lambda}_x \, dV. \tag{74}$$

The symmetry of the Cauchy stress tensor and the use of eqn (51)<sub>2</sub>, enable us to write the second integral of eqn (74) in the form

$$- \int_V \sigma_{ij} \Delta \ddot{u}_{j,i} \, dV = - \frac{1}{2} \int_V \sigma_{ij} (\Delta \ddot{u}_{i,j} + \Delta \ddot{u}_{j,i}) \, dV = - \int_V \sigma_{ij} \Delta D_{ij}^0 \, dV. \tag{75}$$

Then

$$\Delta \Psi = \frac{1}{2} \int_V \rho \Delta \ddot{u}_j \Delta \ddot{u}_j \, dV - \int_V \sigma_{ij} \Delta D_{ij}^0 \, dV + \sum_x \int_V k_x \Delta \dot{\lambda}_x \, dV \tag{76}$$

which, using condition (69)<sub>2</sub>, is transformed into

$$\Delta \Psi = \frac{1}{2} \int_V \rho \Delta \ddot{u}_j \Delta \ddot{u}_j \, dV - \sum_x \int_V (N_{xij}^\sigma \sigma_{ij} - k_x) \Delta \dot{\lambda}_x \, dV. \tag{77}$$

The first integral is always positive and equal to zero if and only if

$$\ddot{u}_j^* = \ddot{u}_j \quad \text{in } V. \tag{77'}$$

The second integral, in the region  $V_P$  vanishes, because  $\varphi_x = 0$ ; in the remaining region  $V_R$ , by virtue of the condition

$$\varphi_x \dot{\lambda}_x = (N_{xij}^\sigma \sigma_{ij} - k_x) \dot{\lambda}_x = 0 \tag{78}$$

the term reduces

$$-\sum_x \int_V (N_{xij}^a \sigma_{ij} - k_x) \Delta \dot{\lambda}_x^* dV = -\sum_x \int_{V_R} (N_{xij}^a \sigma_{ij} - k_x) \dot{\lambda}_x^* dV \tag{79}$$

which is always nonnegative for every non-vanishing  $\dot{\lambda}_x^*$  in consequence of condition (69), and because  $\varphi_x \leq 0$ , and is zero if and only if

$$\dot{\lambda}_x^* = 0 \quad \text{where} \quad N_{xij}^a \sigma_{ij} - k_x < 0 \quad \text{in } V_R. \tag{79'}$$

This proves that

$$\Psi(\ddot{u}_i^*, \dot{\lambda}_x^*) \geq \Psi(\ddot{u}_i, \dot{\lambda}_x) \tag{80}$$

for any acceleration field  $\ddot{u}_i^*$  and plastic multiplier accelerations  $\dot{\lambda}_x^*$  satisfying conditions (69), the equality sign holds only inasmuch as eqns (77') and (79') are satisfied.

This proves the theorem. Again, it follows from this proof that the actual acceleration field  $\ddot{u}_i$  is univocally defined; on the contrary, the actual plastic multiplier accelerations  $\dot{\lambda}_x$  may not be determined univocally (even for non-vanishing hardening coefficients  $H_{x\beta}$ ), because the only limitations that  $\dot{\lambda}_x^*$  must satisfy are

$$\begin{aligned} \sum_x N_{xij}^a \dot{\lambda}_x^* &= D_{ij}^{0*} \\ \dot{\lambda}_x^* &\geq 0 \quad \text{if } N_{xij}^a \sigma_{ij} - k_x = 0 \quad \text{in } V_R \\ \dot{\lambda}_x^* &= 0 \quad \text{if } N_{xij}^a \sigma_{ij} - k_x < 0 \quad \text{in } V_R \end{aligned} \tag{80'}$$

which may not be sufficient to determine  $\dot{\lambda}_x^*$  univocally.

4.2. Lagrangian approach

A simple way to derive a theorem corresponding to Theorem I but involving quantities relevant to the Lagrangian approach only, is to adopt a similar proof as Theorem I starting from the following statement.

The functional

$$\begin{aligned} \Phi^L(S_{ij}^*, \ddot{u}_j^*) &= \frac{1}{2} \int_{V_0} \rho_0 \ddot{u}_j^* \ddot{u}_j^* dV_0 + \frac{1}{2} \int_{V_0} S_{ij}^* (x_{h[i} \dot{u}_{r]j} \dot{u}_{h[r} + x_{h[i} \dot{u}_{k]j} \dot{u}_{h[r} \dot{u}_{k[r} \\ &\quad + \dot{u}_{r[i} \dot{u}_{k]j} \dot{u}_{k[r} - \dot{u}_{r[i} \dot{u}_{r]j}) dV_0 - \int_{S_{\sigma_0}} x_{k[j} S_{ij}^* n_{0i} \dot{U}_k dS_{\sigma_0} \end{aligned} \tag{81}$$

defined for all stress  $S_{ij}^*$  and acceleration  $\ddot{u}_j^*$  fields satisfying the conditions

$$\begin{aligned} \frac{\partial}{\partial a_j} \left( S_{jk}^* \frac{\partial x_j}{\partial a_k} \right) + \rho_0 F_{0i} &= \rho_0 \ddot{u}_i^* \quad \text{in } V_0 \\ S_{jk}^* \frac{\partial x_j}{\partial a_k} n_{0j} &= T_{0j} \quad \text{on } S_{T0} \\ N_{zik}^S S_{ik}^* - k_x &= 0 \quad \text{in } V_{P0} \\ N_{zik}^S S_{ik}^* - k_x &\leq 0 \quad \text{in } V_{R0} \end{aligned} \tag{82}$$

attains an absolute minimum for the actual stresses  $S_{ij}$  and accelerations  $\ddot{u}_i$ ,  $V_{P0}$  and  $V_{R0}$  being the plastic and rigid regions referred to the initial configuration.

Again, the proof consists in showing that the difference

$$\Delta\Phi^L = \Phi^L(S_{ij}^*, \bar{u}_j^*) - \Phi^L(S_{ij}, \bar{u}_j) \tag{83}$$

is always nonnegative for any arbitrary  $S_{ij}^*, \bar{u}_j^*$  satisfying conditions (82).

Assuming

$$\begin{aligned} \Delta S_{ij} &= S_{ij}^* - S_{ij} \\ \Delta \bar{u}_j &= \bar{u}_j^* - \bar{u}_j \\ A_{ij} &= x_{h,i} \bar{u}_{r,j} \bar{u}_{h,r} + x_{h,i} \bar{u}_{r,j} \bar{u}_{h,r} \bar{u}_{k,r} + \bar{u}_{r,i} x_{k,j} \bar{u}_{k,r} + \bar{u}_{r,i} \bar{u}_{r,j} \\ B_{ij} &= A_{ij} - 2\bar{u}_{r,i} \bar{u}_{r,j} \end{aligned} \tag{84}$$

we have

$$\Delta\Phi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \bar{u}_i \Delta \bar{u}_i \, dV_0 + \int_{V_0} \rho_0 \Delta \bar{u}_i \bar{u}_i \, dV_0 + \frac{1}{2} \int_{V_0} \Delta S_{ij} B_{ij} \, dV_0 - \int_{S_{u_0}} \frac{\partial x_k}{\partial a_j} \Delta S_{ij} n_{0i} \bar{U}_k \, dS_{u_0}. \tag{85}$$

Using (equilibrium) eqns (82)<sub>1</sub> and (82)<sub>2</sub> and Gauss's theorem, we obtain

$$\begin{aligned} \int_{V_0} \rho_0 \Delta \bar{u}_i \bar{u}_i \, dV_0 &= \int_{V_0} \left( \Delta S_{jk} \frac{\partial x_i}{\partial a_k} \right)_j \bar{u}_i \, dV_0 \\ &= - \int_{V_0} \Delta S_{jk} \frac{\partial x_i}{\partial a_k} \bar{u}_{i,j} \, dV_0 + \int_{S_{u_0}} \Delta S_{jk} \frac{\partial x_i}{\partial a_k} n_{0j} \bar{U}_i \, dS_{u_0} \\ &\quad + \int_{S_{r_0}} \Delta S_{jk} \frac{\partial x_i}{\partial a_k} n_{0i} \bar{U}_j \, dS_{r_0} \end{aligned} \tag{86}$$

where the last term on the right-hand side vanishes because  $\Delta S_{jk} = 0$  on  $S_{r_0}$ . Then the difference, eqn (85), becomes

$$\Delta\Phi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \bar{u}_i \Delta \bar{u}_i \, dV_0 - \int_{V_0} \Delta S_{jk} \left( \frac{\partial x_i}{\partial a_k} \bar{u}_{i,j} \right) \, dV_0 + \frac{1}{2} \int_{V_0} \Delta S_{ij} B_{ij} \, dV_0$$

where on account of the symmetry of the Kirchhoff stress tensor, and using eqns (A3), the second integral may be written as

$$\begin{aligned} - \int_{V_0} \Delta S_{jk} \left( \frac{\partial x_i}{\partial a_k} \bar{u}_{i,j} \right) \, dV_0 &= - \frac{1}{2} \int_{V_0} \Delta S_{jk} \left[ \frac{\partial x_i}{\partial a_k} \bar{u}_{i,j} + \frac{\partial x_i}{\partial a_j} \bar{u}_{i,k} \right] \, dV_0 \\ &= - \frac{1}{2} \int_{V_0} \Delta S_{jk} [\bar{u}_{k,j} + \bar{u}_{i,j} u_{i,k} + \bar{u}_{j,k} + \bar{u}_{i,k} u_{i,j}] \, dV_0 \end{aligned} \tag{87}$$

and the difference  $\Delta\Phi^L$ , by virtue of eqns (53), becomes

$$\Delta\Phi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \bar{u}_i \Delta \bar{u}_i \, dV_0 - \int_{V_0} \Delta S_{ij} \bar{E}_{ij} \, dV_0 + \frac{1}{2} \int_{V_0} \Delta S_{ij} A_{ij} \, dV_0. \tag{88}$$

In eqn (88) the first integral of the second member is always positive for every non-vanishing  $\Delta \bar{u}_i$ , and equal to zero if and only if

$$\ddot{u}_i^* = \ddot{u}_i \quad \text{in } V_0. \tag{89}$$

In consideration of eqn (42) the second term on the right-hand side of eqn (88) becomes

$$-\int_{V_0} \Delta S_{ij} \ddot{E}_{ij} \, dV_0 = -\sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \, dV_0 - \sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) \, dV_0 \tag{90}$$

where, using eqn (38)

$$-\sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) \, dV_0 = -\frac{1}{2} \int_{V_0} \Delta S_{ij} A_{ij} \, dV_0. \tag{90'}$$

Then the difference  $\Delta\Phi^L$  of eqn (88) becomes

$$\Delta\Phi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \ddot{u}_i \Delta \ddot{u}_i \, dV_0 - \sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \, dV_0. \tag{91}$$

In the plastic region (where  $\varphi_x = 0$ ,  $\dot{\lambda}_x \geq 0$ ,  $\varphi_x \dot{\lambda}_x = 0$ ), from condition (82)<sub>2</sub> and (30), it can be stated that

$$-\sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \, dV_0 = \sum_x \int_{V_0} (N_{xij}^S S_{ij} - k_x) \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0 = \sum_x \int_{V_0} \varphi_x \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0 = 0.$$

In the remaining region (where  $\dot{\lambda}_x = 0$ ), from the condition

$$\varphi_x \dot{\lambda}_x = (N_{xij}^S S_{ij} - k_x) \dot{\lambda}_x = 0$$

we can rewrite the last term of eqn (91) in the form

$$-\sum_x \int_{V_0} \Delta S_{ij} \dot{\lambda}_x \frac{\rho_0}{\rho} N_{xij}^S \, dV_0 = -\sum_x \int_{V_0} (N_{xij}^S S_{ij}^* - k_x) \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0 \tag{92}$$

which will never be negative on account of condition (82)<sub>4</sub> and of the nonnegativity of  $\dot{\lambda}_x$  in  $V_{R0}$  stated in eqn (43).

This will be equal to zero if and only if

$$N_{xij}^S S_{ij}^* - k_x = 0 \quad \text{where } \dot{\lambda}_x > 0. \tag{93}$$

This proves that

$$\Phi^L(S_{ij}^*, \ddot{u}_i^*) \geq \Phi^L(S_{ij}, \ddot{u}_i)$$

for any stress  $S_{ij}^*$  and acceleration  $\ddot{u}_i^*$  satisfying conditions (82), the equality sign holding if, and only if, the accelerations  $\ddot{u}_i^*$  satisfy eqn (89) and the stresses  $S_{ij}^*$  satisfy eqn (93). This proves the theorem.

It follows from the above proof that the actual acceleration field  $\ddot{u}_i$  is univocally defined; on the contrary, the actual stress field  $S_{ij}$  may not be univocally determined because

the only limitations that we must respect are

$$\begin{aligned}
 N_{xij}^S S_{ij}^* - k_x &= 0 & \text{in } V_{P0} \\
 N_{xij}^S S_{ij}^* - k_x &= 0 & \text{if } \dot{\lambda}_x > 0 & \text{in } V_{R0} \\
 N_{xij}^S S_{ij}^* - k_x &\leq 0 & \text{if } \dot{\lambda}_x = 0 & \text{in } V_{R0}
 \end{aligned}
 \tag{94}$$

which may not always be sufficient to determine  $S_{ij}$  univocally.

Finally it is easy to show that the statement of the present theorem could have been obtained starting from the corresponding Eulerian formulation (54), (55) and using the formal relationships (see Appendix) between the variables of the Eulerian and Lagrangian approach.

A theorem corresponding to Theorem II but involving quantities relevant to the Lagrangian approach can be derived by a similar proof, starting from the following statement.

*The functional*

$$\Psi^L(\ddot{u}_i^*, \dot{\lambda}_x) = \frac{1}{2} \int_{V_0} \rho_0 \ddot{u}_i^* \ddot{u}_i^* dV_0 - \int_{V_0} \rho_0 F_0 \ddot{u}_i^* dV_0 - \int_{S_{T0}} T_0 \ddot{u}_i^* dS_{T0} + \sum_x \int_{V_0} k_x \dot{\lambda}_x^* \frac{\rho_0}{\rho} dV_0
 \tag{95}$$

defined for all plastic multiplier accelerations  $\dot{\lambda}_x^*$  and accelerations  $\ddot{u}_i^*$  satisfying conditions

$$\begin{aligned}
 \ddot{u}_i^* &= \ddot{U}_i & \text{on } S_{u0} \\
 \dot{E}_{ij}^* &= \sum_x \dot{\lambda}_x \left( \frac{\rho_0}{\rho} N_{xij}^S \right) + \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) & \text{in } V_0 \\
 \dot{\lambda}_x^* &\geq 0 & \text{in } V_{R0}
 \end{aligned}
 \tag{96}$$

attains an absolute minimum for the actual accelerations  $\ddot{u}_i$  and plastic multiplier accelerations  $\dot{\lambda}_x$ ,  $V_{R0}$  being the rigid region referred to the initial configuration.

Again, the point to be proved is that the difference

$$\Delta\Psi^L = \Psi^L(\ddot{u}_i^*, \dot{\lambda}_x^*) - \Psi^L(\ddot{u}_i, \dot{\lambda}_x)$$

is always nonnegative for any arbitrary  $\dot{\lambda}_x^*, \ddot{u}_i^*$  satisfying conditions (96). Assuming position (71), the above difference becomes

$$\begin{aligned}
 \Delta\Psi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta\ddot{u}_i \Delta\ddot{u}_i dV_0 + \int_{V_0} \rho_0 \ddot{u}_i \Delta\ddot{u}_i dV_0 - \int_{V_0} \rho_0 F_0 \Delta\ddot{u}_i dV_0 \\
 - \int_{S_{T0}} T_0 \Delta\ddot{u}_i dS_{T0} + \sum_x \int_{V_0} k_x \Delta\dot{\lambda}_x^* \frac{\rho_0}{\rho} dV_0.
 \end{aligned}
 \tag{97}$$

Using the equilibrium equations, eqns (52), and Gauss's theorem we obtain

$$\begin{aligned} \int_{V_0} \rho_0 \ddot{u}_i \Delta \ddot{u}_i \, dV_0 &= \int_{V_0} \left( S_{jk} \frac{\partial x_i}{\partial a_k} \right) \Delta \ddot{u}_i \, dV_0 + \int_{V_0} \rho_0 F_{0i} \Delta \ddot{u}_i \, dV_0 \\ &= \int_{S_{T0}} T_{0i} \Delta \ddot{u}_i \, dS_{T0} - \int_{V_0} S_{jk} \frac{\partial x_i}{\partial a_k} \Delta \ddot{u}_{i,j} \, dV_0 + \int_{V_0} \rho_0 F_{0i} \Delta \ddot{u}_i \, dV_0 \end{aligned} \quad (98)$$

and then the difference  $\Delta\Psi^L$  reduces

$$\Delta\Psi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \ddot{u}_i \Delta \ddot{u}_i \, dV_0 - \int_{V_0} S_{jk} \frac{\partial x_i}{\partial a_k} \Delta \ddot{u}_{i,j} \, dV_0 + \sum_x \int_{V_0} k_x \Delta \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0. \quad (99)$$

The symmetry of the Kirchhoff stress tensor  $S_{jk}$ , the use of eqns (A3) and (53), make it possible to write the second integral of eqn (99) in the form

$$\begin{aligned} - \int_{V_0} S_{jk} \left( \frac{\partial x_i}{\partial a_k} \Delta \ddot{u}_{i,j} \right) \, dV_0 &= - \frac{1}{2} \int_{V_0} S_{jk} \left[ \frac{\partial x_i}{\partial a_k} \Delta \ddot{u}_{i,j} + \frac{\partial x_i}{\partial a_j} \Delta \ddot{u}_{i,k} \right] \, dV_0 \\ &= - \frac{1}{2} \int_{V_0} S_{jk} [\Delta \ddot{u}_{k,j} + \Delta \ddot{u}_{i,j} u_{i,k} + \Delta \ddot{u}_{j,k} + \Delta u_{i,k} u_{i,j}] \, dV_0 \\ &= - \int_{V_0} S_{jk} \Delta \dot{E}_{jk} \, dV_0 \end{aligned} \quad (100)$$

then

$$\Delta\Psi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \ddot{u}_i \Delta \ddot{u}_i \, dV_0 - \int_{V_0} S_{jk} \Delta \dot{E}_{jk} \, dV_0 + \sum_x \int_{V_0} k_x \Delta \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0 \quad (101)$$

which using condition (96)<sub>2</sub> is transformed into

$$\Delta\Psi^L = \frac{1}{2} \int_{V_0} \rho_0 \Delta \ddot{u}_i \Delta \ddot{u}_i \, dV_0 - \sum_x \int_{V_0} (N_{x,jk}^S S_{jk} - k_x) \Delta \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0. \quad (102)$$

The first integral of eqn (102) is always positive and equal to zero if and only if

$$\ddot{u}_j^* = \ddot{u}_j \quad \text{in } V_0. \quad (103)$$

The second integral, in the region  $V_{P0}$ , vanishes because  $\varphi_x = 0$ ; in the remaining region  $V_{R0}$ , by virtue of the condition

$$\varphi_x \dot{\lambda}_x^* = (N_{xij}^S S_{ij} - k_x) \dot{\lambda}_x^* = 0$$

the term reduces to

$$- \sum_x \int_{V_0} (N_{x,jk}^S S_{jk} - k_x) \Delta \dot{\lambda}_x \frac{\rho_0}{\rho} \, dV_0 = - \sum_x \int_{V_0} (N_{x,jk}^S S_{jk} - k_x) \dot{\lambda}_x^* \frac{\rho_0}{\rho} \, dV_0 \quad (104)$$

which is always nonnegative for every non-vanishing  $\dot{\lambda}_x^*$  as a consequence of condition (96)<sub>3</sub> and because  $\varphi_x \leq 0$ , and is zero if and only if

$$\dot{\lambda}_x^* = 0 \quad \text{where } N_{xij}^S S_{ij}^* - k_x < 0 \quad \text{in } V_{R0}. \quad (105)$$

This proves that



$$\Psi^L(\ddot{u}_i^*, \dot{\lambda}_x^*) \geq \Psi^L(\ddot{u}_i, \dot{\lambda}_x)$$

for every acceleration  $\ddot{u}_i^*$  and plastic multiplier acceleration  $\dot{\lambda}_x^*$  satisfying conditions (96), the equality sign holding if and only if eqns (103) and (105) are satisfied.

This proves the theorem. Again it follows from this proof that the actual acceleration field  $\ddot{u}_i$  is univocally defined; on the contrary, the actual plastic multiplier accelerations  $\dot{\lambda}_x$  may not be determined (even for non-vanishing hardening coefficients  $H_{x\beta}$ ) because the only limitations that  $\dot{\lambda}_x^*$  must satisfy are

$$\begin{aligned} \ddot{E}_{ij}^* &= \sum_x \dot{\lambda}_x^* \left( \frac{\rho_0}{\rho} N_{xij}^S \right) + \sum_x \dot{\lambda}_x \frac{d}{dt} \left( \frac{\rho_0}{\rho} N_{xij}^S \right) \\ \dot{\lambda}_x^* &\leq 0 \quad \text{if } N_{xij}^S S_{ij} - k_x = 0 \quad \text{in } V_{R0} \\ \dot{\lambda}_x^* &= 0 \quad \text{if } N_{xij}^S S_{ij} - k_x < 0 \quad \text{in } V_{R0} \end{aligned} \tag{106}$$

which may not always be sufficient to determine  $S_{ij}$  univocally.

For this theorem too, finally it is easy to show that the statement of the theorem could have been obtained starting from the corresponding Eulerian theorem formulation (95), (96) and using the formal relationship (see Appendix) between the variables of the Eulerian and Lagrangian approach.

### 5. LINKS WITH PREVIOUS THEOREMS

The theorem of Stolarsky and Belytschko[3] and the less recent theorems of Capurso[2] appear to be different forms of Theorem II and special cases of both theorems, respectively.

Stolarsky and Belytschko's theorem corresponds to Theorem II of the Eulerian approach when the functional dependence from the variable  $\dot{\lambda}_x^*$  and the relevant conditions are implicitly expressed in the functional. This may be obtained by defining as kinematically admissible the fields  $\sigma_{ij}^*$ ,  $\ddot{u}_i^*$  satisfying the following conditions:

- (a)  $\ddot{u}_i^*$  satisfies the boundary conditions (eqn (69)<sub>1</sub>);
- (b)  $\sigma_{ij}$  are consistent with the relevant field  $D_{ij}$ , eqn (26) in  $V_p$ . In  $V_R$  they correspond to  $D_{ij}^{0*}$  through eqn (28) where  $D_{ij}^{0*}$  is given by eqn (18)  $\ddot{u}_i$  being replaced by  $\ddot{u}_i^*$  and respecting limitations (29) with  $\dot{\lambda}_x = \dot{\lambda}_x^* \geq 0$ .

In other words, the stresses  $\sigma_{ij}^*$  ( $\ddot{u}_i^*$ ) corresponding to kinematically admissible accelerations  $\ddot{u}_i^*$  are defined both in the region  $V_p$  and (although not univocally) in the region  $V_R$ , by the conditions

$$\begin{aligned} D_{ij}^{0*}(\ddot{u}_i^*) &= N_{xij}^\sigma \dot{\lambda}_x^* \\ N_{xij}^\sigma \sigma_{ij}^*(\ddot{u}_i^*) - k_x &= 0 \quad \text{if } \dot{\lambda}_x^* > 0 \\ N_{xij}^\sigma \sigma_{ij}^*(\ddot{u}_i^*) - k_x &\leq 0 \quad \text{if } \dot{\lambda}_x^* = 0 \end{aligned} \tag{107}$$

where the last two equations can be more concisely expressed as

$$(N_{xij}^\sigma \sigma_{ij}^* - k_x) \dot{\lambda}_x^* = 0. \tag{108}$$

Then, bases on eqns (68) and (69) and using eqns (108) and (107)<sub>1</sub>, Theorem II can be written as follows.

*Among all kinematically admissible fields of accelerations  $\ddot{u}_i^*$ , the solution  $\ddot{u}_i$  minimizes the functional*

$$J(\ddot{u}_i^*) = \frac{1}{2} \int_V \rho \ddot{u}_i^* \ddot{u}_i^* \, dV - \int_V \rho F_j \ddot{u}_j^* \, dV - \int_{S_T} T_j \ddot{u}_j^* \, dS_T + \int_V \sigma_{ij}^*(\ddot{u}_i^*) D_{ij}^{0*}(\ddot{u}_i^*) \, dV. \tag{109}$$

This is Stolarsky and Belytschko's theorem[3], which, however, in the last integral of eqn

(109), loses the quadratic form of the functional, typical of the above Theorems I and II, when the yield surface is generally convex (not necessarily piecewise linear) and  $N_{\alpha j}^*$  and  $k_\alpha$  are suitable functions of  $\sigma_{ij}$ .

Finally, the particularization of Theorems I and II of the Lagrangian approach to the case of small strain-finite displacement theory quite naturally leads to Capurso's theorem[2] when considering that the new configuration of an original infinitesimal element must coincide with the initial one, except for a rigid body motion of any amplitude which has taken place, i.e.

$$\begin{aligned} \rho &\simeq \rho_0, & dV &\simeq dV_0 \\ \frac{\partial a_i}{\partial x_k} &\simeq \frac{\partial x_k}{\partial a_i} = F_{ki} \\ F_{ij} &= R_{ih} U_{hj} \simeq R_{ij} \\ \dot{E}_{ij} &= F_{mi} D_{mn} F_{nj} \simeq R_{mi} D_{mn} R_{nj}. \end{aligned} \quad (110)$$

Besides, in eqn (42) the last term of the second member vanishes as can be shown using the equivalent expression (37'), taking eqns (110) and (8) into account, i.e.

$$\frac{d}{dt} \left( \frac{\partial x_h}{\partial a_i} \frac{\partial x_k}{\partial a_j} R_{hr} R_{ks}} \right) = \frac{d}{dt} (R_{hi} R_{kj} R_{hr} R_{ks}) = \frac{d}{dt} (\delta_{ir} \delta_{js}) = 0 \quad (111)$$

and, then, eqns (40) and (42) of the constitutive laws, reduce to

$$\begin{aligned} \dot{E}_{ij} &= \sum_{\alpha} \dot{\lambda}_{\alpha} N_{\alpha ij}^S \\ \dot{E}_{ij} &= \sum_{\alpha} \dot{\lambda}_{\alpha} N_{\alpha ij}^S, \end{aligned} \quad (112)$$

Using the above positions, Theorems I and II of the Lagrangian approach come to coincide with Capurso's small-strain, large-displacement theorems.

In particular functional (81) written in the form

$$\Phi^I(S_{ij}^*, \ddot{u}_j^*) = \frac{1}{2} \int_{V_0} \rho_0 \ddot{u}_j^* \ddot{u}_j^* dV_0 + \frac{1}{2} \int_{V_0} S_{ij}^* (A_{ij} - 2\dot{u}_{rj} \dot{u}_{rj}) dV_0 - \int_{S_{u0}} x_{k/j} S_{ij}^* n_{0i} \dot{U}_k dS_{u0} \quad (113)$$

transforms itself, taking into account eqn (90'), into

$$\Phi_c(S_{ij}^*, \ddot{u}_j^*) = \frac{1}{2} \int_{V_0} \rho_0 \ddot{u}_j^* \ddot{u}_j^* dV_0 - \int_{V_0} S_{ij}^* \dot{u}_{rj} \dot{u}_{rj} dV_0 - \int_{S_{u0}} x_{k/j} S_{ij}^* n_{0i} \dot{U}_k dS_{u0} \quad (114)$$

which is the functional of Theorem I of Capurso[2].

#### REFERENCES

1. V. P. Tamuzh, On a minimum principle in dynamics of rigid plastic solids. *Prikl. Mat. Mekh.* **26**, 1067-1077 (1962).
2. M. Capurso, On the extremal properties of the solution in dynamics of rigid-viscoplastic bodies allowing for large displacement effects. *Meccanica* **7**(4), 236-247 (1972).
3. H. Stolarsky and T. Belytschko, Large deformation, rigid-plastic dynamics by an extremum principle. *Comp. Meth. Appl. Mech. Engrg* **21**, 217-230 (1980).
4. L. E. Malvern, *Introduction to the Mechanics of a Continuous Medium*. Prentice-Hall, Englewood Cliffs, New Jersey (1969).
5. Y. C. Fung, *Foundations of Solid Mechanics*. Prentice-Hall, Englewood Cliffs, New Jersey (1965).

6. T. Belytschko, Non-linear analysis description and numerical stability. In *Computer Programs in Shock and Vibration* (Edited by W. Pilkey and B. Pilkey), pp. 537-562. The Shock and Vibration Information Center, U.S.A. Department of Defense, Washington, DC (1975).
7. T. Belytschko and T. J. R. Hughes, *Computational Methods in Transient Analysis*. Elsevier, Amsterdam (1983).

APPENDIX

The above widely used relationships between static, kinematic and material behaviour quantities relevant to the Eulerian and Lagrangian approach are summarized here.

Denoting by  $x$ , and  $a$ , the current (at time  $t$ ) and the original (at time  $t = 0$ ) positions of the same material particle, the Eulerian and Lagrangian descriptions of the geometry are based on the relations[4,5]

$$a_i = x_i(t) - u_i[x_i(t), t] \quad (\text{Eulerian}) \tag{A1}$$

$$x_i(t) = a_i + u_i(a_i, t) \quad (\text{Lagrangian}) \tag{A2}$$

implying (if  $\partial/\partial a_i$  is denoted by  $/\bar{j}$ ) the following relations :

$$\begin{aligned} \frac{\partial a_i}{\partial x_j} &= \delta_{ij} - \frac{\partial u_i}{\partial x_j} = \delta_{ij} - u_{ij} \\ \frac{\partial x_i}{\partial a_j} &= \delta_{ij} + \frac{\partial u_i}{\partial a_j} = \delta_{ij} + u_{ij\bar{j}} \end{aligned} \tag{A3}$$

and the following material time derivatives :

$$\frac{d}{dt}(u_i) = \dot{u}_i = \frac{\partial u_i}{\partial t} + u_{i,k} \dot{u}_k \tag{A4}$$

$$\frac{d}{dt} \left( \frac{\partial u_i}{\partial x_j} \right) = \dot{u}_{i,j} - \dot{u}_{k,i} u_{k,j}, \quad \frac{d}{dt} \left( \frac{\partial u_i}{\partial a_j} \right) = \frac{\partial \dot{u}_i}{\partial a_j} \tag{A5}$$

$$\frac{d}{dt} \left( \frac{\partial \dot{u}_i}{\partial x_j} \right) = \ddot{u}_{i,j} - \dot{u}_{k,i} \dot{u}_{k,j}, \quad \frac{d}{dt} \left( \frac{\partial \dot{u}_i}{\partial a_j} \right) = \frac{\partial \ddot{u}_i}{\partial a_j} \tag{A6}$$

Deformations

Almansi  $e_{ij}$  and Green  $E_{ij}$  tensors as well as the deformation gradient  $F_{ij}$  are given and correlated by the following relations :

$$e_{ij} = \frac{1}{2}(u_{ij} + u_{ji} - u_{k,i} u_{k,j}) \tag{A7}$$

$$E_{ij} = \frac{1}{2}(u_{ij\bar{j}} + u_{ji\bar{i}} + u_{k,i} u_{k,j}) \tag{A8}$$

$$F_{ij} = \frac{\partial x_i}{\partial a_j} = \delta_{ij} + \frac{\partial u_i}{\partial a_j} \tag{A9}$$

$$e_{ij} = E_{nk} \frac{\partial a_n}{\partial x_i} \frac{\partial a_k}{\partial x_j}, \quad e_{ij} = \frac{1}{2} \left( F_{jk} - \frac{\partial a_k}{\partial x_j} \right) \frac{\partial a_k}{\partial x_i} \tag{A10}$$

$$E_{ij} = e_{nk} \frac{\partial x_n}{\partial a_i} \frac{\partial x_k}{\partial a_j}, \quad E_{ij} = \frac{1}{2}(F_{ki} F_{kj} - \delta_{ij}) \tag{A11}$$

$$F_{ki} \frac{\partial a_i}{\partial x_k} = 2e_{nk} + \frac{\partial a_i}{\partial x_k} \frac{\partial a_i}{\partial x_k}, \quad F_{ij} = 2E_{jk} \frac{\partial a_k}{\partial x_i} + \frac{\partial a_i}{\partial x_i} \tag{A12}$$

Stress density and forces

The Cauchy  $\sigma_{ij} = \sigma_{ji}$ , Kirchhoff  $S_{ij} = S_{ji}$  and Lagrange  $T_{ij} \neq T_{ji}$  stress tensors are brought into relation by

$$\sigma_{ij} = \frac{\rho}{\rho_0} \frac{\partial x_i}{\partial a_k} \frac{\partial x_j}{\partial a_k} S_{nk}, \quad \sigma_{ij} = \frac{\rho}{\rho_0} \frac{\partial x_j}{\partial a_k} T_{ki} \tag{A13}$$

$$S_{ij} = \frac{\rho_0}{\rho} \frac{\partial a_i}{\partial x_k} \frac{\partial a_j}{\partial x_k} \sigma_{nk}, \quad S_{ij} = T_{nk} \frac{\partial a_i}{\partial x_k} \tag{A14}$$

$$T_{ij} = \frac{\rho_0}{\rho} \frac{\partial a_i}{\partial x_k} \sigma_{kj}, \quad T_{ij} = S_{nk} \frac{\partial x_j}{\partial a_k} \tag{A15}$$

while density and forces are related as follows :

$$\rho_0 dV_0 = \rho dV, \quad F_{0i} = F_i, \quad T_{0i} dS_0 = T_i dS \quad (\text{A16})$$

$$\frac{\partial a_i}{\partial X_k} n_{0k} dS_0 = \frac{\rho}{\rho_0} n_k dS \quad (\text{A16}')$$

where "0" refers to the variable value at time  $t = 0$ .

#### Yield functions

Depending on the chosen stress space, the piecewise-linearized yield surface, is expressed as

$$\begin{aligned} \varphi_s &= N_{si}^s \sigma_{ij} - k_s \leq 0 \\ \varphi_s &= N_{si}^s S_{ij} - k_s \leq 0 \\ \varphi_s &= \hat{N}_{si} \hat{\sigma}_{ij} - k_s \leq 0 \end{aligned} \quad (\text{A17})$$

where  $\hat{\sigma}_{ij}$  are the components of the corotational stress tensor

$$\hat{\sigma}_{ij} = R_{ni} \sigma_{nk} R_{kj} \quad (\text{A18})$$

$R_n$  being a generic rigid body motion.

The relations between the outward normal unit vectors  $N_{si}$  are

$$\hat{N}_{si} = R_{ni} N_{shk}^s R_{kj}, \quad \hat{N}_{si} = \frac{\rho_0}{\rho} \frac{\partial a_i}{\partial X_k} \frac{\partial a_i}{\partial X_k} R_{ni} N_{shk}^s R_{kj} \quad (\text{A19})$$

$$N_{si}^s = R_{ni} \hat{N}_{shk} R_{kj}, \quad N_{si}^s = \frac{\rho_0}{\rho} \frac{\partial a_k}{\partial X_i} \frac{\partial a_k}{\partial X_j} N_{shk}^s \quad (\text{A20})$$

$$N_{si}^s = \frac{\rho}{\rho_0} \frac{\partial X_k}{\partial a_i} \frac{\partial X_k}{\partial a_j} R_{ni} \hat{N}_{shk} R_{kj}, \quad N_{si}^s = \frac{\rho}{\rho_0} \frac{\partial X_k}{\partial a_i} \frac{\partial X_k}{\partial a_j} N_{shk}^s \quad (\text{A21})$$