

DETERMINANTAL EQUATIONS IN STRUCTURAL MECHANICS

THOMAS R. KANE

Division of Applied Mechanics, Durand Building, Stanford University, Stanford, CA 94305, U.S.A.

(Received 31 December 1980)

The following mathematical problem arises frequently in connection with physical problems: Given the elements of a determinant $\Delta(x)$ as functions of a variable x , find real values of x for which $\Delta(x)$ vanishes. Two important examples that come to mind immediately are the determination of natural frequencies of a continuous structure, such as a beam, plate or shell, and the search for eigenvalues of a constant, real, symmetric matrix (where the eigenvalues play the role of x). This Note deals with a simple method for finding x , a method that frees one from having to expand Δ in literal form, which becomes an important consideration when Δ is large.

Let $y(\tau)$ denote a function of a variable τ , let k be any constant, and require that

$$y(0) = k \tag{1}$$

and

$$\Delta[y(\tau)] = (1 - \tau)\Delta(k). \tag{2}$$

Then $y(1)$ satisfies $\Delta[y(1)] = 0$, which means that $y(1)$ is precisely one of the values of x being sought. To find $y(1)$, proceed as follows: Differentiate eqn (2) with respect to τ , solve the resulting equation for $dy/d\tau$, obtaining

$$\frac{dy}{d\tau} = - \frac{\Delta(k)}{\frac{d\Delta}{dy}} \tag{3}$$

and integrate this equation numerically from $\tau = 0$ to $\tau = 1$, using eqn (1) as an initial condition, and assigning to k a value in the vicinity of an expected value of x .

The characteristic equation for a cantilever beam of length L , flexural rigidity EI , and mass per unit of length ρ , which can be written

$$\Delta(x) \triangleq \begin{vmatrix} \sin x + \sinh x & \cos x + \cosh x \\ \cos x + \cosh x & -\sin x + \sinh x \end{vmatrix} = 0 \tag{4}$$

furnishes an illustrative example. Replacing x with y in eqn (4), and differentiating with respect to y , one arrives at

$$\frac{d\Delta}{dy} = \begin{vmatrix} \cos y + \cosh y & -\sin y + \sinh y \\ \cos y + \cosh y & -\sin y + \sinh y \end{vmatrix} + \begin{vmatrix} \sin y + \sinh y & \cos y + \cosh y \\ -\sin y + \sinh y & -\cos y + \cosh y \end{vmatrix} \tag{5}$$

so that, since the first determinant on the right-hand side is equal to zero, substitution from eqns (4) and (5) into eqn (3) yields

$$\frac{dy}{d\tau} = - \frac{\begin{vmatrix} \sin k + \sinh k & \cos k + \cosh k \\ \cos k + \cosh k & -\sin k + \sinh k \end{vmatrix}}{\begin{vmatrix} \sin y + \sinh y & \cos y + \cosh y \\ -\sin y + \sinh y & -\cos y + \cosh y \end{vmatrix}} \tag{6}$$

Table 1.

Line	k	x	$ \Delta(x) $
1	1.00000000	1.87437055	6×10^{-3}
2	1.87437055	1.87584140	6×10^{-3}
3	1.87584140	1.87510652	2×10^{-5}
4	1.87510652	1.87510284	1×10^{-5}
5	1.87510284	1.87510406	$< 10^{-6}$
6	4.00000000	4.69360687	5×10^{-2}
7	4.69360687	4.69461382	5×10^{-2}
8	4.69461382	4.69409282	2×10^{-4}
9	4.69409282	4.69409026	9×10^{-5}
10	4.69409026	4.69409112	$< 10^{-6}$
11	7.00000000	4.70582236	1
12	4.70582236	4.68123089	1
13	4.68123089	4.69405020	4×10^{-3}
14	4.69405020	4.69411222	2×10^{-3}
15	4.69411222	4.69409124	9×10^{-6}
16	4.69409124	4.69409111	$< 10^{-6}$
17	11.00000000	10.9955517	6×10^{-1}
18	10.9955517	10.9955348	3×10^{-1}
19	10.9955348	10.9955391	$< 10^{-6}$

Numerical integration of this equation, from $\tau = 0$ to $\tau = 1$, with $y(0) = k$, leads to the values recorded in Table 1.

The values of k listed in lines 1, 6, 11 and 17 were chosen arbitrarily, whereas each of the remaining k 's is simply equal to the x on the preceding line, a choice that can be automated easily and that leads to good results rather quickly, as is apparent from the associated rapid decreases in $|\Delta(x)|$. The fact that many choices of k can lead to the same value of x (see lines 6 and 11 for k and lines 10 and 16 for the corresponding values of x) means that one need not possess great prescience to make a suitable choice for k . Moreover, in order to find a particular root of $\Delta(x) = 0$, one does not need to use the method more than once. The accuracy of the result one obtains from a single application of the method depends both on the proximity of k to the root in question and on the quality of the integration algorithm being employed. (The results in Table 1 were generated with a rather crude integrator on a desktop computer.)

The ideas underlying the method here set forth are the same as those employed in [1] to solve sets of nonlinear equations. They have been employed also by Shippy[2] to find eigenvalues and eigenvectors.

REFERENCES

1. T. R. Kane, Real solutions of sets of nonlinear equations. *AIAA J.* 4(10), 1880-1881 (1966).
2. D. J. Shippy, Matrix eigenvalues by numerical integration. *AIAA J.* 7(3), 531 (1969).