



## Letter to the Editor

### Comment on “comparison of two-stage sorption design models for the removal of lead ions by polyvinyl-modified Kaolinite clay”

Unuabonah et al. published the paper “comparison of two-stage sorption design models for the removal of lead ions by polyvinyl-modified Kaolinite clay” [1]. In Section 2.4. “Adsorption kinetic models” the authors used Eqs. (2)–(4) in the paper. In 1998, the pseudo-second order kinetic expression for the adsorption of dyes [2,3], metals [2,4], and organic substances [4] were reported by Ho and McKay. In order to distinguish kinetics equation based on adsorption capacity of solid from one based on the concentration of solution. The second order rate expression has been called pseudo-second order [2–4]. Furthermore, the kinetic expression has also been applied to a multi-stage batch adsorption design [5,6], and pseudo-isotherm studies [7,8]. It is clear that Unuabonah et al. used the idea of figures, tables, and equations from the papers entitled “a two-stage batch sorption optimised design for dye removal to minimum contact time” [5] and “a multi-stage batch sorption design with experimental data” [6]. In addition, similar comment has also been reported in *Biochemical Engineering Journal* [9].

In my view, Unuabonah et al. should have cited the original paper for the kinetic model and equations for two-stage batch sorption design as well as thereby provided greater accuracy and information details about the idea they employed.

### References

- [1] E.I. Unuabonah, B.I. Olu-Owolabi, D. Okoro, K.O. Adebawale, Comparison of two-stage sorption design models for the removal of lead ions by polyvinyl-modified Kaolinite clay, *J. Hazard. Mater.* 171 (2009) 215–221.
- [2] Y.S. Ho, G. McKay, A comparison of chemisorption kinetic models applied to pollutant removal on various sorbents, *Process Safety Environ. Protect.* 76 (1998) 332–340.
- [3] Y.S. Ho, G. McKay, Sorption of dye from aqueous solution by peat, *Chem. Eng. J.* 70 (1998) 115–124.
- [4] Y.S. Ho, G. McKay, Kinetic model for lead(II) sorption on to peat, *Adsorpt. Sci. Technol.* 16 (1998) 243–255.
- [5] Y.S. Ho, G. McKay, A two-stage batch sorption optimised design for dye removal to minimum contact time, *Process Safety Environ. Protect.* 76 (1998) 313–318.
- [6] Y.S. Ho, G. McKay, A multi-stage batch sorption design with experimental data, *Adsorpt. Sci. Technol.* 17 (1999) 233–243.
- [7] Y.S. Ho, C.C. Wang, Pseudo-isotherms for the sorption of cadmium ion onto tree fern, *Process Biochem.* 39 (2004) 759–763.
- [8] Y.S. Ho, Pseudo-isotherms using a second order kinetic expression constant, *Adsorpt.-J. Int. Adsorpt. Soc.* 10 (2004) 151–158.
- [9] Y.S. Ho, Comment on “Two-stage batch sorber design using second-order kinetic model for the sorption of metal complex dyes onto pine sawdust” by Özacar, M. and Şengül, İ.A., *Biochem. Eng. J.* 23 (2005) 291–292.

Yuh-Shan Ho\*

Water Research Centre, Asia University, Taichung  
41354, Taiwan

\* Tel.: +866 4 2332 3456x1797;  
fax: +866 4 2330 5834.  
E-mail address: [ysho@asia.edu.tw](mailto:ysho@asia.edu.tw)

21 September 2011  
Available online 1 October 2011