

|   |      |
|---|------|
| T. SAKAI and M. IWATA   | 1659 |
| Effect of oxygen on sintering of AlN  |      |
| K. G. HOGE and A. K. MUKHERJEE  | 1666 |
| The temperature and strain rate dependence of the flow stress of tantalum   |      |
| M. R. ARORA and R. KELLY  | 1673 |
| The structure and stoichiometry of anodic films on V, Nb, Ta, Mo and W  |      |
| <b>Letters</b>  |      |
| V. A. NIEBERLEIN and B. STEVERDING  | 1685 |
| Thermal conductivity of epoxy-aluminium powder mixtures   |      |
| W. J. TOMLINSON and D. STAPLEY  | 1689 |
| Thermal conductivity of epoxy resin-aluminium (0 to 50%) composites   |      |
| J. HAUCK  | 1690 |
| Divalent chromium in alkaline earth silicate systems  |      |
| J. VEGA-BOGGIO, J.-Å. SCHWEITZ and O. VINGSBO   | 1692 |
| Surface energy measurements from Griffith cracks in boron fibres  |      |
| R. P. KUSY, H. B. LEE and D. T. TURNER  | 1694 |
| Influence of temperature on the fracture rib spacing of poly(methyl methacrylate)   |      |
| B. A. NEWMAN, K. D. PAE and T. P. SHAM  | 1697 |
| High pressure X-ray studies of polymers. II. Variation of pressure with temperature in the diamond-anvil cell                   |      |
| M. I. de VRIES and A. MASTENBROEK   | 1700 |
| Analyses of faceted fracture surfaces of fatigue-tested type 304 stainless steel by means of selected area channelling patterns |      |
| U. DOMINGUEZ and F. GUIU  | 1703 |
| A method for measuring cyclic microstrains in both tension and compression  |      |
| G. T. STEVENS and A. W. LUPTON  | 1706 |
| Some factors controlling transverse cracking in cross-plyed composites  |      |
| T. O. CRAIG   | 1709 |
| Comments on "Thermal stresses in rubber-modified glassy polymers"   |      |
| A. PAVAN and T. RICCÒ   | 1709 |
| Reply to "Comments on 'Thermal stresses in rubber-modified glassy polymers'"  |      |
| <b>Erratum</b>  | 1711 |

### Errata

- L. A. GYPEN and A. DERUYTTERE, *J. Mater. Sci.* **12** (1977) 1028.  
p. 1028; The footnote should end . . . interaction widths  $w_v \cdot G$  is the solution of the appropriate Green's function.  
p. 1029; The equations in the third column of Table I should be numbered 5 to 14 respectively. A correct version of this table is to be found on p. 1711.  
p. 1031; In Equation 35  $m_1$  should read  $m_2$ .  
p. 1032; In the equation at the foot of Column 2, the power 9 should read  $q$ .

---

Technical articles of full page length, or over, appearing in *Journal of Materials Science* are indexed in *British Technology Index*, *Current Contents*, *Science Citation Index (USA)*, and *Engineering Index*. *Journal of Materials Science* is also used by *Chemical Abstracts*, *Metals Abstracts*, and *Physics Abstracts*.

---

© 1977 Chapman and Hall Ltd. Typeset by the Alden Press Ltd., London and Northampton, and printed in Great Britain by Whitstable Litho Ltd., Whitstable, Kent.