

| | |
|--|------|
| M. J. OWEN and J. R. GRIFFITHS | 1521 |
| Evaluation of biaxial stress failure surfaces for a glass fabric reinforced polyester resin under static and fatigue loading | |
| J. van den BOOMGAARD and R. A. J. BORN | 1538 |
| A sintered magnetoelectric composite material $\text{BaTiO}_3\text{--Ni(Co, Mn) Fe}_2\text{O}_4$ | |
| S. C. AGARWAL and H. HERMAN | 1549 |
| Early-stage phase separation in liquid-quenched Al-7 at % Zn | |
| M. J. MARCINKOWSKI | 1555 |
| Differential geometry of phase transformations | |
| M. SAHOO, D. BARAGAR and R. W. SMITH | 1565 |
| Compressive properties of the unidirectionally solidified Sb-Ge eutectic | |
| J. D. VERHOEVEN and E. D. GIBSON | 1576 |
| The monotectic reaction in Cu-Nb alloys | |
| Letters | |
| P. R. HOWELL and J. V. BEE | 1583 |
| On the interaction of annealing twins in fcc metals and alloys | |
| T. CHIVERS, E. GILMOUR and R. A. KYDD | 1585 |
| Vibrational spectra of sulphur-doped borate glasses | |
| W. ZDANOWICS, T. ULIASZ, J. JURUSIK and J. SZNAJDER | 1588 |
| Domain structure of amorphous Nd-Co thin films | |
| S. C. DANFORTH, H. M. JENNINGS and M. H. RICHMAN | 1590 |
| Strength versus nitrided density and microstructural design of reaction-bonded silicon nitride | |
| H. G. SCOTT | 1592 |
| On the continuous transition between two structure types in the zirconia-gadolinia system | |
| C. A. KAGARAKIS | 1594 |
| Chemical bonding in bismuth telluride | |
| N. G. McCRUM | 1596 |
| The prediction of creep at long times in polymeric solids | |
| V. SCHMIDT and J. HOPFE | 1599 |
| Observation of Dugdale cracks in glass foils — a method for studying surface plasticity of soda-lime glass | |
| S. N. GHOSH, A. K. PAUL and A. K. THAKUR | 1602 |
| Thermal decomposition of CaCO_3 and formation of $\beta\text{-Ca}_2\text{SiO}_4$ | |
| F. P. BAILEY and K. J. T. BLACK | 1606 |
| The effect of ambient atmosphere on the gold-to-alumina solid state reaction bond | |
| Erratum | |
| | 1609 |

Corrigenda

- N. KAMIYA and O. KAMIGAITO, *J. Mater. Sci.* 13 (1978) 212.
 p. 214, Column 1, line 5 from the bottom: 40 should read 60.
 Column 2, Reference 5: NESSLEA should read NESSLER.
 Column 2, line 6 from the bottom: NOBOU should read NOBUO.

Technical articles of full page length, or over, appearing in *Journal of Materials Science* are indexed in *British Technology Index*, *Current Contents*, *Science Citation Index (USA)*, and *Engineering Index*. *Journal of Materials Science* is also used by *Chemical Abstracts*, *Metal Abstracts*, and *Physics Abstracts*.
