

5530168

**PROCESS FOR THE SYNTHESIS OF A
C₂+ ALIPHATIC ALCOHOL IN A
SLURRY REACTOR COMPRISING AN
IN-SITU CATALYST IMPREGNATION
STEP**

Underwood Richard P; Toseland Bernard A; Dahl Thomas A; Hugo Janet F Allentown, PA, UNITED STATES assigned to Air Products and Chemicals Inc

A process is set forth for the synthesis of a C₂+ aliphatic alcohol from hydrogen and carbon oxides in the presence of a copper-based catalyst which has been impregnated with an alkali metal compound. The process differs from the prior art in that the catalyst is impregnated with the alkali metal compound in the same slurry reactor which is used for reacting the hydrogen and carbon oxides. By contrast, in the prior art C₂+ aliphatic alcohol synthesis, impregnation of the copper-based catalyst with the alkali metal compound is accomplished by a separate step in a separate vessel. By eliminating this separate step, the present invention realizes a savings in processing and equipment costs.

5530171

**PROCESS FOR THE CATALYTIC
DEHYDROGENATION OF ALKANES
TO ALKENES WITH SIMULTANEOUS
COMBUSTION OF HYDROGEN**

Agaskar Pradyot A; Grasselli Robert K; Michaels James; Reischman P Thomas; Stern David L; Tsikoyiannis John G Lawrenceville, NJ, UNITED STATES assigned to Mobil Oil Corporation

There is provided a process for the net catalytic oxidative dehydrogenation of alkanes to produce

alkenes. The process involves simultaneous equilibrium dehydrogenation of alkanes to alkenes and combustion of the hydrogen formed to drive the equilibrium dehydrogenation reaction further to the product alkenes. In the present reaction, the alkane feed is passed into a reactor containing both an equilibrium dehydrogenation catalyst and a reducible metal oxide, whereby the alkane is dehydrogenated and the hydrogen produced is simultaneously and selectively combusted in oxidation/reduction (REDOX) reaction with the reducible metal oxide. This particular mode of operation is termed a same reactor, REDOX mode. The equilibrium dehydrogenation catalyst may comprise platinum and the reducible metal oxide may contain bismuth, antimony, indium, or molybdenum, or a mixture thereof.

5532198

**ZIRCONIUM/CERIUM MIXED OXIDE
CATALYST/CATALYST SUPPORT
COMPOSITIONS HAVING
HIGH/STABLE SPECIFIC SURFACES**

Chopin Thierry; Vilmin Gabriel Saint Denis, NJ, FRANCE assigned to Rhone-Poulenc Chimie

Zirconium/cerium mixed oxides (optionally including thermally stabilizing dopant values), comprising solid solutions thereof, having contents of zirconium of up to 99% by weight, and having high specific surface areas, are well suited as catalysts and/or catalyst supports, notably for the treatment/conversion of vehicular exhaust gases; such ZrO₂/CeO₂ mixed oxides are conveniently prepared by (i) intimately admixing a zirconium sol with a cerium sol, the ratio r of the mean diameter r_1 of the particles of the zirconium sol to the diameter r_2 of the particles of the cerium sol being at least 5, (ii) spray drying the admixture thus obtained, and (iii) calcining the dried material.