

Deterministic microscopic three-phase traffic flow models

This article has been downloaded from IOPscience. Please scroll down to see the full text article.

2006 J. Phys. A: Math. Gen. 39 7605

(<http://iopscience.iop.org/0305-4470/39/23/C01>)

View [the table of contents for this issue](#), or go to the [journal homepage](#) for more

Download details:

IP Address: 171.66.16.105

The article was downloaded on 03/06/2010 at 04:37

Please note that [terms and conditions apply](#).

Corrigendum

Deterministic microscopic three-phase traffic flow models

B S Kerner and S L Klenov 2006 *J. Phys. A: Math. Gen.* **39** 1775–1809

In the last sentence of section 2.3 the words ‘steady state of’ should be omitted.

In formula (21) the value of $\tilde{a}^{(\text{phase})}$ should be replaced by $\max(\tilde{a}^{(\text{phase})}, a_{\min})$.

In formulae (23) and (24) the value of $\tilde{a}^{(\text{phase})}$ should be replaced by $a^{(\text{phase})}$.

In table 1, the formulae

$$V^{(\text{free})}(g) = V(g) \quad \text{at } g \geq g_{\min}^{(\text{free})}$$

$$V_{\max}^{(\text{syn})}(g) = V(g) \quad \text{at } g < g_{\min}^{(\text{free})}$$

should be replaced respectively by

$$V^{(\text{free})}(g) = V(g)$$

$$V_{\max}^{(\text{syn})}(g) = V(g).$$