

## SUBJECT INDEX

---

- Anatase titanium dioxide  
 electrochemistry of, in lithium non-aqueous cells, 153
- Barium cerate  
 oxygen ion conduction in pure and yttria-doped, 295
- Batteries  
 lithium  
 ageing of rechargeable, 57  
 electrolyte solutions for, properties and structures of, 39  
 for extended-life continuous-operation applications, preliminary evaluation of, 167  
 general discussion, Second International Meeting on, Paris, April 27, 1984, 259  
 high specific surface area graphitic oxide as cathode material for, 99  
 metal sulphides as cathodes in primary, electrochemical behavior of, 65  
 -molybdenum disulfide, rate limiting mechanisms in, 201  
 polyacetylene electrodes for non-aqueous, 3  
 primary, in Europe, an industrial and commercial fact, 251  
 U S A , an assessment, 247  
 liquid cathode primary, 111  
 polymer electrolyte, behavior of, at 80 - 100 °C and near room temperature, 23
- Battery applications  
 solid lithium ion conductors for, 105
- Battery electrode  
 lead-acid  
 effect of additives on the positive, 305  
 thermopassivation of the positive, Part 3 Thermopassivation of smooth PbO<sub>2</sub> electrodes, 277
- Battery technology  
 lithium, in Japan, the trend of, 255  
 secondary lithium, recent developments in, 179
- Cadmium  
 protection of sealed Ni-Cd cells from cell voltage reversal, 285
- Calcium  
 calcium/Ca(AlCl<sub>4</sub>)<sub>2</sub>-thionyl chloride (TC) cell, effect of temperature and cell parameters on performance, 93
- Carbon electrodes  
 the a c response of porous, in thionyl chloride solutions, 123
- Cathode(s)  
 chromium oxide as a, for lithium organic solvent cells, characteristics of amorphous, 215  
 liquid, primary batteries, 111  
 metal sulphides as, in primary lithium batteries, electrochemical behaviour of, 65
- Cathode material  
 graphitic oxide as, for lithium batteries, high specific surface area, 99  
 V<sub>6</sub>O<sub>13</sub> as, for lithium cells, 235
- Cationic transport numbers  
 in polyether-based networks containing lithium salts, 27
- Cell(s)  
 calcium/Ca(AlCl<sub>4</sub>)<sub>2</sub>-thionyl chloride (TC), effect of temperature and cell parameters on performance, 93  
 lithium, elective replacement indicator for implantable, 83  
 Li/CuO, electrochemical behavior of CuO in a, influence of preparation conditions on, 269  
 lithium-iodine, improvement in discharge rate and low temperature characteristics of, 167  
 lithium nonaqueous, electrochemistry of anatase titanium dioxide in, 153  
 lithium organic solvent, characteristics of amorphous chromium oxide as a cathode for, 215  
 lithium-vanadium pentoxide, an improved, and comparison with a lithium-thionyl chloride cell, 135  
 lithium, V<sub>6</sub>O<sub>13</sub> as cathode material for, 235

- Ni-Cd, protection of sealed, from cell voltage reversal, 285
- secondary lithium, capacity-cycle life behavior in, 53
- Cell voltage reversal
  - protection of sealed Ni-Cd cells from, 285
- Chromium
  - layered  $\text{AMO}_2$  compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of the deintercalation of, 231
- Chromium oxide
  - as a cathode for lithium organic solvent cells, characteristics of amorphous, 215
- Cobalt
  - layered  $\text{AMO}_2$  compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of the deintercalation of, 231
- Conductive polymers
  - new tools and materials for electrochemistry, 11
- Continuous-operation
  - lithium batteries for extended-life, applications, preliminary evaluation of, 167
- Copper
  - $\text{Li}/\text{CuO}$  cell, electrochemical behavior of CuO in a, influence of preparation conditions on, 269
- Cycle life
  - capacity-, behaviour in secondary lithium cells, 53
- Deintercalation
  - of layered  $\text{AMO}_2$  compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of, 231
- Discharge rate
  - and low temperature characteristics of lithium-iodine cells, improvement in, 173
- Elective replacement indicator
  - for implantable lithium cells, 83
- Electrochemical aspects
  - of the deintercalation of layered  $\text{AMO}_2$  compounds (A = Li or Na, M = Cr, Co or Fe), 231
- Electrochemical behavior
  - of CuO in a  $\text{Li}/\text{CuO}$  cell, influence of preparation conditions on, 269
  - of graphite intercalated by fluorine, 149
  - of metal sulphides as cathodes in primary lithium batteries, 65
  - of polysulfides in tetrahydrofuran, 129
- Electrochemical cells
  - thermal behaviour of, by liquid crystal display, 321
- Electrochemical characteristics
  - of polyacetylene in organic electrolytes, 31
- Electrochemical insertion
  - of lithium in manganese dioxide, 141
- Electrochemical reaction
  - between lithium and phthalocyanine, kinetic studies of, 71
- Electrochemistry
  - of anatase titanium dioxide in lithium nonaqueous cells, 153
  - conductive polymers, new tools and materials for, 11
- Electrode(s)
  - the a c response of lithium, stainless steel, and porous carbon, in thionyl chloride solutions, 123
  - lithium, passivating films on, an approach by means of electrode impedance spectroscopy, 45
  - $\text{PbO}_2$ , thermopassivation of smooth, 277
  - polyacetylene, for non-aqueous lithium batteries, 3
  - positive lead-acid battery, effect of additives on, 305
  - theoretical study of a composite, using an intercalation compound, influence of the particle size distribution on the depth of discharge, 209
- Electrode contaminations
  - cycling of  $\beta\text{-LiAl}$  in organic electrolytes, effect of, and electrolyte additives, 193
- Electrode impedance spectroscopy
  - passivating films on lithium electrodes, an approach by means of, 45
- Electrolyte(s)
  - cycling of  $\beta\text{-LiAl}$  in organic, effect of electrode contaminations and electrolyte additives, 193
  - lithium borophosphate vitreous, 87
  - polyacetylene in organic, electrochemical characteristics of, 31
  - poly(ethylene oxide), for operation at near room temperature, 13
- Electrolyte batteries
  - behavior of polymer, at 80 - 100 °C and near room temperature, 23

- Electrolyte solution(s)  
 aprotic organic, cycling behaviour of molybdenum dichalcogenides in, 223  
 for lithium batteries properties and structures of, 39
- Fluorine  
 electrochemical behavior of graphite intercalated by, 149
- Graphite  
 intercalated by fluorine, electrochemical behavior of, 149
- Graphitic oxide  
 as cathode material for lithium batteries, high specific surface area, 99
- Intercalation compound  
 theoretical study of a composite electrode using an, influence of the particle size distribution on the depth of discharge, 209
- Iodine  
 lithium-, cells, improvement in discharge rate and low temperature characteristics of, 173
- Ion conductors  
 solid lithium, for battery applications, 105
- Iron  
 layered AMO<sub>2</sub> compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of the deintercalation of, 231
- Lead-acid battery electrode  
 effect of additives on the positive, 305  
 thermopassivation of the positive, Part 3 Thermopassivation of smooth PbO<sub>2</sub> electrodes, 277
- Lead electrodes  
 thermopassivation of smooth PbO<sub>2</sub> electrodes, 277
- Liquid crystal display  
 thermal behaviour of electrochemical cells by, 321
- Lithium  
 cycling of  $\beta$ -LiAl in organic electrolytes, effect of electrode contaminations and electrolyte additives, 193  
 electrochemical insertion of, in manganese dioxide, 141  
 -iodine cells, improvement in discharge rate and low temperature characteristics of, 173  
 -graphitic oxide cells Part II high specific surface area graphitic oxide as cathode material for lithium batteries, 99  
 layered AMO<sub>2</sub> compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of the deintercalation of, 231  
 Li/CuO cell, electrochemical behavior of CuO in a, influence of preparation conditions on, 269  
 -molybdenum disulfide batteries, rate limiting mechanisms in, 201  
 nonaqueous cells, electrochemistry of anatase titanium dioxide in, 153  
 organic solvent cells, characteristics of amorphous chromium oxide as a cathode for, 215  
 and phthalocyanine, kinetic studies of the electrochemical reaction between, 71  
 Raman spectroscopic study of LiAlCl<sub>4</sub>/SOCl<sub>2</sub>/SO<sub>2</sub> systems, 77  
 -vanadium pentoxide cell, an improved, and comparison with a lithium-thionyl chloride cell, 135
- Lithium batteries  
 ageing of rechargeable, 57  
 electrolyte solutions for, properties and structures of, 39  
 for extended-life continuous-operation applications, preliminary evaluation of, 167  
 general discussion, Second International Meeting on, Paris, April 27, 1984, 259  
 graphitic oxide as cathode material for, high specific surface area, 99  
 metal sulphides as cathodes in primary, electrochemical behaviour of, 65  
 polyacetylene electrodes for non-aqueous, 3  
 primary, in Europe, an industrial and commercial fact, 251  
 U S A , an assessment, 247
- Lithium battery technology  
 in Japan, the trend of, 255

- secondary, recent developments in, 179
- Lithium borophosphate  
vitreous electrolytes, 87
- Lithium cells  
capacity-cycle life behaviour in secondary, 53  
elective replacement indicator for implantable, 83  
 $V_6O_{13}$  as cathode material for, 235
- Lithium electrodes  
the a c response of, in thionyl chloride solutions, 123  
passivating films on, an approach by means of electrode impedance spectroscopy, 45
- Lithium ion conductors  
solid, for battery applications, 105
- Lithium salts  
cationic transport numbers in polyether-based networks containing, 27
- Manganese dioxide  
electrochemical insertion of lithium in, 141
- Metal sulphides  
as cathodes in primary lithium batteries, electrochemical behaviour of, 65
- Molybdenum dichalcogenides  
in aprotic organic electrolyte solution, cycling behaviour of, 223
- Molybdenum disulfide  
lithium-, batteries, rate limiting mechanisms in, 201
- Nickel  
protection of sealed Ni-Cd cells from cell voltage reversal, 285
- Organic electrolytes  
cycling of  $\beta$ -LiAl in, effect of electrode contaminations and electrolyte additives, 193  
electrochemical characteristics of polyacetylene in, 31
- Oxygen ion conduction  
in pure and yttria-doped barium cerate, 295
- Passivating films  
on lithium electrodes, an approach by means of electrode impedance spectroscopy, 45
- Phthalocyanine  
electrochemical reaction between lithium and, kinetic studies of the, 71
- Polyacetylene  
in organic electrolytes, electrochemical characteristics of, 31
- Polyacetylene electrodes  
for non-aqueous lithium batteries, 3
- Polyether-based networks  
containing lithium salts, cationic transport numbers in, 27
- Poly(ethylene oxide) electrolytes  
for operation at near room temperature, 13
- Polymers  
conductive, new tools and materials for electrochemistry, 11
- Polymer electrolyte  
batteries, behavior of, at 80 - 100 °C and near room temperature, 23
- Polysulfides  
electrochemical behaviour of, in tetrahydrofuran, 129
- Raman spectroscopic study  
of  $LiAlCl_4/SOCl_2/SO_2$  systems, 77
- Sodium  
layered  $AMO_2$  compounds (A = Li or Na, M = Cr, Co or Fe), electrochemical aspects of the deintercalation of, 231
- Stainless steel electrodes  
the a c response of, in thionyl chloride solutions, 123
- Tetrahydrofuran  
electrochemical behavior of polysulfides in, 129
- Thermal behavior  
of electrochemical cells by liquid crystal display, 321
- Thermopassivation  
of the positive lead-acid battery electrode, Part 3 Thermopassivation of smooth  $PbO_2$  electrodes, 277
- Thionyl chloride cell  
calcium/ $Ca(AlCl_4)_2$ -, effect of temperature and cell parameters on performance, 93  
a lithium-, an improved lithium-vanadium pentoxide cell and comparison with, 135

**Thionyl chloride solutions**

the a c response of lithium, stainless steel, and porous carbon electrodes in, 123

**Titanium dioxide**

electrochemistry of anatase, in lithium nonaqueous cells, 153

**Vanadium**

$V_6O_{13}$  as cathode material for lithium cells, 235

**Vanadium pentoxide**

an improved lithium-, cell and comparison with a lithium-thionyl chloride cell, 135